

LED LAMP

SPECIFICATIONS

Feit Electric's 18-watt Ballast Bypass (Type B) Non-dimmable Linear LED Tubes replace T8 and T12 fluorescent tubes. They require direct wiring by bypassing the existing ballast for efficient operation and less maintenance over time. Choose from four white light options to have the right light for any job. Each tube provides bright 1800-lumen light for garages, offices, and hospitality applications. T4815/4CCT/B/LED/10 light tubes offer flicker-free instant-on illumination with no warm-up time. They are mercury-free and shatter-resistant, for easy disposal. Lower heat emission extends the life of the tube and ends do not turn black or burn with age. The estimated energy cost is only \$2.17 per year, saving energy over equivalent fluorescents. Switch to LED linear lights and get up to 50,000 hours of life. That's 45.7 years of superior light with 3 hours of daily use.

Ideal For

General Purpose and Task Lighting

Benefits

- Ballast bypass installation requires direct wiring for longer installation time, but more efficient operation and less maintenance over time
- Shatter-resistant and mercury-free, no special disposal is required
- Flicker-free, instant ON illumination at full brightness
- 3000K, 4000K, 5000K, or 6500K, superior light quality with accurate color rendering (CRI: 80)
- LED technology offers more lumens per watt, saving energy over fluorescents and costing only \$2.17/year



Specifications

Item Number	Input Power (Watts)	Incandescent Equiv. (Watts)	Color Temperature
T4815/4CCT/B/LED/10	18	32	3000 4000 5000 6500 °K (Selectable)
Annual Energy Cost	Life Hours / Years	Energy Efficiency	Voltage
\$2.17 (Est.)	50000 / 45.7	Up to 43.8%	120-277
CRI	Shape	Base	Finish
80	T8 (Tubular)	G13 (Bi-Pin)	White
Dimmable	Weights and Measures		
NO	47.8 in. (Length) / 1.1 in. (Diameter) / 0.5 oz. (Weight)		