



Product Specifications: Polyester Collection		
CATEGORY	STANDARD	METRIC
Dimensions:	2' x 2' (Nominal)	603mm x 603mm
Gauge:	0.35"	9mm
Style:	Square Edge	
Installation System:	Install as a lay-in ceiling tile (24" x 24" grid system) or as a Stuck-On (gridless) ceiling or wall tile. Always use TopTile™ Ceiling Tile Adhesive 6518 for gridless installations.	
Pieces / Carton:	10	
Coverage / Carton:	40 Sq. Ft. (Nominal)	3.63 Sq. M.
Weight / Carton:	10 lbs	4.5 kg
Cartons / Pallet:	Not Applicable (Floor Loaded)	
Pallets / Container:	Not Applicable (Floor Loaded)	
Cartons / Container:	1,200	
Container Size:	40' GP	
Coverage / Container:	48,000 Sq.Ft. (Nominal)	4,356 Sq.M.
Commercial Warranty:	10-Years Limited	
Residential Warranty:	15-Years Limited	

ASTM and Other Test Data	
TEST	RESULTS
ASTM C423 (Sound Absorption):	Lay-in/Grid Installation System (Ceiling): NRC 0.75 Stuck-On/Adhesive Installation System (Ceiling): NRC 0.30
ASTM E84 (Surface Burning Characteristics):	Class: A
ASTM D5116 (Air Quality Standards):	Meets Highest Air Quality Standards
ASTM D6329 (Microbial Resistance):	Resistant to Mold and Microbial Growth as validated by the GREENGUARD Environmental Institute

09.16.2014





Product Specifications: Stuck-On Polyester Collection		
CATEGORY	STANDARD	METRIC
Dimensions:	2' x 2' (Nominal)	603mm x 603mm
Gauge:	0.35"	9mm
Style:	Beveled Edge	
Installation System:	Use TopTile™ Ceiling Tile Adhesive 6518	
Pieces / Carton:	10	
Coverage / Carton:	40 Sq. Ft. (Nominal)	3.63 Sq. M.
Weight / Carton:	17 lbs	7.7 kg
Cartons / Pallet:	Not Applicable (Floor Loaded)	
Pallets / Container:	Not Applicable (Floor Loaded)	
Cartons / Container:	1,200	
Container Size:	40' GP	
Coverage / Container:	48,000 Sq.Ft. (Nominal)	4,356 Sq.M.
Commercial Warranty:	35-Years Limited	
Residential Warranty:	Lifetime Limited	

ASTM and Other Test Data	
TEST	RESULTS
ASTM C423 (Sound Absorption):	Stuck-On/Adhesive Installation System (Ceiling): NRC 0.30
ASTM E84 (Surface Burning Characteristics):	Class: A
ASTM D5116 (Air Quality Standards):	Meets Highest Air Quality Standards
ASTM D6329 (Microbial Resistance):	Resistant to Mold and Microbial Growth as validated by the GREENGUARD Environmental Institute

09.16.2014

