Safety Data Sheet



Revision Number: 002.1 Issue date: 05/17/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: GE Supreme Silicone Kitchen & Bath IDH number: 2764352

Projects

Product type/use: Silicone sealant **Restriction of Use:** None identified

Restriction of Use: None identified Company address:

Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

WARNING: MAY CAUSE AN ALLERGIC SKIN REACTION.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2

PICTOGRAM(S)



Precautionary Statements

IDH number: 2764352

Response:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing dust or fumes. Contaminated work clothing should not be

allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.

IF ON SKIN: Wash with plenty of water. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	>= 10 - <= 20
octamethylcyclotetrasiloxane	556-67-2	>= 1 - <= 5
1,1,1,3,3,3-Hexamethyldisilazane	999-97-3	>= 1 - <= 5
Trimethoxy(methyl)silane	1185-55-3	>= 1 - <= 5

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If not breathing, give artificial respiration. If breathing is difficult, oxygen

should be administered by qualified personnel. Move to fresh air. If symptoms

persist, seek medical advice.

Skin contact: Wipe off with paper towel or cloth. Rinse with running water and soap.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse. Seek medical attention

immediately.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Seek medical attention immediately.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Seek medical

attention immediately.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat. In case of fire, keep containers cool with water spray.

Hazardous combustion products: Oxides of carbon. Oxides of silicon. Formaldehyde. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear appropriate personal protective equipment.

Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed

container for disposal.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Vapours should be extracted to avoid

inhalation. Avoid contact with eyes, skin and clothing. Do not wear contact lenses. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Wash thoroughly after handling. See Section 8 of the SDS for Personal Protective

Equipment. Keep container closed.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

IDH number: 2764352

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silane, dichlorodimethyl-, reaction products with silica	None	0.8 mg/m3 TWA 20 MPPCF TWA	None	None
octamethylcyclotetrasiloxane	None	None	10 ppm TWA	None
1,1,1,3,3,3-Hexamethyldisilazane			50 ppm STEL 10 ppm TWA	None
Trimethoxy(methyl)silane	None	None	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

solid Physical state: Color: Colorless Odor: amine-like Odor threshold: Not available. Not available. pH: Vapor pressure: Not available. Boiling point/range: Not available. Not available. Melting point/ range: Vapor density: Not available. Flash point: Not available. Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Evaporation rate: Not available. Solubility in water: Not available. Partition coefficient (n-octanol/water): Not available.

VOC content: 2.8 %; 33 g/l (by weight, calculated using CARB method; g/L less water, less

exempts calculated using SCAQMD method)

Viscosity: Not available.

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Oxides of silicon. Formaldehyde.

Incompatible materials: Acids and bases. Oxidizing agents. Amines.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight.

Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

IDH number: 2764352 Product name: GE Supreme Silicone Kitchen & Bath Projects

Potential Health Effects/Symptoms

Inhalation: When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may

form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible

limit.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: May cause eye irritation.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Silane, dichlorodimethyl-, reaction products with silica	None	No Target Organs	
octamethylcyclotetrasiloxane	Oral LD50 (Rat) = > 4,800 mg/kg Dermal LD50 (Rat) = > 2,000 mg/kg Dermal LD50 (Rabbit) = > 4,640 mg/kg Inhalation LC50 (Rat, 4 h) = 36 mg/l	Irritant	
1,1,1,3,3,3-Hexamethyldisilazane	Oral LD50 (Rat) = 847 mg/kg Oral LD50 (Rabbit) = 1,100 mg/kg Oral LD50 (Mouse) = 850 mg/kg Inhalation LC50 (Rat, 4 h) = 8,700 mg/m3 Inhalation LC50 (Rat, 4 h) = 10.3 mg/l	Irritant	
Trimethoxy(methyl)silane	Inhalation LC50 (Rat, 4 h) = > 26000 ppm	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silane, dichlorodimethyl-, reaction products with silica	No	No	No
octamethylcyclotetrasiloxane	No	No	No
1,1,1,3,3,3-Hexamethyldisilazane	No	No	No
Trimethoxy(methyl)silane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (octamethylcyclotetrasiloxane)

Hazard class or division: 9
Identification number: UN 3077
Packing group: III

IDH number: 2764352 Product name: GE Supreme Silicone Kitchen & Bath Projects

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(octamethylcyclotetrasiloxane)

Hazard class or division: Identification number:

Identification number: UN 3077
Packing group: III

Marine pollutant: octamethylcyclotetrasiloxane

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: Solvent (CAS# 556-67-2).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Delayed Health
None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

Canada Regulatory Information

IDH number: 2764352

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 9

Prepared by: Product Safety and Regulatory Affairs

Issue date: 05/17/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.