

D7100-2 Series Fiberglass Multi Section Extension Ladders



The D7100-2 extension ladders boast a duty rating of 375 lbs and feature the exclusive ALFLO® rung joint that guarantees TWIST-PROOF® performance. External guides at top of base section help secure the interlocking siderails. Pre-pierced holes at the top of the fly section allow for easy field installation of accessories. The plate and rung assembly are riveted at four points to each side rail. The TRACTION-TRED® D rungs are slip resistant and the durable rail shield and shoe bracket protects the rail from damage. (38 ft & 40 ft versions rated at 300 lbs and do not have interlocking rails)

Features

- Alflo rung joint for Twist-Proof performance
- Base section may be used as a single ladder
- Electrically non-conductive side rails
- Guides at top of base section
- Guides on bottom of fly section
- Interlocking side rails
- Mar-resistant molded end caps
- Plate and rung assembly to allow for rung replacement
- Rail shield and shoe bracket protects rail
- Rope and pulley system
- Rope clamp ties rope to rung
- Rugged gravity spring locks
- Shoe with slip-resistant pad and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Load Capacity	Type
D7116-2 	16 ft	16 ft	13 ft	13 ft	375 lbs	Type IAA Duty Rating
D7120-2	20 ft	19 ft	17 ft	17 ft	375 lbs	Type IAA Duty Rating
D7124-2	24 ft	23 ft	21 ft	21 ft	375 lbs	Type IAA Duty Rating
D7128-2	28 ft	27 ft	25 ft	25 ft	375 lbs	Type IAA Duty Rating
D7132-2	32 ft	31 ft	29 ft	29 ft	375 lbs	Type IAA Duty Rating
D7136-2	36 ft	34 ft	32 ft	32 ft	300 lbs	Type IA Duty Rating
D7140-2	40 ft	37 ft	35 ft	35 ft	300 lbs	Type IA Duty Rating