



ARTISAN®

Paver Cleaner

DESCRIPTION

Artisan® Paver Cleaner is a newly developed product for cleaning and maintaining most concrete and clay masonry surfaces. This product replaces conventional mineral and organic acids, which are too aggressive for the surface being cleaned, as well as for the applicator. It is a non-fuming, phosphate free product that is 2 to 10 times more effective than other acids when dissolving salts and other common contaminants, without the hazards that are inherent with commonly used acids. Artisan also contains an inhibitor that minimizes iron staining and a special surfactant that provides superior detergency properties. The surfactant helps this product penetrate the surface aids with the removal of light grease and oil stains. It does not contain any hydrochloric, hydrofluoric, bleach, abrasives, caustic, mineral acids or petroleum distillates.

USES

Use Artisan to remove stains, stubborn efflorescence and surface discolorations that accumulate throughout the winter and during in-season use. Artisan can be safely used on pavers, brick, stamped concrete, exposed aggregate, block, stucco and other similar surfaces. Artisan will remove light efflorescence, rust and stains, without etching, pitting or damaging the surface, mortar joints or grout.

PREPARATION

For best results, test a solution before general use. It is imperative that a test be done, and allowed to dry, prior to general use. Protect all surfaces this product is not intended. Do not use on any polished or honed stone, metal and painted surfaces. Keep away from plants and vegetation.

EQUIPMENT

Apply using acid resistant brushes. Only apply with equipment made of polyethylene or polypropylene. Do not mix, use or apply with any metal buckets or applicators.

PROPERTIES

| | |
|-------------|--------------|
| Appearance | Amber liquid |
| Flash Point | N/A |
| pH | 1 |

APPLICATION

Artisan Paver Cleaner can be used full strength for heavy duty cleaning or diluted with equal parts water for light duty cleaning. Apply solution onto a dry surface and let solution stand for approximately 5-10 minutes, depending on surface and contaminants. After allowing dwell time, agitate and rinse thoroughly or power wash. For surfaces being sealed, neutralize with a mild solution of Artisan Grease & Oil Emulsifier.

PACKAGED

Artisan Paver Cleaner is available in gallons (4/case), 5 gallon pails and 55 gallon drums.

DISPOSAL

Use completely or dispose of properly. Local requirements vary.

STORAGE AND SHELF LIFE

Store in original closed containers, in a cool, dry place. Store away from alkaline products and oxidizers.

TRANSPORTATION

Not regulated by the U.S. Department of Transportation for ground shipments.





SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Efflorescence Remover causes burns to the eyes. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

STORAGE AND SHELF LIFE

Store in original closed containers. Heat reduces the shelf life. Store in a cool, dry place. Store away from alkaline products and oxidizers.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, nor can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

