



Touch Up Paint Instructions:



Paint Storage:

- ✓ Keep Away from children and animals
- ✓ Ensure the lids are tightly closed to prevent spillage.
- ✓ Do not allow paints/stains to freeze.

Application instructions:

- ✓ As needed, fill any screw/nail wholes, miter joints or other openings with wood filler or bondo. Allow for the filler to completely dry before moving to the next step.
- ✓ Ensure the paint/stain lids are sealed completely. Shake containers well to ensure a good color mix.
- ✓ Each color panel has it's on unique set up paints/stains. Some more than others. At a minimum you will receive two bottles. The first bottle is the base color, which will be labeled as such. The secondary bottle(s) will the be actual color tint/stain. Each bottle with be marked with the color.
- ✓ Apply the base using a standard paint brush. Paint only the area that is needing touchup. Allow for the paint to completely dry before moving to the next step.
- ✓ Once the base is completely dry, identify which color tint is needed to match the surrounding area of the panel. Normally just one color will be needed per area. Using a small brush, apply the stain over the newly painted base. Once applied, lightly wipe the stain with a rag until you achieve the desired effect. Allow the stain to completely dry.

Helpful Hints:

- ✓ Always use a clean dry brush when applying stains.
- ✓ Avoid applying stain over existing stain, this can cause the area to darken.

Tritan BP
866-771-2345
Sales@tritanbp.com
www.tritanbp.com