

KILZ® UPSHOT® INTERIOR OIL-BASE PRIMER



- Oil base primer/sealer/stainblocker in convenient to use aerosol spray
- Interior use; ideal for ceilings
- Spot primer to seal surfaces
- Blocks/Seals heavy stains including water stains, smoke and tannin
- Seals pet, smoke and food odors
- Tinted to match most aged and acoustical ceilings
- Vertical spray tip makes overhead application easy



Mineral Spirits
Clean-Up



14 - 19 sq.ft*



1 Hr Dry Time to Recoat**



Protect from
Freezing

DESCRIPTION

KILZ® Upshot® aerosol primer is an interior oil-base stainblocker with a unique vertical spray tip for overhead application. It's great for blocking ceiling stains like water, smoke and grease. Easy to use and apply, the convenient 10 fluid ounce aerosol is ideal for spot application to block water stains on ceilings prior to applying the topcoat. It is also pre-tinted to match most aged acoustical ceiling tiles.

Typical Uses

- Ideal for ceilings
- Blocks stains caused by water, smoke, tannin, ink, pencil, felt marker and grease
- Use on interior surfaces including wood, drywall, plaster, paneling, wallpaper, masonry, brick and painted metal
- Seals pet and smoke odors

Product Benefits

- Tinted to match most aged and acoustical ceilings
- Fast and easy vertical spray
- Interior use
- Oil-base primer
- Recoat in 1 hour
- Topcoat with water or oil-base paint

Product Benefits (Aerosol)

- Ideal for spot painting or small, focused application projects
- Equipped with wide comfort tip
- Anti-clog spray tip
- Covers up to 19 square feet total area
- Lightweight (less than 1 lbs)

SURFACE PREPARATION (The following steps are recommended for product performance)

- All surfaces must be clean, dry and free of dust, grease, wax, peeling paint, mold, mildew, wallpaper paste. If washing is necessary, use a non-soapy detergent or TSP substitute. Rinse well and allow to dry.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.*
***WARNING** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.
- Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.*

APPLICATION

- Eye protection is recommended.
- For best results, use at room temperature. Cover adjacent areas to protect from overspray.
- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use. Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted. Two to three thin coats produce best results.
- Topcoat with water or oil-based paint after 60 minutes. NOTE: On some surfaces, spot priming may cause a non-uniform appearance in the final coat. To avoid this, prime the entire surface.

CLEAN-UP & DISPOSAL

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean. Do not stick pins or wire into can opening.
- Replace nozzle with valve opening pointed away from you. Clean fresh overspray with mineral spirits or paint thinner. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.
- Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.



KILZ® UPSHOT® INTERIOR OIL-BASE PRIMER



- Oil base primer/sealer/stainblocker in convenient to use aerosol spray
- Interior use; ideal for ceilings
- Spot primer to seal surfaces
- Blocks/Seals heavy stains including water stains, smoke and tannin
- Seals pet, smoke and food odors
- Tinted to match most aged and acoustical ceilings
- Vertical spray tip makes overhead application easy



Mineral Spirits
Clean-Up



14 - 19 sq.ft*



1 Hr Dry Time to Recoat**



Protect from
Freezing

VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), **DO NOT** use this product unless you can achieve cross-ventilation by opening windows and doors during application and drying. **CONTAINS PETROLEUM DISTILLATES AND ACETONE. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **NOTICE:** Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air, and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE:** Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Prolonged exposure to sun may cause bursting. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY



WARNING

Cancer and Reproductive Harm
www.P65Warnings.ca.gov

LIMITED WARRANTY: Masterchem Industries LLC warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. If this product is found to be defective upon inspection by its representative, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Note to residents of the State of New Jersey: The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call: 1-866-774-6371, or email: techservice@masterchem.com. Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty

* Depending on the surface texture, porosity and application method.

**At 77°F (25°C), 50% RH. Longer dry time may be required in cooler temperatures and in higher humidity.

Maximum V.O.C.: 60% By Weight

Maximum Product Weighted MIR: 0.7

