

CHALK

PINTY[®]
PLUS
CHALK
FINISH
SPRAY PAINT

Chalk finish spray paint



CHALK

Chalk finish spray paint for decoration purposes.
Ultra matt finish with a velvety appearance.

Perfect for any surface including expanded polystyrene. It can be washed with soap and water within the first 15 minutes. Maximum coverage and fast drying. **Water-based formulated**, it is more respectful of the environment.

APPLICATIONS:

Allows decorating easily multiple surfaces in order to give a vintage touch to your objects. Ideal on wood, melamine, canvas, iron, plastic, cardboard and even on glass. As it does not contain aggressive solvents, it does not attack the expanded polystyrene (Polystyrene). In order to achieve a smooth finish surface, it is recommended to apply several thin layers, letting them dry and sanding them lightly until you obtain the desired texture.

TECHNICAL CHARACTERISTICS:

Performance 520/400ml = 2 m²

Drying time in 20 minutes, total drying in 1 hour.

Repainted with the same paint 1 hour.

Repainted with other paint 24 hours.



CK789
Cream



CK800
Beige
Sahara



CK801
Mustard



CK802
Peach



CK793
Rose
garden



CK792
Pink
petal



CK804
Red
velvet



CK818
Glamour
red



CK796
Pale
Turquoise



CK797
Turquoise



CK795
Blue
indigo



CK794
Mint
green



CK803
Oliva
vintage



CK791
Stone



CK798
Ash
grey



CK817
London
grey



CK790
Chestnut
Brown



CK799
Black
plumb



CK788
Broken
white

HOW TO APPLY:

The surface to be painted should be **clean**, dry and free of any contaminants. **Shake** the can vigorously during 1 minute. **Spray** from a distance of 25 cm., applying **thin and quick layers**, first horizontally and then vertically. To achieve a uniform coverage and avoid drippings, it is advisable to apply several thin layers instead of a thick one.

Once the operation is completed **reverse the can and push the nozzle until only gas comes out** in order to prevent nozzle clogging.

RECOMMENDATIONS:

Spray the product using the can in a vertical position. Once the surface is dry, wipe to remove the excess of chalk dust. Wait 5 minutes between layers. Only when the surface is dry to the touch, you can apply the next layer, removing the dust in excess before each application. In the case the nozzle is obdurate, clean the dispenser with a wiper and continue to paint normally.

If a layer of varnish is needed, the most indicated one is a water-based Varnish either within our **Pintyplus Aqua** or our **Pintyplus Art&craft** ranges. If you want to paint a **plastic surface**, we recommend you to prepare the object with a layer of our **Pintyplus Tech Plastic Primer**. This way, you achieve a better anchorage of the chalk paint.