

OPERATING

CUTTING INSTRUCTIONS

REPLACING SPOOL / CLEARING JAMS AND TANGLED LINES

From time to time, especially when cutting thick or stocky weeds, the line feeding hub may become clogged with sap or other material and the line will become jammed as a result. To clear the jam, follow these steps.

- Turn off the trimmer and unplug from power source.
- Press the release tabs on the line spool retainer and remove the cover by pulling it straight off.
- Lift the spool of nylon line out of the hub and clear any broken line or cutting debris from the spool area.
- In case of jams and tangled line, unwrap about one foot (30cm) of line to ensure that it is undamaged. If it is OK, rewind it and insert the line ends through the eyelets in the spool hub.
- Press the spool down GENTLY and rotate it until you feel it drop into place. (When in place, the spool will freely turn a few degrees left and right.)
- Snap the spool retainer back on, insert the cord into the outlet and turn the tool on. In a few seconds or less you'll hear the line being cut automatically to the proper length.

REWINDING SPOOL FROM BULK LINE (USE ONLY .065" DIAMETER LINE)

Bulk line for your trimmer/edger is available at extra cost from your local dealer or service center. To install bulk line, follow these steps:

- Turn off the trimmer and unplug from the power source.
- Remove the spool assembly from the trimmer. To do so, hold the outer ribbed part of the assembly with one hand, while pushing down and turning the spool head to unlock it with the other hand.
- Remove any existing line from the spool.
- Using approximately 9 ft. of .065 replacement line, loop the line into 2 equal lengths. Insert looped center into slot of spool.
- Wind the line tightly around the spool. The line is wound in the direction of the arrow on the spool. Tightly wind it until there is about 6" of line left.
- Lock each end of line into opposite holding slot.
- Thread each end of the line through the upper and lower eyelets of the white plastic cover.
- Insert the line through each eyelet in the spool carrier and slide the spool into it.
- Insert the spring, assemble the spool and spool retainer back onto the trimmer. To do so, push the head on and turn it clockwise until it locks.
- Plug trimmer back in and in a few seconds or less you'll hear the line being cut automatically to the proper length.

