



S-761

# Seam Adhesive

for sheet floors

## Unir Pisos

para los suelos



**Easy as 1-2-3!** // **¡Fácil como 1-2-3!**

- Strong bond for flooring seams
- Easy installation, easy clean up
- Enlace fuerte para solar costuras
- Fácil instalación y limpiar

8 fl. oz. (236 ml)

**USE FOR:** Seaming sheet floors.

**INSTALLATION INSTRUCTIONS:**

- 1) Overlap floor and double-cut to create a perfectly aligned seam.
- 2) Peel back one side of the floor and remove excess pieces.
- 3) Apply a 1/8" bead of S-761 along the seam edge and the floor.
- 4) Tuck other side into the seam, allowing adhesive to ooze up the seam to the top of the floor.
- 5) Wipe up excess adhesive with a clean, white cloth dampened with water.
- 6) Roll seam with a roller, rolling pin, or other firm, cylindrical object, such as a roll of masking tape.
- 7) Remove excess wet adhesive with a clean, damp cloth. Do not use solvent or high pH cleaner.

**CAUTION: IRRITANT.** Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed.

**KEEP OUT OF REACH OF CHILDREN.**

**CAUTION:** Initially there may be a potential adverse impact on indoor air quality within the general work area during the installation process. During the installation process, adequate ventilation of the work area should be maintained without causing the entry of contaminants to other parts of building. Persons who are sensitive to odors and/or chemicals should avoid the work area.

**NOTE:** Do not reuse container. Dispose of container and adhesive residue in accordance with federal, provincial and local waste disposal regulations. Do not flush adhesive down drains.

**WARRANTY.** This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective materials called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty details or to obtain an MSDS for the product, contact ARMSTRONG Customer service at 800 233 3823.

© 2012 AWI Licensing Company

Made in the USA for/Hecho en loss EE.UU. para Armstrong World Industries, Inc., Lancaster, PA 17603 800 233 3823 armstrong.com 00761603 612

**SPANISH IN THIS AREA.**

