

OIL-BASE INTERIOR/EXTERIOR ENAMEL

- Available in Satin & Semi-Gloss Finishes
- Excellent Flow and Leveling
- Hard, Durable Finish
- Easy Stain Removal
- Resists Household Chemicals
- Mildew-Resistant Paint Finish
- For Doors, Trim, Molding & Cabinetry

No. 3800 White Base*
No. 3830 Deep Base*
No. 7800 White Base*
No. 7830 Deep Base*

*Available in select stores

2 Coats Recommended for Optimal Durability

Spread Rate:
Rough 350–400 Sq. Ft.
Smooth 500–550 Sq. Ft.

Dry Time:
2–3 Hr. Dry to Touch
24 Hr. Recoat

Clean-Up: Mineral Spirits

WHITE BASE: *READY TO USE OR ADD TINTING COLORANTS.*
DEEP BASE: *DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.*
PROTECT FROM FREEZING.

PREPARATION

(Proper surface preparation is required.) All surfaces must be clean, sound, dry and free of any dirt, oil and grease stains. Remove mildew stains with a mildew stain removing product.
Interior/Exterior Wood Trim, Door & Cabinetry: Remove all loose and peeling paint; caulk and repair imperfections. Sand all wood surfaces in the direction of the wood grain to the desired smoothness. Remove all dust from sanded surfaces with a damp, lint-free cloth. **Uncoated Exterior Wood:** Use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner. **Interior/Exterior Concrete & Masonry:** Allow new stucco, plaster and masonry to cure for 30 days. Use a concrete & masonry degreaser & cleaner to clean and prepare the surface. Powerwash to remove chalk on exterior surfaces. **Interior/Exterior Metal:** Etch galvanized metal. Follow all label instructions.

PRIME

For all exterior surfaces, use a product such as BEHR® Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436. For all interior surfaces, use a product such as BEHR Kitchen, Bath & Trim Interior Stain-Blocking Primer & Sealer No. 75. Follow all label instructions.

APPLICATION

- DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity.
- Use adequate ventilation during application and drying process. Certain colors may require two or more coats to achieve complete hide and coverage.
- Use product when air and surface temperature are 40–90˚ F (4–32˚ C).
- Apply a thin coat using a high quality china bristle brush, high quality
- 1/4"–1/2" nap roller or an airless sprayer (.013"–.015" spray tip, 60 mesh filter).
- NOTE: If touch-up is necessary, same application method is recommended

DRY TIME

Longer dry time required in cooler temperatures and higher humidity or with darker colors. Wait 30 days before rinsing or cleaning the surface with a mild, non-abrasive detergent.

DISPOSAL

For disposal of empty containers and unused product, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice, and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY For one year from the date that the product is received by the original consumer purchaser or their authorized representative (installation contractor, etc.), Behr Process LLC warrants to the original consumer purchaser, (1) that the product meets Behr Process LLC's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date that the product is received by the original consumer purchaser or their authorized representative (installation contractor, etc.), Behr Process LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warrant, negligence, strict liability, or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. To obtain warranty service, call 1-800-854-0133. Behr Process LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-854-0133.

©2025 Behr Process LLC
Santa Ana, CA 92705 U.S.A. • behr.com
VOC < 380 g/L • REV. 12/25

⚠ **WARNING:** This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

IMPORTANT STORAGE AND DISPOSAL: **DANGER** Rags, steel wool and waste soaked with this BEHR PREMIUM OIL-BASED ENAMEL may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross-ventilation by opening windows and doors during application and drying. **CAUSES EYE, NOSE, THROAT AND SKIN IRRITATION.** Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. May affect the brain or nervous system causing dizziness, headache or nausea. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Follow respirator manufacturer's directions for respirator use. Avoid contact with clothing. Wash thoroughly after handling and before smoking and eating. NOTICE: Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **VAPORS MAY CAUSE FLASH FIRE.** Keep away from sparks, heat and open flame. Do not smoke. Vapors are heavier than air, and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. Close container after each use. **FIRST AID:** If swallowed, do not induce vomiting. Call a physician immediately. If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.