

PERMA PATCH

DESCRIPTION (Speed, Perfection and Longevity)	<p>Patented PVC fiber composite material patch that is 8 x 8", .014" thick and comes in retail 2-pack case of 50 packs which weights 8.6. Perma-Patch is also packaged in 10 per bag 10 bags per box that weigh 5.3 pounds and 10 per bag 50 bags per box that weight 26.5. A case of 500 bulk weighs 26.5.</p> <p>Perma-Patch is a drywall patch used for receptacle relocation, doorknob repair, furniture moving damage, ceiling light relocation and can light repair. Standard design patterns are imprinted on Perma-Patch for easy use. Perma-Patch makes repairs strong, fast and easy. Same high-tech composite material as Strait-Flex.</p>
ADVANTAGES	<ul style="list-style-type: none"> • Quickly repairs door knob damage to drywall • PVC fiber composite material is strong and will not soften or sag • Material is imprinted with designs of receptacle/ceiling/can light for easy adjustments • Makes receptacle, ceiling and can light relocation easy. • Material is not affected by water and damp conditions • Perma-Patch will not fuzz-up during sanding like competitive fiber glass-metal patches • Waterproof, rustproof
WARRANTY	<p>Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.</p>
DIRECTIONS	<ul style="list-style-type: none"> • Prepare surface by cleaning and lightly sanding area around receptacle. • Apply 1/4" of quick set or drywall compound directly to back of Perma Patch. • Flip over patch and position Perma Patch over center of repair and wipe down flat to wall using joint knife. • Immediately skim coat edges of patch and let dry. Compound that remains on back side of Perma Patch in damaged or mis-cut areas makes Perma Patch very rigid. • Apply second coat. Let dry and sand. Perma Patch will not fuzz up during sanding. One Perma Patch repairs holes up to six inches in diameter.
STORAGE	<p>Store in dry place protected from moisture</p>

Submittal Approvals:

Job Name:	
Contractor:	Date: