

The Toro Company

Chemwatch: 5351-42

Version No: 2.1.1.2 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Toro Flex Force Lithium Ion Battery (UN3480)	
Synonyms	Not Available	
Proper shipping name	Lithium ion batteries including lithium ion polymer batteries	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses Rechargeable battery. NOTE: Chemical materials are stored in sealed metal case. The toxic properties of the electrode materials are hazardous only if the materials are released by damaging the cell or if exposed to fire. The sealed battery is not hazardous in normal use. The chemical hazards are related to the leaked battery contents.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	The Toro Company
Address	8111 Lyndale Avenue South Bloomington MN 55420 United States
Telephone	+1 952 888 8801
Fax	Not Available
Website	Not Available
Email	Not Available

Emergency phone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

CHEMWATCH HAZARD RATINGS

	Min	Max	NFPA 704 diamond	
Flammability	2			
Toxicity	1			
Body Contact	3			
Reactivity	0		0 = Minimum	
Chronic	2		2 = Moderate 3 = High 4 = Extreme	Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)
	Classification	Flamm Categ	nable Solid Category 2, Skin Corrosion/Irritation	Category 1B, Serious Eye Damage Category 1, Specific target organ toxicity - repeated exposure
Label element	s			

Hazard pictogram(s)	
SIGNAL WORD	DANGER
Hazard statement(s)	
H228	Flammable solid.

Chemwatch Hazard Alert Code: 3

Issue Date: 05/13/2021 Print Date: 05/13/2021 L.GHS.USA.EN

Issue Date: 05/13/2021 Print Date: 05/13/2021

Toro Flex Force Lithium Ion Battery (UN3480)

H314	Causes severe skin burns and eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.

Precautionary statement(s) Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
Immediately call a POISON CENTER or doctor/physician.	
In case of fire: Use alcohol resistant foam or normal protein foam for extinction.	
Wash contaminated clothing before reuse.	
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		hermetically sealed case with
12190-79-3	50	lithium cobaltate
7782-42-5	30	graphite
21324-40-3	5	lithium fluorophosphate
Listed below		electrolyte solvent contents listed below*
96-49-1	1	ethylene carbonate*
108-32-7	1	propylene carbonate*
105-58-8	1	diethyl carbonate*
105-37-3	1	ethyl propionate*
7440-50-8	15	copper
7429-90-5	10	aluminium
24937-79-9	0.99	vinylidene fluoride homopolymer
12597-69-2	100	steel
7440-02-0	1	nickel

SECTION 4 FIRST-AID MEASURES

Description of first aid measures		
Eye Contact	 Generally not applicable. If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 	

Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	Remove patient to fresh air and seek medical attention.
Ingestion	 Not considered a normal route of entry. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit acrid smoke. May emit corrosive and poisonous fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid contact with skin and eyes. Place in suitable containers for disposal.
Major Spills	 Clean up all spills immediately. Wear protective clothing, safety glasses, dust mask, gloves. Secure load if safe to do so. Bundle/collect recoverable product. Use dry clean up procedures and avoid generating dust. Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Water may be used to prevent dusting. Collect remaining material in containers with covers for disposal. Flush spill area with water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling			
Safe handling	Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid physical damage to containers. Do not connect the positive terminal to the negative terminal with electrical wire or chain. Avoid polarity reverse connection when installing the battery to an instrument. Do not wet the battery with water, seawater or acid; or expose to strong oxidizer. Do not damage or remove the external tube. Keep the battery away from heat and fire. Do not disassemble or reconstruct the battery; or solder the battery directly. Do not give a mechanical shock or deform. Do not use		

	unauthorized charger or other charging method. Terminate charging when the charging process does not end within specified time.
Other information	 Keep dry. Store under cover. Protect containers against physical damage. Observe manufacturer's storage and handling recommendations contained within this SDS. Keep out of reach of children. Store out of direct sunlight Store away from incompatible materials.
Conditions for safe storage,	including any incompatibilities
Suitable container	Store in original containers.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

 INCO	CDICN	TDATA
 INGR	EVIEN	

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US ACGIH Threshold Limit Values (TLV)	lithium cobaltate	Cobalt and inorganic compounds, as Co	0.02 mg/m3	Not Available	Not Available	TLV® Basis: Asthma; pulm tunc; myocardial eff; BEI
US NIOSH Recommended Exposure Limits (RELs)	graphite	Black lead, Mineral carbon, Plumbago, Silver graphite, Stove black [Note: Also see specific listing for Graphite (synthetic).]	2.5 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z3	graphite	Graphite	15 mppcf	Not Available	Not Available	(Name ((Natural)))
US ACGIH Threshold Limit Values (TLV)	graphite	Graphite (all forms except graphite fibers)	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	graphite	Graphite, natural, respirable dust	Not Available	Not Available	Not Available	See Table Z-3
US NIOSH Recommended Exposure Limits (RELs)	copper	Copper metal dusts, Copper metal fumes	1 mg/m3	Not Available	Not Available	[*Note: The REL also applies to other copper compounds (as Cu) except Copper fume.]
US ACGIH Threshold Limit Values (TLV)	copper	Copper - Dusts and mists, as Cu	1 mg/m3	Not Available	Not Available	TLV® Basis: Irr; GI; metal fume fever; BEI
US ACGIH Threshold Limit Values (TLV)	copper	Copper - Fume, as Cu	0.2 mg/m3	Not Available	Not Available	TLV® Basis: Irr; GI; metal fume fever; BEI
US OSHA Permissible Exposure Levels (PELs) - Table Z1	copper	Copper: Dusts and mists (as Cu)	1 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	copper	Copper: Fume (as Cu)	0.1 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	aluminium	Aluminium, Aluminum metal, Aluminum powder, Elemental aluminum	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	aluminium	Aluminum metal and insoluble compounds	1 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium	Aluminum, metal (as Al): Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium	Aluminum, metal (as Al): Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	nickel	Nickel metal: Elemental nickel, Nickel catalyst	0.015 mg/m3	Not Available	Not Available	Ca See Appendix A [*Note: The REL does not apply to Nickel carbonyl.]
US ACGIH Threshold Limit Values (TLV)	nickel	Nickel and inorganic compounds including Nickel subsulfide, as Ni - Elemental	1.5 mg/m3	Not Available	Not Available	TLV® Basis: Dermatitis; pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nickel	Nickel, metal and insoluble compounds (as Ni)	1 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
graphite	Graphite; (Mineral carbon)	6 mg/m3	16 mg/m3	95 mg/m3
lithium fluorophosphate	Lithium hexafluorophosphate	7.5 mg/m3	83 mg/m3	500 mg/m3
ethylene carbonate	Glycol carbonate; (Ethylene carbonate)	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene carbonate	Propylene carbonate, 1,2-	3.3 mg/m3	37 mg/m3	220 mg/m3
diethyl carbonate	Diethyl carbonate	12 ppm	140 ppm	810 ppm
ethyl propionate	Ethyl propionate	6.3 ppm	69 ppm	410 ppm
copper	Copper	3 mg/m3	33 mg/m3	200 mg/m3
nickel	Nickel	4.5 mg/m3	50 mg/m3	99 mg/m3
Ingredient	Original IDLH	Revised IDLH		
lithium cobaltate	Not Available	Not Available		

graphite	1,250 mg/m3	Not Available
lithium fluorophosphate	Not Available	Not Available
ethylene carbonate	Not Available	Not Available
propylene carbonate	Not Available	Not Available
diethyl carbonate	Not Available	Not Available
ethyl propionate	Not Available	Not Available
copper	100 mg/m3	Not Available
aluminium	Not Available	Not Available
vinylidene fluoride homopolymer	Not Available	Not Available
steel	Not Available	Not Available
nickel	Not Available	Not Available

MATERIAL DATA

Exposure controls

Appropriate engineering controls	General exhaust is adequate under normal operating conditions.
Personal protection	
Eye and face protection	None under normal operating conditions. OTHERWISE: ► Safety glasses.
Skin protection	See Hand protection below
Hands/feet protection	None under normal operating conditions. OTHERWISE: ▶ Rubber Gloves
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

• Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Coloured solid article with no odour; insoluble in water.		
Physical state	Manufactured	Relative density (Water = 1)	Not Applicable
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable

Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Not normally a hazard due to physical form of product. Vapors or fumes may cause respiratory tract irritation.		
Ingestion	Considered an unlikely route of entry in commercial/industrial environments Ingestion may result in nausea, abdominal irritation, pain and vomiting		
Skin Contact	Not normally a hazard due to physical form of product. The electrolyte causes severe skin burns and irritation.		
Eye	Not normally a hazard due to physical form of product. The electrolyte causes eye irritation and damage.		
Chronic	Not normally a hazard due to physical form of product. The chemicals in this product are contained in a sealed case and exposure does not occur during normal handling and use.		
Toro Flex Force Lithium Ion	ΤΟΧΙΟΙΤΥ	IRRITATION	
Battery (UN3480)	Not Available	Not Available	
	тохісіту	IRRITATION	
lithium cobaltate	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available	
	Oral (rat) LD50: >5000 mg/kg ^[1]		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
graphite	Inhalation (rat) LC50: >2 mg/l4 h ^[1]	Not Available	
	Oral (rat) LD50: >2000 mg/kg ^[2]		
lithium fluorophosphate	TOXICITY	IRRITATION	
	Oral (rat) LD50: 50-300 mg/kg ^[1]	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 20 mg - mild	
ethylene carbonate	Oral (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]	
		Skin (rabbit): 660 mg - moderate	
		Skin: no adverse effect observed (not irritating) ^[1]	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye (rabbit): 60 mg - moderate	
propylene carbonate	Oral (rat) LD50: >5000 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]	
p. opylone our solidie		Skin (human): 100 mg/3d-l moderate	
		Skin (rabbit): 500 mg moderate	
		Skin: no adverse effect observed (not irritating) ^[1]	

	TOXICITY	IRRITATION
diethyl carbonate	Not Available	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
	ΤΟΧΙCITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
ethyl propionate	Oral (rat) LD50: >5000 mg/kg ^[1]	Skin (rabbit):500 mg/24h-moderate
		Skin: adverse effect observed (irritating) ^[1]
	ΤΟΧΙCITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
copper	Inhalation (rat) LC50: 0.733 mg/l4 h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: 300-500 mg/kg ^[1]	
aluminium	ΤΟΧΙΟΙΤΥ	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
vinylidene fluoride	ΤΟΧΙΟΙΤΥ	IRRITATION
homopolymer	Not Available	Not Available
	ΤΟΧΙΟΙΤΥ	IRRITATION
steel	Not Available	Not Available
	ΤΟΧΙΟΙΤΥ	IRRITATION
nickel	Oral (rat) LD50: 5000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substance	es - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified

data extracted from RTECS - Register of Toxic Effect of chemical Substances

ETHYLENE CARBONATE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermattis (nonallergic). This form of dermattis is often characterised by skin redenses (erythema) and swelling epidemis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidemis. Mammalian toxicity: Reliable acute toxicity tests are available on ethylene carbonate. Ethylene carbonate is practically nontoxic following acute oral exposure in a test that meets OECD and EPA test guidelines. Ethylene carbonate is rapidly metabolized to ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. for endpoints are carbonate is rapidly converted into ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rate, ethylene glycol proving administration to rats, ethylene carbonate is rapidly converted into ethylene glycol. Following gavage administration to rate, ethylene glycol proving administration and regover and the males and females and 50,000 ppm for famales, male and 26 females and 5000 pgkgday. No toxic effects were found in females, but increased mortality in vitro genotoxicity tests were conducted on ethylene glycol. The lowere

	 carely. Cardiovascular Effects. Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of oral ethylene glycol poisoning, which is 12-24 hours after acute exposure. The symptoms of cardiac involvement include tachycardia, ventricular galio and cardac enlargement. Ingestion of ethylene yhoic may also cause hypertension or hypotersion, which may progress to cardiogenic shock. Myocarditis has been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol. No may regress to cardiogenic shock. Nevertheless, circulatory disturbances are a rare occurrence, having been reported in only 6 of 36 severely poisoned cases. Therefore, it appears that acute exposure to high levels of ethylene glycol an cause serious cardiovascular effects in humans. The effects of a long ethylene glycol area causes around yorks, and adhorinal cramping and pain are common early effects of acute ethylene glycol ingestion. Acute effects of ethylene glycol ingestion in one patient included intermittent diarrhea and abdominal pain, which were attributed to mild colonic lischaemia; severe abdominal pain secondary to colonic stricture and perforation developed 3 months after ingestion, and histology of the resected cion showed birefingent crystals highly suggestive of oxalate deposition. Musculoskelatal Effects. Reported musculoskelatel effects in cases of acute ehylene glycol poisoning have included diffuse muscle tenderness and mysalipia associated with hyderia ehylene glycol ingestion in humans can be observed during the third stage of ethylene glycol loxicity 24-72 hours after acute exposur. The hallmark of renal acids is the prevence of humans to ethylene glycol provides explase in the liver have been observed at autops in cases of people whoid tell following acute ingestion of ethylene glycol. Other signs of nephrotoxicity can include tubular nell explase in the internet acute exposur. The hallmark o
	Cancer: No studies reduction in toetal body weight. Cancer: No studies were located regarding cancer effects in humans or animals after dermal exposure to ethylene glycol. Genotoxic Effects: Studies in humans have not addressed the genotoxic effects of ethylene glycol. However, available <i>in vivo</i> and <i>in vitro</i> laboratory studies provide consistently negative genotoxicity results for ethylene glycol.
PROPYLENE CARBONATE	Numerous adequate and reliable acute toxicity tests are available on propylene carbonate. Oral and dermal tests meet OECD and EPA test guidelines. Propylene carbonate is practically nontoxic following acute exposures; the oral LD50 is >.5000 mg/kg and the dermal LD50 is >.3000 mg/kg. No further testing is recommended. Subchronic studies (13- 14 weeks) of propylene carbonate by inhalation (aerosol) and oral (gavage) routes were conducted in rats according to current guidelines. The oral study indicated low systemic toxicity from propylene carbonate (NOAEL = 5000 mg/kg/day). In the inhalation study, no systemic toxicity was seen at concentrations up to 1000 mg/m ⁻ ; however, there was periocular irritation and swelling in a few males at 500 and 1000 mg/m3. A dermal carcinogenicity study in mice did not indicate tumorigenic potential or systemic toxicity from 2 years of exposure to propylene carbonate. No further testing is recommended. There is a negative Ames in vitro mutagenicity assay of propylene carbonate. A single intraperitoneal injection of 1666 mg/kg propylene carbonate did not induce an increase in micronuclei when examined after 30,48 and 72 hours. The mutagenicity battery is satisfactorily filled; no further mutagenicity testing is recommended. Gavage administration of propylene carbonate to pregnant rats days 6-15 of gestation resulted in systemic toxicity at doses of 3000 and 5000 mg/kg/day, including mortality (not seen in 13 week study of non-pregnant rats). The NOAEL for maternal toxicity was 1000 mg/kg/day. This indicates that pregnant rats are more susceptible to propylene carbonate than are non-pregnant rats. There were no significant differences in live litter size, average fetal weight, percentage of males, or malformed fetuses. No studies of the effect of propylene carbonate on reproduction are available. However, no adverse effects on testis, ovaries, or accessory sex organs were noted in rats following oral or inhalation of propylene carbonate for 13 weeks. Therefore, repr
DIETHYL CARBONATE	Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis). Equivocal tumorigen by RTECS criteria
COPPER	for copper and its compounds (typically copper chloride): Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs. No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation. Repeat dose toxicity : In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague- Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 1.3 mg/kg bw/day for male and female rats, respectively. No deaths were observed in male rats. One treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach wais increased in a

	chromosome aberration in Chinese hamster lung (CHL) cells showed that copper monochloride induced structural and numerical aberrations at the concentration of 50, 70 and 100 ug/mL without S9 mix. In the presence of the metabolic activation system, significant increases of structural aberrations were observed at 50 and 70 ug/mL and significant increases of numerical aberrations were observed at 70 ug/mL. In an in vivo mammalian erythrocyte micronucleus assay, all animals dosed (15 - 60 mg/kg bw) with copper monochloride exhibited similar PCE/(PCE+NCE) ratios and MNPCE frequencies compared to those of the negative control animals. Therefore copper monochloride is not an in vivo mutagen. Carcinogenicity: there was insufficient information to evaluate the carcinogenic activity of copper monochloride. Reproductive and developmental toxicity: In the combined repeated dose toxicity study with the reproduction/developmental toxicity screening test (OECD TG 422), copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39-51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day). WARNING: Inhalation of high concentrations of copper may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever.			
NICKEL	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.			
	WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [<i>National Toxicology Program: U.S. Dep. of Health & Human Services 2002</i>] Oral (rat) TDLo: 500 mg/kg/5D-I Inhalation (rat) TCLo: 0.1 mg/m3/24H/17W-C			
LITHIUM COBALTATE & GRAPHITE & LITHIUM FLUOROPHOSPHATE & ALUMINIUM & VINYLIDENE FLUORIDE HOMOPOLYMER	No significant acute toxicological data identified in literature search.			
GRAPHITE & LITHIUM FLUOROPHOSPHATE & ETHYLENE CARBONATE & DIETHYL CARBONATE & ETHYL PROPIONATE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.			
PROPYLENE CARBONATE & ETHYL PROPIONATE	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.			
Acute Toxicity	×	Carcinogenicity	×	
Skin Irritation/Corrosion	✓	Reproductivity	×	
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×	
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	✓	
Mutagenicity	×	Aspiration Hazard	×	

Legend: 🔰

X − Data either not available or does not fill the criteria for classification
→ Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Toro Flex Force Lithium Ion Battery (UN3480)	ENDPOINT Not Available	TEST DURATION (HR) Not Available	SPECIES Not Available		VALUE Not Available	SOURCE Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALU	ΙE	SOURCE
	LC50	96	Fish	0.001	-0.406mg/L	2
lithium cobaltate	EC50	48	Crustacea 0.002		-0.618mg/L	2
	EC50	96	Algae or other aquatic plants 0.071		-0.314mg/L	2
	NOEC	96	Crustacea	0.001	-0.2819mg/L	2
	ENDROINT		SDECIES		VALUE	SOURCE
			Fish		100mg/l	2
graphite	LC50	90			>100mg/L	2
	EC50	48	Crustacea	Crustacea >1		2
	EC50	72	Algae or other aquatic plants	Algae or other aquatic plants >10		2
	NOEC	72	Algae or other aquatic plants		>=100mg/L	2

lithium fluorophosphate	ENDPOINT	TEST DURATION (HR)	SPECIES VALUE		SOURCE	
	LC50	96	Fish 42mg/L		42mg/L	2
	EC50	48	Crustacea		98mg/L	2
	EC50	96	Algae or other aquatic plants		43mg/L	2
	NOEC	528	Fish		0.2mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	LC50	96	Fish		>100mg/L	2
ethylene carbonate	EC50	48	Crustacea		>100mg/L	2
	EC50	96	Algae or other aquatic plants	uatic plants 17.388mg/L		3
	NOEC	72	Algae or other aquatic plants		100mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE		SOURCE
	LC50	96	Fish	>1-mg/L		2
propulene carbonate	EC50	48	Crustacea	:	>1-mg/L	2
propylene carbonate	EC50	96	Algae or other aquatic plants		12.203mg/L	3
	EC0	24	Crustacea		=500mg/L	1
	NOEC	96	Fish		1-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	١	ALUE	SOURCE
	LC50	96	Fish	4	16.738mg/L	3
diethyl carbonate	EC50	48	Crustacea	;	>74.16mg/L	2
	EC50	96	Algae or other aquatic plants	3	3.616mg/L	3
	NOEC	96	Fish	1	1-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	LC50	96	Fish 4.77mg/L		4.77mg/L	2
ethyl propionate	EC50	48	Crustacea		25.5mg/L	2
	EC50	96	Algae or other aquatic plants		2.644mg/L	3
	NOEC	504	Crustacea		1.3mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALU	JE	SOURCE
	LC50	96	Fish	0.001	-0.09mg/L	2
	EC50	48	Crustacea	0.001	mg/L	2
copper	EC50	72	Algae or other aquatic plants	0.013	3335mg/L	4
	BCF	960	Fish	200m	ng/L	4
	EC25	6	Algae or other aquatic plants	0.00150495mg/L		4
	NOEC	96	Crustacea	0.000)8mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALU	JE	SOURCE
	LC50	96	Fish	0.001-0.134mg/L		2
aluminium	EC50	48	Crustacea	0.7364mg/L		2
arunnnum	EC50	72	Algae or other aquatic plants	0.001-0.799mg/L		2
	BCF	360	Algae or other aquatic plants	9mg/L		4
	NOEC	168	Crustacea	0.001	-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	V	ALUE	SOURCE
vinylidene fluoride homopolymer	LC50	96	Fish 39.014mg/L		9.014mg/L	3
	EC50	96	Algae or other aquatic plants	14	49.630mg/L	3
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
steel	Not Available	Not Available	Not Available		Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE		SOURCE
	LC50	96	Fish 0.0000475mg		475mg/L	4
niokol	EC50	48	Crustacea 0.001-0.576mg/).576mg/L	2
nickei	EC50	72	Algae or other aquatic plants 0.00094mg/L		4mg/L	2
	BCF	1440	Algae or other aquatic plants 0.47mg/L		g/L	4
	NOEC	240	Crustacea	>0.001	-0.715mg/L	2

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12

(QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene carbonate	HIGH	HIGH
propylene carbonate	HIGH	HIGH
diethyl carbonate	HIGH	HIGH
ethyl propionate	LOW	LOW
vinylidene fluoride homopolymer	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene carbonate	LOW (LogKOW = -0.3388)
propylene carbonate	LOW (LogKOW = -0.41)
diethyl carbonate	LOW (LogKOW = 1.21)
ethyl propionate	LOW (LogKOW = 1.21)
vinylidene fluoride homopolymer	LOW (LogKOW = 1.24)

Mobility in soil

Ingredient	Mobility
ethylene carbonate	LOW (KOC = 9.168)
propylene carbonate	LOW (KOC = 14.85)
diethyl carbonate	LOW (KOC = 28.08)
ethyl propionate	LOW (KOC = 11.85)
vinylidene fluoride homopolymer	LOW (KOC = 35.04)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill. Recycle containers if possible. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill. Recycle wherever possible or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO Not Applicable

Land transport (DOT)

UN number	3480		
UN proper shipping name	Lithium ion batteries including lithium ion polymer batteries		
Transport hazard class(es)	Class 9 Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	Hazard Label9Special provisionsA51, A54		

Air transport (ICAO-IATA / DGR)

UN number 3480	
UN proper shipping name Lithium io	a batteries (including lithium ion polymer batteries)

	ICAO/IATA Class	9		
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable		
	ERG Code	9F		
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
	Special provisions		A88 A99 A154 A164 A183 A201 A206 A331	_
	Cargo Only Packing In	nstructions	See 965	_
	Cargo Only Maximum Qty / Pack		See 965	
Special precautions for user	Passenger and Cargo	Packing Instructions	Forbidden	
	Passenger and Cargo	Maximum Qty / Pack	Forbidden	
	Passenger and Cargo	Limited Quantity Packing Instructions	Forbidden	
	Passenger and Cargo	Limited Maximum Qty / Pack	Forbidden	

Sea transport (IMDG-Code / GGVSee)

1

UN number	3480		
UN proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)		
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	EMS NumberF-A , S-ISpecial provisions188 230 310 348 376 377 384Limited Quantities0		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

LITHIUM COBALTATE(12190-79-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US Clean Air Act - Hazardous Air Pollutants		
Monographs	US EPCRA Section 313 Chemical List		
US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits	US National Toxicology Program (NTP) 14th Report Part B. Reasonably Anticipated to be a		
US - Washington Permissible exposure limits of air contaminants	Human Carcinogen		
US ACGIH Threshold Limit Values (TLV)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory		
US ACGIH Threshold Limit Values (TLV) - Carcinogens	US TSCA Chemical Substance Inventory - Interim List of Active Substances		
US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes			
GRAPHITE(7782-42-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS			
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants		
US - California Permissible Exposure Limits for Chemical Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants		
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z-3 Mineral Dusts		
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (Spanish)		
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)		
US - Michigan Exposure Limits for Air Contaminants	US DOE Temporary Emergency Exposure Limits (TEELs)		
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)		
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs) (Spanish)		
US - Oregon Permissible Exposure Limits (Z-3)	US OSHA Permissible Exposure Levels (PELs) - Table Z1		
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z3		
US - Rhode Island Hazardous Substance List	US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)		
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US OSHA Permissible Exposure Limits - Annotated Table Z-3 (Spanish)		
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory		
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances		
LITHIUM FLUOROPHOSPHATE(21324-40-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS			
International Air Transport Association (IATA) Dangerous Goods Regulations	US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide		
International Maritime Dangerous Goods Requirements (IMDG Code)	US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID)		
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations	Number		
(English)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory		
US Department of Transportation (DOT), Hazardous Material Table	US TSCA Chemical Substance Inventory - Interim List of Active Substances		
US DOE Temporary Emergency Exposure Limits (TEELs)			

ETHYLENE CARBONATE(96-49-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

GESAMP/EHS Composite List - GESAMP Hazard Profiles	US - Pennsylvania - Hazardous Substance List
IMO IBC Code Chapter 17: Summary of minimum requirements	US DOE Temporary Emergency Exposure Limits (TEELs)
IMO IBC Code Chapter 18: List of products to which the Code does not apply	US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances	Liquid Cargoes
US - Massachusetts - Right To Know Listed Chemicals	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
	US I SCA Chemical Substance Inventory - Interim List of Active Substances
PROPYLENE CARBONATE(108-32-7) IS FOUND ON THE FOLLOWING REGULATORY LIS	STS
GESAMP/EHS Composite List - GESAMP Hazard Profiles	LIS DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk
IMO IBC Code Chanter 17: Summary of minimum requirements	
IMO IBC Code Chapter 18: List of products to which the Code does not apply	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US DOE Temporary Emergency Exposure Limits (TEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances
-	
DIETHYL CARBONATE(105-58-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
GESAMP/EHS Composite List - GESAMP Hazard Profiles	US Department of Transportation (DOT), Hazardous Material Table
IMO IBC Code Chapter 17: Summary of minimum requirements	US DOE Temporary Emergency Exposure Limits (TEELs)
International Air Transport Association (IATA) Dangerous Goods Regulations	US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide
International Maritime Dangerous Goods Requirements (IMDG Code)	US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID)
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations	Number
(English)	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Massachusetts - Right To Know Listed Chemicals	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Pennsylvania - Hazardous Substance List	
ETHYL PROPIONATE(105-37-3) IS FOLIND ON THE FOLLOWING REGULATORY LISTS	
	US Department of Transportation (DOT) Hazardaya Material Table
GESAMP/EHS Composite List - GESAMP Hazard Promes	US Department of Transportation (DOT), Hazardous Material Table
INO IBC Code Chapter 17: Summary of minimum requirements	US DOE Temporary Emergency Exposure Limits (TEELS)
INIO MARPOL (Annex II) - List of Noxious Liquid Substances Carned III Bulk	
International Maritime Dangerous Goods Requirements (IMDG Code)	US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide
International Manufier Dangerous Goods Requirements (INDG Code)	US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID)
(English)	Number
US - Massachusetts - Right To Know Listed Chemicals	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Pennsylvania - Hazardous Substance List	US TSCA Chemical Substance Inventory - Interim List of Active Substances
,	
COPPER(7440-50-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Alaska Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US ACGIH Threshold Limit Values (Spanish)
US - California Permissible Exposure Limits for Chemical Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Hawaii Air Contaminant Limits	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Idaho - Limits for Air Contaminants	US CWA (Clean Water Act) - Priority Pollutants
US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits	US CWA (Clean Water Act) - Toxic Pollutants
US - Massachusetts - Right To Know Listed Chemicals	US Department of Transportation (DOT) List of Hazardous Substances and Reportable
US - Michigan Exposure Limits for Air Contaminants	Quantities - Hazardous Substances Other Than Radionuclides
US - Minnesota Permissible Exposure Limits (PELs)	US Department of Transportation (DOT) Marine Pollutants - Appendix B
US - Oregon Permissible Exposure Limits (Z-1)	US DOE Temporary Emergency Exposure Limits (TEELS)
US - Pennsylvania - Hazardous Substance List	US EPA Calcinogens Listing
US - Rhode Island Hazardous Substance List	US NIOSH Recommended Exposure Limite (PELs)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	LIS NIOSH Recommended Exposure Limits (RELs)
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table 71
Contaminants	US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)
US - Washington Permissible exposure limits of air contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Washington Toxic air pollutants and their ASIL. SQER and de minimis emission values	US TSCA Chemical Substance Inventory - Interim List of Active Substances
-	
ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Air Transport Association (IATA) Dangerous Goods Regulations	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
International Maritime Dangerous Goods Requirements (IMDG Code)	US ACGIH Threshold Limit Values (Spanish)
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations	US ACGIH Threshold Limit Values (TLV)
(English)	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Alaska Limits for Air Contaminants	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - California Permissible Exposure Limits for Chemical Contaminants	US Department of Homeland Security (DHS) - Chemical Facility Anti-Terrorism Standards
US - Hawaii Air Contaminant Limits	(CFATS) - Chemicals of Interest
US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits	US Department of Transportation (DOT), Hazardous Material Table
US - Massachusetts - Right To Know Listed Chemicals	US Department of Transportation (DOT), Hazardous Material Table : Goods Forbidden for
US - IVICNIGAN EXPOSURE LIMITS for Air Contaminants	LIS EDCDA Section 212 Chamical List
US - Minnesota Permissible Exposure Limits (PELs)	US EFURA SECTION STO CHEMICAL LIST
US - Oregon Permissible Exposure Limits (2-1)	US NIOSH Recommended Exposure Limits (RELS)
US - Peninsylvania - mazardous Substance List	US OSHA Permissible Exposure Levels (PELs) (Spanist)
US - RHOUE ISIAND MAZAROOUS SUDSTANCE LIST	US OSHA Permissible Exposure Limits - Annotated Table 7-1 (Spanish)
US - remessee Occupational Exposure Limits Fol All Contaminants	US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID)
Contaminants	Number
US - Washington Permissible exposure limits of air contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
	US TSCA Chemical Substance Inventory - Interim List of Active Substances

VINYLIDENE FLUORIDE HOMOPOLYMER(24937-79-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
STEEL(12597-69-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
Not Applicable	
NICKEL(7440-02-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Washington Permissible exposure limits of air contaminants US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US ACGIH Threshold Limit Values (Spanish)
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US ACGIH Threshold Limit Values (TLV)
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US ACGIH Threshold Limit Values (TLV) - Carcinogens
(CRELs)	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - California Office of Environmental Health Hazard Assessment Proposition 65 No	US Clean Air Act - Hazardous Air Pollutants
Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels	US CWA (Clean Water Act) - Priority Pollutants
(MADLS) for Chemicals Causing Reproductive Toxicity	US CWA (Clean Water Act) - Toxic Pollutants
	US Department of Transportation (DOT) List of Hazardous Substances and Reportable
US - California i roposition 05 - Calcinogens	Quantities - Hazardous Substances Other Than Radionuclides
US - Idaho - Limits for Air Contaminants	US DOE Temporary Emergency Exposure Limits (TEELs)
US - Mario - Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Michigan Exposure Limits for Air Contaminants	US National Toxicology Program (NTP) 14th Report Part B. Reasonably Anticipated to be a
US - Michigan Exposure Limits for Air Contaminants	Human Carcinogen
US - New Jersey Pight to Know - Special Health Hazard Substance List (SHHSL):	US NIOSH Recommended Exposure Limits (RELs)
Carcinogens	US NIOSH Recommended Exposure Limits (RELs) (Spanish)
US - Oregon Permissible Exposure Limits (7-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Dennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Vermont Permissible Exposure Limits Table 7-1-A Final Rule Limits for Air Contaminants	
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air	
Contaminants	

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)		
Gas under pressure	No	
Explosive	No	
Self-heating	No	
Pyrophoric (Liquid or Solid)	No	
Pyrophoric Gas	No	
Corrosive to metal	No	
Oxidizer (Liquid, Solid or Gas)	No	
Organic Peroxide	No	
Self-reactive	No	
In contact with water emits flammable gas	No	
Combustible Dust	No	
Carcinogenicity	No	
Acute toxicity (any route of exposure)	No	
Reproductive toxicity	No	
Skin Corrosion or Irritation	Yes	
Respiratory or Skin Sensitization	No	
Serious eye damage or eye irritation	Yes	
Specific target organ toxicity (single or repeated exposure)	Yes	
Aspiration Hazard	No	
Germ cell mutagenicity	No	
Simple Asphyxiant	No	
Hazards Not Otherwise Classified	No	

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Copper	5000	2270
Nickel	100	45.4

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS: LISTED SUBSTANCE

Nickel (Metallic) Listed

National Inventory Status

National Inventory	Status
Australia - AICS	No (steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Canada - DSL	No (steel; lithium fluorophosphate; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Canada - NDSL	No (diethyl carbonate; vinylidene fluoride homopolymer; graphite; copper; ethyl propionate; ethylene carbonate; aluminium; nickel; lithium cobaltate; propylene carbonate; steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
China - IECSC	No (steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Europe - EINEC / ELINCS / NLP	No (vinylidene fluoride homopolymer; steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Japan - ENCS	No (graphite; copper; aluminium; nickel; steel; lithium fluorophosphate; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Korea - KECI	No (steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
New Zealand - NZIoC	No (steel; lithium fluorophosphate; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Philippines - PICCS	No (lithium cobaltate; steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
USA - TSCA	No (steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Taiwan - TCSI	No (electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Mexico - INSQ	No (vinylidene fluoride homopolymer; ethylene carbonate; lithium cobaltate; steel; lithium fluorophosphate; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Vietnam - NCI	No (lithium cobaltate; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Russia - ARIPS	No (lithium cobaltate; steel; lithium fluorophosphate; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Thailand - TECI	No (vinylidene fluoride homopolymer; copper; aluminium; lithium cobaltate; steel; electrolyte solvent contains; inert components, proprietary) Non-disclosed ingredients
Legend:	Yes = All declared ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	05/13/2021
Initial Date	07/05/2019

SDS Version Summary

Version	Issue Date	Sections Updated
2.1.1.2	05/13/2021	Appearance

Other information

Ingredients with multiple cas numbers

Name	CAS No
propylene carbonate	108-32-7, 51260-39-0, 16606-55-6
copper	7440-50-8, 133353-46-5, 133353-47-6, 195161-80-9, 65555-90-0, 72514-83-1
aluminium	7429-90-5, 91728-14-2

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit₀ IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LODEL: Imit Value LOD: Limit of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.