



10100 Rodney Street
 Pineville NC 28134
 1-888-939-6971

IPEX USA LLC
 homeflexunderground@ipexamerica.com
 homeflexunderground.com

Product HOME-FLEX™ Underground Anodeless Meter Riser, 3/4" - 2" IPS

Project Information

Job Name: _____
 Location: _____
 Engineer: _____
 Contractor: _____

Date Submitted: _____
 Submitted by: _____
 Approved by: _____
 Manufacturer's Rep: _____

Installation

Must be installed in accordance with the HOME-FLEX™ Underground Installation Practices and Guidelines and in accordance with local codes.

Application Information

For use in Natural Gas and Liquefied Petroleum (Propane) Gas applications with Polyethylene (PE) gas pipelines.

Technical Data

Materials

Male Pipe Thread Steel Gas Carrier (ASTM A53/API 5L)
 Powder Coating PPG-PCT70265
 Plain End Polyethylene Pipe (ASTM D513)

Pressure Ratings

Max Operating Pressure 80 PSIG

Temperature Ratings

Operating Temperature Range 0°F - 140°F

Codes

Uniform Plumbing Code (UPC)
 International Fuel Gas Code (IFGC)

Standards

ASTM F1973, D2513, A53/API 5L
 ANSI B1.20.1

Listings

IAPMO Listed

Dimensional Information

	Size (IPS)	Part Number	Dimensions (in)			Weight (lbs)
			L	W	H	
	3/4" SDR 11	251026	29	1.2	31	5
	1" SDR 11	251027	29	1.6	31	6
	1-1/4" SDR 11	251028	29	2.0	31	9
	1-1/2" SDR 11	251029	29	2.2	31	14
	2" SDR 11	251030	29	2.6	31	28

