

Safety Data Sheet

Refractory Cement

1

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Refractory Cement
SDS Number: 33
Product Code: 610, 611, 612
Revision Date: 10/19/2021
Version: 1
Product Description: Pre-mixed cement
Product Use: For masonry to masonry repairs; Use to set, coat, or repair brick in fire boxes.
Supplier Details: Rutland
7 Crabtree Road
Jacksonville, IL 62650
Contact: Faith Nergenah, Brian Miller
Phone: 217-245-7810
Fax: 217-245-1194
Email: faith@rutland.com bmillier@rutland.com
Web: www.rutland.com
Emergency: CHEMTREC (800) 424-9300

Refractory Cement

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Serious Eye Damage/Eye Irritation, 2 B
Health, Skin corrosion/irritation, 2
Health, Carcinogenicity, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

H320 - Causes eye irritation
H315 - Causes skin irritation
H351 - Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

GHS Precautionary Statements:

P234 - Keep only in original container.
P260 - Do not breathe dust or mist.
P264 - Wash skin thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/ physician.
P321 - Specific treatment (see supplemental first aid instructions on this label).
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.
P405 - Store locked up.
P406 - Store in corrosive resistant stainless steel container with a resistant inner liner.
P501 - Dispose of contents/ container to an approved waste disposal plant.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Ingestion; Skin;

Skin Contact: May cause irritation.

Eye Contact: May cause irritation.

Ingestion: Ingestion is not an applicable route of entry for intended use. May be harmful if swallowed.

Safety Data Sheet

Refractory Cement

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
1332-58-7		Kaolin
1310-73-2		Sodium hydroxide (NaOH)
1344-09-8		Silicic acid, sodium salt
13983-17-0		Calcium Metasilicate (Wollastonite)
14808-60-7		Silica, crystalline

Percentages withheld, Trade Secret

4 FIRST AID MEASURES

- Inhalation:** Remove to fresh air. Seek medical attention if cough or other symptoms develop or persist.
- Skin Contact:** Wash with plenty of water. Get medical attention if irritation develops or persists.
- Eye Contact:** Immediately flush eyes with plenty of water. After initial flushing, remove contact lenses and continue flushing for at least 15 minutes. If effects occur, consult a physician, preferably an ophthalmologist. May cause injury due to mechanical action.
- Ingestion:** If Swallowed, DO NOT INDUCE VOMITING. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Never give anything by mouth to an unconscious or convulsive person.

5 FIRE FIGHTING MEASURES

Flammability: Non-Flammable

Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Absorb spilled material and place in appropriate container for disposal.

7 HANDLING AND STORAGE

- Handling Precautions:** Avoid contact with eyes and skin. Use in a well-ventilated area. Avoid inhalation of vapors and mists.
- Storage Requirements:** Keep container closed to prevent drying out.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** A system of local and/or general exhaust is recommended to keep employee exposures as low as possible.
- Personal Protective Equipment:** EYES AND FACE: Wear safety glasses with side shields. Chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent) are recommended. SKIN: Wear protective clothing, including long sleeves and gloves, to prevent skin contact. Thoroughly wash clothing before reuse. RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment.

Safety Data Sheet

Refractory Cement

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Buff	Odor:	Mild
Physical State:	Paste	Molecular Formula:	Not Available
Odor Threshold:	Not Available	Solubility:	Insoluble
Particle Size:	Not Available	Softening Point:	Not Available
Spec Grav./Density:	1.8	Percent Volatile:	Not Available
Viscosity:	Not Available	Heat Value:	Not Available
Saturated Vapor Concentration:	Not Available	Freezing/Melting Pt.:	Not Available
Boiling Point:	Not Available	Flash Point:	Not Available
Flammability:	Not Available	Octanol:	Not Available
Partition Coefficient:	Not Available	Vapor Density:	Not Available
Vapor Pressure:	Not Available	VOC:	Not Available
pH:	10	Bulk Density:	Not Available
Evap. Rate:	Not Available		Not Available
Molecular weight:	Not Available	Auto-Ignition Temp:	Not Available
Decomp Temp:	Not Available	UFL/LFL:	Not Available

10

STABILITY AND REACTIVITY

Reactivity:	This product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	None Known
Materials to Avoid:	Strong Acids; Strong Oxidizing Agents;
Hazardous Decomposition:	None Known
Hazardous Polymerization:	Will not occur.

11

TOXICOLOGICAL INFORMATION

No data available.

12

ECOLOGICAL INFORMATION

No information available

13

DISPOSAL CONSIDERATIONS

Dispose of this product in accordance with all applicable local, state and federal regulations.

14

TRANSPORT INFORMATION

Not Regulated by DOT

Safety Data Sheet

Refractory Cement

15

REGULATORY INFORMATION

RQ (CAS#) Substance - Reg Codes

Kaolin (1332-58-7) CAPROP65, OSHAWAC, PA, TSCA, TXAIR

RQ(1000LBS), Sodium hydroxide (NaOH) (1310-73-2) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

Silicic acid, sodium salt (1344-09-8) TSCA

Calcium Metasilicate (Wollastonite) (13983-17-0)

Silica, crystalline (14808-60-7) GADSL, MASS, NRC, OSHAWAC, PA, PROP65, TSCA, TXAIR



WARNING

This product can expose you to chemicals including Silica, Crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity
CAPROP65 = California Prop 65
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level
CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances
MASS = MA Massachusetts Hazardous Substances List
GADSL = Global Automotive Declarable Substance List (GADSL)
NRC = Nationally Recognized Carcinogens

16

OTHER INFORMATION

PREPARED BY: Brian Miller

MANUFACTURER DISCLAIMER: The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to their circumstances.

Revision Date: 10/19/2021