SAFETY DATA SHEET



1. Identification

Product identifier BEHR Weatherstrong, White

Other means of identification

Product number BS40
Recommended use Sealant.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp.

1801 E. St. Andrew Place Santa Ana, CA 92705

Telephone 714-545-7101 Emergency telephone +1 760 476 3962 +1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSensitization, skinCategory 1Reproductive toxicityCategory 1B

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. May damage fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. If

skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before

reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Limestone	1317-65-3	30 - 60	
Calcium carbonate	471-34-1	1 - 5	
Titanium dioxide	13463-67-7	1 - 5	

Quartz (SiO ₂)	14808-60-7	0.1 - 1
Dibutylbis(pentane-2,4-dionato -o,o')tin	22673-19-4	0.1 - 1
N-(3-(trimethoxysilyl)propyl)eth ylenediamine	1760-24-3	0.1 - 1

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantMay cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Protect from sunlight. Avoid contact with water and moisture. Recommended storage temperature: 41 - 95°F. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air (Contaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS 22673-19-4)	PEL	0.1 mg/m3	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910. ⁻	1000)		
Components	Туре	Value	Form
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		15 mg/m3 50 mppcf	Total dust. Total dust.
		-	
IIS ACGIH Threshold Limit Values		50 mppcf	Total dust.
US. ACGIH Threshold Limit Values Components	Туре	50 mppcf	Total dust.
		50 mppcf 15 mppcf	Total dust. Respirable fraction.
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS	Туре	50 mppcf 15 mppcf Value	Total dust. Respirable fraction.
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS	Type STEL	50 mppcf 15 mppcf Value 0.2 mg/m3	Total dust. Respirable fraction.
Components Dibutylbis(pentane-2,4-dion ato-0,0')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS	Type STEL TWA	50 mppcf 15 mppcf Value 0.2 mg/m3	Total dust. Respirable fraction. Form
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS 14808-60-7) Titanium dioxide (CAS	Type STEL TWA TWA TWA	50 mppcf 15 mppcf Value 0.2 mg/m3 0.1 mg/m3 0.025 mg/m3	Total dust. Respirable fraction. Form
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)	Type STEL TWA TWA TWA	50 mppcf 15 mppcf Value 0.2 mg/m3 0.1 mg/m3 0.025 mg/m3	Total dust. Respirable fraction. Form
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemical Components (CAS 14808-	Type STEL TWA TWA TWA TWA	50 mppcf 15 mppcf Value 0.2 mg/m3 0.1 mg/m3 0.025 mg/m3 10 mg/m3	Total dust. Respirable fraction. Form Respirable fraction.
Components Dibutylbis(pentane-2,4-dion ato-0,0')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium carbonate (CAS	Type STEL TWA TWA TWA TWA TWA TOTAL	50 mppcf 15 mppcf Value 0.2 mg/m3 0.1 mg/m3 0.025 mg/m3 10 mg/m3	Total dust. Respirable fraction. Form Respirable fraction.
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium carbonate (CAS 471-34-1) Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS	Type STEL TWA TWA TWA TWA TWA TOTAL	50 mppcf 15 mppcf Value 0.2 mg/m3 0.1 mg/m3 0.025 mg/m3 10 mg/m3 Value 5 mg/m3	Total dust. Respirable fraction. Form Respirable fraction. Form Respirable.
Components Dibutylbis(pentane-2,4-dion ato-o,o')tin (CAS 22673-19-4) Quartz (SiO ₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium carbonate (CAS 471-34-1) Dibutylbis(pentane-2,4-dion	Type STEL TWA TWA TWA TWA ical Hazards Type TWA	50 mppcf 15 mppcf Value 0.2 mg/m3 0.1 mg/m3 0.025 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3	Total dust. Respirable fraction. Form Respirable fraction. Form Respirable.

US. NIOSH: Pocket Guide to Chemical Hazards

 Components
 Type
 Value
 Form

 Quartz (SiO₂) (CAS
 TWA
 0.05 mg/m3
 Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

14808-60-7)

US - California OELs: Skin designation

Dibutylbis(pentane-2,4-dionato-o,o')tin (CAS 22673-19-4) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Dibutylbis(pentane-2,4-dionato-o,o')tin (CAS 22673-19-4) Skin designation applies.

US - Tennessee OELs: Skin designation

Dibutylbis(pentane-2,4-dionato-o,o')tin (CAS 22673-19-4) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Dibutylbis(pentane-2,4-dionato-o,o')tin (CAS 22673-19-4) Danger of cutaneous absorption

US. NIOSH: Pocket Guide to Chemical Hazards

Dibutylbis(pentane-2,4-dionato-o,o')tin (CAS 22673-19-4) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Paste.
Color White.
Odor Musty.
Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point >= 284.0 °F (>= 140.0 °C)

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper Not available.

(%)

Vapor pressure Not available. Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Insoluble in water. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Solid content: ≥ 97 % Other information

Density 1.65 g/cm3 Not explosive. **Explosive properties Oxidizing properties** Not oxidizing. VOC < 20 g/l (2%)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Cures in the presence of moisture and releases a small amount of methanol.

Conditions to avoid Keep away from heat, sparks and open flame. Protect against direct sunlight. Keep from freezing.

Avoid contact with water and moisture. Contact with incompatible materials.

Strong oxidizing agents. Water. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

May cause discomfort if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Calcium carbonato (CAS 471 34 1)		

Calcium carbonate (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/kg

N-(3-(trimethoxysilyl)propyl)ethylenediamine (CAS 1760-24-3)

Acute Dermal

> 2000 mg/kg LD50 Rat

Oral

Rat 2413 mg/kg LD50

Components Species Test Results

Quartz (SiO₂) (CAS 14808-60-7)

Chronic Inhalation

LOEC Human 0.0563 mg/m3

Titanium dioxide (CAS 13463-67-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

CarcinogenicityDue to the form of the product, exposure to the potentially carcinogenic components is not

expected.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (SiO₂) (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Quartz (SiO₂) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO₂) (CAS 14808-60-7) Cancer

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO₂) (CAS 14808-60-7)

lung effects

immune system effects

kidney effects

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

SARA 311/312 Hazardous

Classified hazard

chemical

Respiratory or skin sensitization

Reproductive toxicity categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 471-34-1)

Limestone (CAS 1317-65-3)

Quartz (SiO₂) (CAS 14808-60-7)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Calcium carbonate (CAS 471-34-1)

Limestone (CAS 1317-65-3) Quartz

(SiO₂) (CAS 14808-60-7) Titanium

dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Version #: 01 Revision date: - Issue date: 14-April-2021

Calcium carbonate (CAS 471-34-1)

Limestone (CAS 1317-65-3)

Quartz (SiO₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Calcium carbonate (CAS 471-34-1)

Dibutylbis(pentane-2,4-dionato-o,o')tin (CAS 22673-19-4)

Limestone (CAS 1317-65-3) Quartz (SiO₂) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 14-April-2021

Revision date - Version # 0°

Further information HMIS® is a registered trade and service mark of the ACA.

HMIS® ratings
Health: 2*
Flammability: 0
Physical hazard: 0

List of abbreviationsDOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

LOEC: Lowest observable effect concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

Disclaimer Masterchem Industries LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.