

TECHNICAL DATA SHEET

PHYSICAL PROPERTIES (FLOATING MULTILAYER MODULR FLOORING) – 6.5 MM GAUGE/22 MIL WEAR LAYER				
Collection	Plank			
Size	7.13" x 48.03" (181 mm x 1220 mm), 8.98" x 48.03" (228 mm x 1220 mm), 8.98" x 59.84" (220 mm X 1520 mm); multi width (4.96"/7/13"/8.98") x 48.03" (126 mm/181 mm/228 mm x1220 mm)			
Overall Gauge	6.5 mm ().256")			
Wear Layer	22 mils (0.55 mm)			
Core	5.5 mm (0.217") SPC Rigid Core			
Pad	1.0 mm (0.039") IXPE with antimicrobial			
Use	Light Commercial and Residential			
Profile	Painted Edge			
Finish	Crystalguard			
Antimicrobial	Included in Finish and Pad			
Embossing	Embossed			
Pieces/Carton	6,8,10 Depending on model.			
Coverage/Carton	17.98, 19.05, 23.44 sq.ft. depending on model.			
Limited Warranty	Light Commercial – 20 Years Residential - Lifetime			

STANDARDS – SAFETY & PERFORMANCE						
Standard	Description	Requirements	Results			
ASTM E648	Critical Radiant Flux (Radiant Panel	Class 1: ≥ 0.45 W/cm	Passed Requirements			
ASTM E662	Smoke Density	Flaming and Non-Flaming ≤ 450	Passed Requirements			
ANSI A137.1	Dynamic Coefficient of Friction	No Standard. Check Local Requirement	DCOF: 0.38			
ASTM F970	Static Load	0.13 mm	0.002 mm at 250 psi			
ASTM F1914	Short Term Indentation	≤ 0.007 in.	Passed Requirements			
ASTM F2199	Dimensional Stability	≤ 0.25% per lineal ft.	Passed Requirements			
ASTM F925	Chemical Resistance	No more than "Slight Change"	Passed Requirements			
ASTM F1514	Resistance to Heat	Average ∆E < 8.0	Passed Requirements			
ASTM F1515	Resistance to Light	Average ∆E < 8.0	Passed Requirements			
ASTM E2180	Antimicrobial	No Standard	≥ 99.99% Reduction			
ASTM F963	Heavy Metals	Per F963 Limits	Not detected			
CPSC-CH-C1001- 09.4	Phthalates	0.1%	Not detected			

STANDARD - SOUND						
Assembly	ASTM E90	ASTM E492	ASTM E2179	Results (Remarks)		
6" Concrete Slab with Drop Ceiling	STC 65	IIC 69	Not Applicable	All tested assemblies pass IBC⁵ requirements of STC ≥ 50 and IIC ≥ 50 for multi-story dwellings		

ENVIRONMENTAL AND COMPLIANCE					
Certification	Description				
Greenguard Gold	Indoor Air Quality. Meets US EPA and California Department of Public Health Section 01350 requirements for				
Greenguaru Golu	Children and Schools.				

THD LP SPC 22 mil v1 Page 1 Issued: 10-11-2024