DEWALT®

STAINLESS STEEL / CAST IRON / ALUMINUM AUTOMATIC SUBMERSIBLE SUMP PUMPS

DEWALT SUMP PUMPS are engineered to be contractor tough and deliver the performance you demand. Designed to keep your basement dry day and night.

C US

DXWPSUMP

GUARANTEED TOUGH.®

AUTOMATIC SUBMERSIBLE SUMP PUMP

Easy to install and maintain

Pump Dimensions

SPECIFICATIONS

MATERIALS	Stainless Steel / Cast Iron /Aluminum
SWITCH TYPE	Vertical or Tethered with Piggy-Back Plug
SOLIDS HANDLING	Up to 1/2 in. Diameter
DISCHARGE SIZE	1-1/2 in. FPT or 2 in. FPT Switch
RUNNING AMPS BY HP	7.6 - 10 - 11 - 12
CORD LENGTH	10 ft.
VOLTAGE	120 Volt AC

PERFORMANCE - GPM AT HEIGHT

Model Vertical	Model Tethered	HP	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.	25 ft.	30 ft.
DXWP62383 DXWP62389	DXWP62381	1/3	75	70	63	56	48	38	28
DXWP62583	DXWP62581	1/2	102	94	86	74	63	50	38
DXWP62783	DXWP62781	3/4	108	101	90	84	73	60	46
DXWP62183	DXWP62181	1	117	110	100	90	78	65	50

PUMP INCLUDES

- (1) Automatic Submersible Sump Pump
- (1) 1-1/2 in. FPT x 2 in. MPT Adapter
- (1) *DXWP62389 includes Check Valve
- (1) Owners Manual

PUMP WARRANTY

10 YEAR

LIMITED WARRANTY

*SUMP PUMP KIT DXWP62389

INCLUDES:

Rubber Boot Check Valve

Intake: 1-1/4 in. or 1-1/2 in.

Discharge: 1-1/4 in. or 1-1/2 in

Check Valve Only Part # **DXWPCV69512**

DEWALT®, GUARANTEED TOUGH® and the yellow/black color scheme are trademarks for DEWALT power tools, outdoor equipment, accessories, anchors and concrete adhesives and are used under license. Product may differ from that pictured. Does not affect function.

Manufactured under license by:
PEDROLLO GROUP INC. | 45 MARYLAND AVE EAST | ST. PAUL, MN 55117

SSPMA CERTIFIED

DXWPSUMP
Form 602501 Rev: 7/2022