



BEHR PREMIUM® Semi-Transparent Concrete Stain

No. 850 Tint Base

- Interior/Exterior
- Decorative, Flat Finish
- Siliconized 100% Acrylic
- Chemical and Hot-Tire Resistant
- Available in Custom Colors



Spread Rate:
Rough 250-400 Sq. Ft.
Smooth 400-500 Sq. Ft.



Dry Time:
1 Hr. Dry to Touch.
4 Hr. Recoat



Clean-Up:
Soap & Water



Protect
from Freezing

CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

WHERE TO USE

For uncoated and unsealed, properly prepared Interior or Exterior Patios, Pavers, Driveways*, Walkways, Garage Floors*, Pool Decks** and other concrete floors. *The composition of concrete varies; therefore, the lack of proper surface preparation and/or over application can lead to automobile tires lifting the product from the surface. **Light and pastel colored concrete stains should be used over pool deck surfaces. DARK COLORS RETAIN HEAT.

PREPARATION † (Proper Surface Preparation is Required.)

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease.
- New concrete must cure for a minimum of 30 days.
- Use a paint stripper to remove any previous coatings or sealers.
- Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper.
- Wipe your fingers over the clean, dry floor to check for dust or powder. Ensure there is no residue on your fingers that may have been left from the etcher. If residue is found, rinse the surface to remove residue. Allow the surface to dry completely. Sprinkle a few drops of water onto the surface. If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready. If not, re-etch.
- For areas subject to automotive traffic, apply a product such as BEHR PREMIUM® No. 880 Concrete and Masonry Bonding Primer to increase adhesion of topcoat to the surface. Follow all label instructions.

APPLICATION

- DO NOT THIN.
- Intermix all cans of same product to ensure color uniformity.
- Stir stain before and occasionally during application. Use product when air and surface temperatures are between 50-90° F (10-32° C).
- Do not apply in direct sunlight. Apply to dry concrete. Do not apply if rain or heavy dew is expected within 24 hours.
- Apply stain in small concrete sections approximately 4' by 4'. Work quickly and feather edges.
- Apply with a high quality pump sprayer with a fine spray setting using a circular motion.
Optional: If a more even, uniform appearance is desired, immediately backroll with a pad applicator or 3/8" nap roller after spraying.
- Spread rate will vary depending on the porosity and texture of the surface.
- Allow first coat to dry before deciding if a second coat is necessary. An additional coat will provide a darker and more uniform color.
- Horizontal surfaces may be subject to premature wear. Periodic touch-ups may be necessary.

OPTIONAL TOPCOAT

- For added protection, use a product such as BEHR PREMIUM No. 985 Wet-Look Sealer for a high-gloss finish or a product such as BEHR PREMIUM No. 986 Low-Lustre Sealer for a low-gloss finish.
- Allow stain at least 24 hours to dry before topcoating.
- NOTE: Do not use Wet-Look Sealer or Low-Lustre Sealer as a topcoat around pool decks or other areas subject to consistent moisture. Follow all label instructions.

DRY TIME

- Longer dry time required in cooler temperatures and higher humidity. Allow 24 hours for light foot traffic.
- Allow 72 hours before subjecting surface to automotive tires, repositioning planters or furniture. Park tires on corrugated cardboard for 7 days after applying stain.
- After 30 days, clean as needed with a mild, non-abrasive liquid detergent.

DISPOSAL

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing.
- To recycle or properly dispose of product in your community, contact your household refuse collection service.

LIMITED WARRANTY

Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead

WARNING Cancer and Reproductive Harm www.P65Warnings.ca.gov

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2018 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 03/18