SAFETY DATA SHEET

Issuing Date 16-Mar-2015 Revision Date 16-Mar-2015 Revision Number 2

(U_L)

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Toro 4 Cycle Oil 10w30

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Engine (motor) oil for Auto or Boat

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name The Toro Company

Supplier Address 8111 Lyndale Avenue South

Bloomington

MN 8515 US

Supplier Phone Number Phone:952-887-8515

Contact Phone951-785-3482

eden.allen@toro.com

Supplier Email

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger



Hazard Statements

May cause cancer



Appearance Clear, amber

Physical State Liquid

Odor Oily

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	60 - 100	*
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate	72162-32-4	1 - 5	*
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES



First aid measures

General AdviceNote: When using this product in high pressure equipment - Accidential high

velocity dermal injection of this material requires immediate medical attention.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention immediately if symptoms occur.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion Call a physician or poison control center immediately. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and No information available.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use

personal protective equipment as required.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or

sanitary sewer system.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Use personal protection equipment. Take precautionary measures

against static discharges.

Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated

place.

Incompatible Products Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	TWA: 5 mg/m³, as oil mist, mineral STEL: TWA: 10 mg/m³, as oil mist, mineral	TWA: 5 mg/m³, as oil mist, mineral	
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4	-	TWA: 1 mg/m³ Ni (vacated) TWA: 0.1 mg/m³ Ni	IDLH: 10 mg/m³ Ni TWA: 0.015 mg/m³ except Nickel carbonyl Ni

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health



Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 **Other Exposure Guidelines**

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

> Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Tight sealing safety goggles. **Eye/Face Protection**

Skin and Body Protection Wear protective gloves and protective clothing.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

None known

provided in accordance with current local regulations.

Hygiene Measures When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid		
Appearance	Clear, amber	Odor	Oily

Color No information available No information available **Odor Threshold**

Property Values Remarks Method **UNKNOWN** None known Melting / freezing point No data available None known No data available None known

Boiling point / boiling range Flash Point No data available None known No data available None known **Evaporation Rate** Flammability (solid, gas) No data available None known

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available

Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known **Water Solubility** Insoluble in water None known No data available Solubility in other solvents None known Partition coefficient: n-octanol/waterNo data available None known None known No data available **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity

Dynamic viscosity No data available No data available **Explosive properties Oxidizing Properties** No data available

Other Information

No data available **Softening Point VOC Content (%)** No data available **Particle Size** No data available



Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information .

Inhalation Specific test data for the substance or mixture is not available.

Eye Contact Specific test data for the substance or mixture is not available.

Skin Contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Component Information

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.



Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	A2	Group 1		Х
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4		Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Chronic Toxicity Contains a known or suspected carcinogen.

Target Organ Effects Skin.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)	-	48h EC50: > 1000 mg/L
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3		96h LC50: 1.0 - 5.0 mg/L (Pimephales promelas) 96h LC50: 10.0 - 35.0 mg/L (Pimephales promelas)		48h EC50: 1 - 1.5 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 221

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3	Toxic

14. TRANSPORT INFORMATION

 DOT
 NOT REGULATED

 Proper Shipping Name
 NON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated
Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

Not regulated

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



ADR

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate - 72162-32-4	72162-32-4	1 - 5	0.1
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts - 68649-42-3	68649-42-3	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic Health Hazard Yes
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4		X		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Sulfuric acid, nickel salt, reaction products with sulfurized calcium	Carcinogen

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
phosphorodithioic acid O,O-dialkyl(C=I-14) esters zinc				X	
salts					
68649-42-3					
Sulfuric acid, nickel salt, reaction products with sulfurized			Х	X	X
calcium phenolate					
72162-32-4					

International Regulations

Mexico



Revision Date 16-Mar-2015

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Sulfuric acid, nickel salt, reaction products with		Mexico: TWA 0.1 mg/m ³
sulfurized calcium phenolate		Mexico: STEL 0.3 mg/m ³
72162-32-4 (1 - 5)		

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class D2A - Very toxic materials



16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and

Chemical Hazards -

HMIS Health Hazards 1* Flammability 0 Physical Hazard 0 Personal Protection

X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 16-Mar-2015 **Revision Date** 16-Mar-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



SAFETY DATA SHEET



1. Identification

Product identifier Lead Acid Battery Wet, Filled With Acid

Other means of identification

may include gel/absorbed electrolyte type lead acid batteries Synonyms

Recommended use Electric storage battery.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier East Penn Manufacturing Company, Inc. 102 Deka Road, Lyon Station PA 19536 Address

Telephone number (610) 682-6361

East Penn EHS Department Contact person

Emergency telephone

number F-mail contactus@eastpenn-deka.com

2. Hazard(s) identification

Physical hazards Explosive Chemical, Division 1.3

Health hazards Acute toxicity, oral Category 4

> Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 1A Serious eye damage/eye irritation Category 1 Carcinogenicity Category 1A Reproductive toxicity Category 1A

USA/Canada: CHEMTREC (800) 424-9300, Outside USA 1 (703) 527-3887

Specific target organ toxicity following single

exposure

Category 1 (respiratory system)

Specific target organ toxicity following single

exposure

Category 3 respiratory tract irritation

Specific target organ toxicity following

repeated exposure

Category 1 (respiratory system)

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Category 1

Hazardous to the aquatic environment,

long-term hazard

Category 1

Label elements











Signal word Danger

Hazard statement Harmful if swallowed. Harmful if inhaled. Causes severe skin burns and eye damage. May cause

cancer. May damage fertility or the unborn child. Causes damage to organs (respiratory system). Causes damage to organs (respiratory system) through prolonged or repeated exposure. May cause respiratory irritation. Very toxic to aquatic life with long lasting effects.

Explosive; fire, blast or projection hazard.

Precautionary statements

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Lead Acid Battery Wet, Filled With Acid 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 Response IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTRE/doctor. Wash contaminated clothing before reuse. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Storage

Refer to manufacturer/supplier for information on recovery/recycling. Dispose of Disposal

contents/container in accordance with local/regional/national/international regulations.

Other hazards Under normal conditions of processing and use, exposure to the chemical constituents in this

product is unlikely. The battery should not be opened or burned. Exposure to the ingredients

contained within or their combustion products could be harmful.

Supplemental information In use, may form flammable/explosive vapour-air mixture.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Lead and lead compounds (inorganic)	7439-92-1	43 - 70
Electrolyte (Sulfuric acid)	7664-93-9	20 - 44
Antimony	7440-36-0	3 - 5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

Content composition concentrations will vary with battery type/size.

4. First-aid measures

Exposure to contents of an open or damaged battery: Move injured person into fresh air and keep Inhalation

person under observation. Get medical attention if any discomfort continues.

Exposure to contents of an open or damaged battery: Immediately flush with plenty of water for at Skin contact

least 15 minutes while removing contaminated clothing and shoes. Get medical attention if

irritation develops and persists.

Exposure to contents of an open or damaged battery: Flush thoroughly with water for at least 15 Eve contact

minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Get medical

attention if irritation develops and persists.

Exposure to contents of an open or damaged battery: Rinse mouth thoroughly with water. DO NOT Ingestion

induce vomiting because of danger of aspirating liquid into lungs. Get medical attention

immediately.

Most important

symptoms/effects, acute and

delayed

Under normal conditions of processing and use, exposure to the chemical constituents in this product is unlikely. The battery should not be opened or burned. Exposure to the ingredients

contained within or their combustion products could be harmful.

Heavy lead exposure may result in central nervous system damage, encephalopathy and damage

to the blood-forming (hematopoietic) tissues.

Indication of immediate medical attention and special

treatment needed General information Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Dry chemical, foam, carbon dioxide, water fog.

Do NOT use water on live electrical circuits.

Specific hazards arising from the chemical

Batteries evolve flammable hydrogen gas during charging and may increase fire risk. Containers may explode when heated.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in

the workplace. Fire fighting

Use standard firefighting procedures and consider the hazards of other involved materials.

equipment/instructions General fire hazards

Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of corrosive and flammable materials.

Lead Acid Battery Wet, Filled With Acid 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 2/8

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Avoid contact with skin.

Methods and materials for containment and cleaning up

Neutralize the spilled material before disposal. Sweep up or vacuum up spillage and collect in suitable container for disposal. Dispose of waste and residues in accordance with local authority requirements.

Environmental precautions

Prevent runoff from entering drains, sewers, or streams.

7. Handling and storage

Precautions for safe handling

In the event of damage resulting in a leak of exposed materials, avoid contact with contents of an open or damaged cell or battery. Keep away from heat, sparks and open flame. Do not allow conductive material to touch the battery terminals. A dangerous short-circuit may occur and cause battery failure and fire.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Protect containers from damage. Place cardboard between layers of stacked batteries to avoid damage and short circuits.

8. Exposure controls/personal protection

US. ACGIH Threshold Limit Values

Occupational exposure limits

Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	T
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.
Lead and lead compounds (inorganic) (CAS 7439-92-1)	TWA	0.05 mg/m3	
Canada. Alberta OELs (Occupation	al Health & Safety Code, Sch	nedule 1 Table 2)	
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	STEL	3 mg/m3	
	TWA	1 mg/m3	
Lead and lead compounds (inorganic) (CAS 7439-92-1)	TWA	0.05 mg/m3	
Canada. British Columbia OELs. (C Safety Regulation 296/97, as amen		s for Chemical Substances, O	ccupational Health and
Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	TWA	0.2 mg/m3	Mist.
Lead and lead compounds (inorganic) (CAS 7439-92-1)	TWA	0.05 mg/m3	
Canada. Manitoba OELs (Reg. 217/	2006, The Workplace Safety	And Health Act)	
Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.
Lead and lead compounds (inorganic) (CAS 7439-92-1)	TWA	0.05 mg/m3	
Canada. Ontario OELs. (Control of	Exposure to Biological or Ch	nemical Agents)	
Components	Type	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.

Lead Acid Battery Wet, Filled With Acid

SDS Canada 3 / 8

923330 Version #: 04 Revision date: 19-September-2019

Components		Туре			Value	Form
Lead and lead compounds (inorganic) (CAS 7439-92-1)		TWA			0.05 mg/m3	
Canada. Quebec OELs. (M	inistry of Labor -	Regu	lation respecting	occupationa	al health and sa	nfety)
Components		Type			Value	
Antimony (CAS 7440-36-0)		TWA			0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)		STEL			3 mg/m3	
		TWA			1 mg/m3	
Lead and lead compounds (inorganic) (CAS 7439-92-1)		TWA			0.05 mg/m3	
logical limit values						
ACGIH Biological Exposure	e Indices					
Components	Value		Determinant	Specimen	Sampling	Time
Lead and lead compounds (inorganic) (CAS 7439-92-1)	200 μg/l		Lead	Blood	*	
* - For sampling details, plea	ase see the source	e docu	ment			

Appropriate engineering

Provide adequate ventilation. Provide easy access to water supply and eye wash facilities.

controls

Individual protection measures, such as personal protective equipment

Eye/face protection None under normal conditions. Leak from a damaged or opened battery: Wear safety glasses with

side shields (or goggles).

Skin protection

Hand protection None under normal conditions. Leak from a damaged or opened battery: Wear appropriate

chemical resistant gloves.

None under normal conditions. Leak from a damaged or opened battery: Wear suitable protective Other

clothing. Use of an impervious apron is recommended.

Respiratory protection None under normal conditions.

Thermal hazards When material is heated, wear gloves to protect against thermal burns.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Sulfuric acid, liquid. Lead, solid. Form

Not available. Colour Odour Odourless. Odour threshold Not available.

< 1 рН

Melting point/freezing point Not available.

Initial boiling point and boiling

range

112.78 - 115.56 °C (235 - 240 °F) (Sulfuric acid)

Below room temperature (as hydrogen gas).

Flash point Evaporation rate < 1 (n-BuAc=1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower 4 % (Hydrogen)

(%)

Lead Acid Battery Wet, Filled With Acid 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 SDS Canada

Flammability limit - upper

(%)

74 % (Hydrogen)

Vapour pressure 10 mm Hg Vapour density > 1 (Air = 1)1.27 - 1.33Relative density

Solubility(ies)

Solubility (water) 100 % (Sulfuric acid)

Not available. Partition coefficient

(n-octanol/water)

Not available. Auto-ignition temperature Not available. Decomposition temperature Not available. Viscosity

Other information

Explosive properties Not explosive. Oxidising properties Not oxidising.

10. Stability and reactivity

Reactivity Chemical The product is non-reactive under normal conditions of use, storage and transport.

stability Possibility of Stable at normal conditions.

Will not occur. hazardous

reactions

Conditions to avoid Overcharging, Ignition sources.

Incompatible materials Strong bases. Combustible organic materials. Reducing Agents. Finely divided metals. Strong

oxidizers. Water.

Hazardous decomposition

products

Sulfur dioxide. Sulfur trioxide. Carbon monoxide. Sulfuric acid. Hydrogen.

11. Toxicological information

Information on likely routes of exposure

Exposure to contents of an open or damaged battery: Harmful if inhaled. Causes severe Inhalation

respiratory tract irritation.

Skin contact Exposure to contents of an open or damaged battery: Causes severe skin burns. Exposure to contents of an open or damaged battery: Causes serious eye damage. Eye contact

Exposure to contents of an open or damaged battery: Harmful if swallowed. Ingestion

Symptoms related to the

physical, chemical and toxicological characteristics Exposure to contents of an open or damaged battery: Dust may irritate the eyes and the

respiratory system.

Information on toxicological effects

Acute toxicity Exposure to contents of an open or damaged battery: Harmful if inhaled or swallowed.

Components Species Test Results

Electrolyte (Sulfuric acid) (CAS 7664-93-9)

Acute Oral

LD50 Rat 2140 mg/kg

Skin corrosion/irritation Exposure to contents of an open or damaged battery: Causes severe skin burns. Serious eye damage/eye Exposure to contents of an open or damaged battery: Causes serious eye damage.

irritation

Respiratory or skin sensitisation Canada - Alberta OELs: Irritant

> Antimony (CAS 7440-36-0) Irritant

Respiratory sensitisation No data available. Skin sensitisation No data available. No data available. Germ cell mutagenicity

SDS Canada 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 5/8

The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid Carcinogenicity

mists containing sulfuric acid" as a known human carcinogen, (IARC category 1). This

classification applies only to mists containing sulfuric acid and not to sulfuric acid or sulfuric acid

solutions.

ACGIH Carcinogens

Electrolyte (Sulfuric acid) (CAS 7664-93-9) A2 Suspected human carcinogen.

Lead and lead compounds (inorganic) (CAS 7439-92-1) A3 Confirmed animal carcinogen with unknown relevance to

Canada - Alberta OELs: Carcinogen category

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Suspected human carcinogen.

Lead and lead compounds (inorganic) (CAS 7439-92-1) Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

Lead and lead compounds (inorganic) (CAS 7439-92-1) Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

Electrolyte (Sulfuric acid) (CAS 7664-93-9) 1 Carcinogenic to humans.

Lead and lead compounds (inorganic) (CAS 7439-92-1) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Known To Be Human Carcinogen.

Lead and lead compounds (inorganic) (CAS 7439-92-1) Reasonably Anticipated to be a Human Carcinogen.

None under normal conditions. Exposure to contents of an open or damaged battery: May damage Reproductive toxicity

fertility or the unborn child.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

None under normal conditions. Exposure to contents of an open or damaged battery: Causes

damage to organs (respiratory system).

None under normal conditions, Exposure to contents of an open or damaged battery: Causes

damage to organs through prolonged or repeated exposure: Respiratory system.

Due to the physical form of the product it is not an aspiration hazard. Aspiration hazard

Exposure to contents of an open or damaged battery: Heavy lead exposure may result in central Chronic effects

nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic)

tissues. Chronic inhalation of sulfuric acid mist may increase the risk of lung cancer.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment. Exposure to contents of an open or damaged battery: Very toxic to aquatic life with long lasting

effects.

Species Components Test Results

Lead and lead compounds (inorganic) (CAS 7439-92-1)

LC50 Rainbow trout, donaldson trout 1.17 mg/l, 96 Hours

(Oncorhynhus mykiss)

The degradation half-life of the product is not known. Lead and its compounds are highly persistent Persistence and degradability

in water.

Bioaccumulative potential Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants, but very little

bioaccumulation occurs through the food chain.

Mobility in soil If the product enters soil, one or more constituents will or may be mobile and may contaminate

groundwater.

Mobility in general The product is insoluble in water and will spread on the water surface.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Recycle the batteries, as the primary disposal method, Avoid discharge into water courses or onto

the ground. Dispose of this material and its container to hazardous or special waste collection

point. Neutralize electrolyte/sulfuric acid.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Local disposal regulations

Spent lead-acid batteries are not regulated as hazardous waste when recycled. Hazardous waste code

Depending upon circumstances, the following waste codes may apply:

Spilled electrolyte/Sulfuric acid. D002: Corrosive waste

Lead Acid Battery Wet, Filled With Acid SDS Canada 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017

Waste from residues / unused

products

Avoid discharge into water courses or onto the ground.

Contaminated packaging

Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

TDG

UN number UN2794

UN proper shipping name

BATTERIES, WET, FILLED WITH ACID, electric storage

Transport hazard class(es)

Class 8 Subsidiary risk Packing group Ш Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN2794 **UN** number

UN proper shipping name

Batteries, wet, filled with acid electric storage

Transport hazard class(es)

Class 8 Subsidiary risk Packing group Environmental hazards No **ERG Code** 8L

Special precautions for user Read safety instructions. SDS and emergency procedures before handling.

Packing Instruction: 870

IMDG

UN number UN2794

UN proper shipping name

BATTERIES, WET, FILLED WITH ACID electric storage

Transport hazard class(es)

Class Subsidiary risk Packing group Environmental hazards Marine pollutant No

EmS F-A, S-B

Read safety instructions, SDS and emergency procedures before handling. Special precautions for user

Packing Instruction: P801

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not applicable.

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS Canadian regulations

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed. Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Antimony (CAS 7440-36-0)

Electrolyte (Sulfuric acid) (CAS 7664-93-9)

Precursor Control Regulations

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Class B

International regulations

Stockholm Convention

Not applicable.

Lead Acid Battery Wet, Filled With Acid 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 7/8 **Rotterdam Convention**

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Japan Inventory of Existing and New Chemical Substances (ENCS) No Existing Chemicals List (ECL) Korea Yes New Zealand New Zealand Inventory Yes Philippines

Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

16. Other information

19-September-2017 Issue date 19-September-2019 Revision date

04 Version No.

LD50: Lethal Dose 50%. List of abbreviations

LC50: Lethal Concentration 50%.

IARC Monographs. Overall Evaluation of Carcinogenicity References

Registry of Toxic Effects of Chemical Substances (RTECS)

Issue date: September-2017

Disclaimer The information in this SDS was obtained from sources which we believe are reliable, but no

warranty or representation as to its accuracy or completeness is hereby given. Users should consider the information herein only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal, the safety and health of employees and customers

and the protection of the environment.

Lead Acid Battery Wet, Filled With Acid

923330 Version #: 04 Revision date: 19-September-2019

SDS Canada

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SAFETY DATA SHEET

1. Identification

EASTPENN

Product identifier Lead Acid Battery Wet, Filled With Acid

Other means of identification

Synonyms may include gel/absorbed electrolyte type lead acid batteries

Recommended use Electric storage battery.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier East Penn Manufacturing Company, Inc.
Address 102 Deka Road, Lyon Station PA 19536

Telephone number (610) 682-6361

Contact person East Penn EHS Department

Emergency telephone

number
E-mail contactus@eastpenn-deka.com

2. Hazard(s) identification

Physical hazards Explosive Chemical, Division 1.3

Health hazards Acute toxicity, oral Category 4

Acute toxicity, inhalation

Category 4

Skin corrosion/irritation

Category 1A

Serious eye damage/eye irritation

Carcinogenicity

Category 1A

Reproductive toxicity

Category 1A

USA/Canada: CHEMTREC (800) 424-9300, Outside USA 1 (703) 527-3887

Specific target organ toxicity following single

exposure

Category 1 (respiratory system)

Specific target organ toxicity following single

exposure

Category 3 respiratory tract irritation

Specific target organ toxicity following

repeated exposure

Category 1 (respiratory system)

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Category 1

Hazardous to the aquatic environment,

long-term hazard

Category 1

Label elements











Signal word Danger

Hazard statement Harmful if swallowed. Harmful if inhaled. Causes severe skin burns and eye damage. May cause

cancer. May damage fertility or the unborn child. Causes damage to organs (respiratory system). Causes damage to organs (respiratory system) through prolonged or repeated exposure. May

cause respiratory irritation. Very toxic to aquatic life with long lasting effects. Explosive; fire, blast or projection hazard.

Precautionary statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Lead Acid Battery Wet, Filled With Acid

923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off Response

immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTRE/doctor. Wash contaminated clothing before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed.

Refer to manufacturer/supplier for information on recovery/recycling. Dispose of Disposal

contents/container in accordance with local/regional/national/international regulations.

Other hazards Under normal conditions of processing and use, exposure to the chemical constituents in this

product is unlikely. The battery should not be opened or burned. Exposure to the ingredients

contained within or their combustion products could be harmful.

Supplemental information In use, may form flammable/explosive vapour-air mixture.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Lead and lead compounds (inorganic)	7439-92-1	43 - 70
Electrolyte (Sulfuric acid)	7664-93-9	20 - 44
Antimony	7440-36-0	3 - 5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

Content composition concentrations will vary with battery type/size.

4. First-aid measures

Exposure to contents of an open or damaged battery: Move injured person into fresh air and keep Inhalation

person under observation. Get medical attention if any discomfort continues.

Exposure to contents of an open or damaged battery: Immediately flush with plenty of water for at Skin contact

least 15 minutes while removing contaminated clothing and shoes. Get medical attention if

irritation develops and persists.

Exposure to contents of an open or damaged battery: Flush thoroughly with water for at least 15 Eve contact

minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Get medical

attention if irritation develops and persists.

Ingestion Exposure to contents of an open or damaged battery: Rinse mouth thoroughly with water. DO NOT

induce vomiting because of danger of aspirating liquid into lungs. Get medical attention

Most important

symptoms/effects, acute and

delayed

Under normal conditions of processing and use, exposure to the chemical constituents in this product is unlikely. The battery should not be opened or burned. Exposure to the ingredients

contained within or their combustion products could be harmful.

Heavy lead exposure may result in central nervous system damage, encephalopathy and damage

to the blood-forming (hematopoietic) tissues.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Dry chemical, foam, carbon dioxide, water fog.

Do NOT use water on live electrical circuits.

Batteries evolve flammable hydrogen gas during charging and may increase fire risk. Containers may explode when heated.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Use standard firefighting procedures and consider the hazards of other involved materials.

Fire fighting equipment/instructions

Like any sealed container, battery cells may rupture when exposed to excessive heat; this could General fire hazards

result in the release of corrosive and flammable materials. Lead Acid Battery Wet, Filled With Acid SDS Canada

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin.

Methods and materials for containment and cleaning up Neutralize the spilled material before disposal. Sweep up or vacuum up spillage and collect in suitable container for disposal. Dispose of waste and residues in accordance with local authority requirements.

Environmental precautions

Prevent runoff from entering drains, sewers, or streams.

Handling and storage

Precautions for safe handling

In the event of damage resulting in a leak of exposed materials, avoid contact with contents of an open or damaged cell or battery. Keep away from heat, sparks and open flame. Do not allow conductive material to touch the battery terminals. A dangerous short-circuit may occur and cause battery failure and fire.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Protect containers from damage. Place cardboard between layers of stacked batteries to avoid damage and short circuits.

8. Exposure controls/personal protection

LIS ACCIH Threshold Limit Values

Occupational exposure limits

Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.
Lead and lead compounds (inorganic) (CAS 7439-92-1)	TWA	0.05 mg/m3	
Canada. Alberta OELs (Occupation	al Health & Safety Code, Sch	edule 1, Table 2)	
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)	STEL	3 mg/m3	
	TWA	1 mg/m3	
Lead and lead compounds (inorganic) (CAS 7439-92-1)	TWA	0.05 mg/m3	
Canada. British Columbia OELs. (C Safety Regulation 296/97, as amen		s for Chemical Substances, Oc	•
Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Electrolyte (Sulfuric acid)	TWA	0.2 mg/m3	Mist.
(CAS 7664-93-9)			
	TWA	0.05 mg/m3	
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS		· ·	
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Manitoba OELs (Reg. 217/		· ·	Form
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1)	2006, The Workplace Safety /	And Health Act) Value	
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Manitoba OELs (Reg. 217/ Components	2006, The Workplace Safety <i>i</i> Type	And Health Act)	
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Manitoba OELs (Reg. 217/ Components Antimony (CAS 7440-36-0) Electrolyte (Sulfuric acid)	2006, The Workplace Safety / Type TWA	And Health Act) Value 0.5 mg/m3	Form
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Manitoba OELs (Reg. 217/ Components Antimony (CAS 7440-36-0) Electrolyte (Sulfuric acid) (CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Ontario OELs. (Control of	2006, The Workplace Safety / Type TWA TWA TWA	And Health Act) Value 0.5 mg/m3 0.2 mg/m3 0.05 mg/m3	Form Thoracic fraction.
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Manitoba OELs (Reg. 217/ Components Antimony (CAS 7440-36-0) Electrolyte (Sulfuric acid) (CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1)	2006, The Workplace Safety / Type TWA TWA TWA	And Health Act) Value 0.5 mg/m3 0.2 mg/m3 0.05 mg/m3	Form
(CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Manitoba OELs (Reg. 217/ Components Antimony (CAS 7440-36-0) Electrolyte (Sulfuric acid) (CAS 7664-93-9) Lead and lead compounds (inorganic) (CAS 7439-92-1) Canada. Ontario OELs. (Control of	2006, The Workplace Safety / Type TWA TWA TWA TWA Exposure to Biological or Ch	And Health Act) Value 0.5 mg/m3 0.2 mg/m3 0.05 mg/m3 emical Agents)	Form Thoracic fraction.

Lead Acid Battery Wet, Filled With Acid

SDS Canada Issue date: September-2017

Components		Туре			Value	Form
Lead and lead compounds (inorganic) (CAS 7439-92-1)		TWA			0.05 mg/m3	
Canada. Quebec OELs. (M	inistry of Labor	- Regu	lation respecting	occupationa	al health and sa	fety)
Components	-	Туре			Value	
Antimony (CAS 7440-36-0)		TWA			0.5 mg/m3	
Electrolyte (Sulfuric acid) (CAS 7664-93-9)		STEL			3 mg/m3	
		TWA			1 mg/m3	
Lead and lead compounds (inorganic) (CAS 7439-92-1)		TWA			0.05 mg/m3	
logical limit values						
ACGIH Biological Exposure	Indices					
Components	Value		Determinant	Specimen	Sampling	Time
Lead and lead compounds (inorganic) (CAS 7439-92-1)	200 μg/l		Lead	Blood	*	

Appropriate engineering

Provide adequate ventilation. Provide easy access to water supply and eye wash facilities.

controls

Individual protection measures, such as personal protective equipment

None under normal conditions. Leak from a damaged or opened battery: Wear safety glasses with Eye/face protection

side shields (or goggles).

Skin protection

Hand protection None under normal conditions. Leak from a damaged or opened battery: Wear appropriate

chemical resistant gloves.

None under normal conditions. Leak from a damaged or opened battery: Wear suitable protective Other

clothing. Use of an impervious apron is recommended.

Respiratory protection None under normal conditions.

Thermal hazards When material is heated, wear gloves to protect against thermal burns.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

Issue date: September-2017

9. Physical and chemical properties

Appearance

Physical state Solid.

Sulfuric acid, liquid. Lead, solid. Form

Not available. Colour Odour Odourless. Odour threshold Not available.

< 1 рH

Melting point/freezing point Not available.

Initial boiling point and boiling

112.78 - 115.56 °C (235 - 240 °F) (Sulfuric acid)

range

Flash point

Below room temperature (as hydrogen gas).

Evaporation rate < 1 (n-BuAc=1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower 4 % (Hydrogen)

(%)

Lead Acid Battery Wet, Filled With Acid

SDS Canada

Flammability limit - upper 74 % (Hydrogen)

(%)

Vapour pressure 10 mm Hg Vapour density > 1 (Air = 1) Relative density 1.27 - 1.33

Solubility(ies)

Solubility (water) 100 % (Sulfuric acid)

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidising properties Not oxidising.

Stability and reactivity

Reactivity Chemical The product is non-reactive under normal conditions of use, storage and transport.

stability Possibility of Stable at normal conditions.

hazardous Will not occur.

reactions

Conditions to avoid Overcharging. Ignition sources.

Incompatible materials Strong bases. Combustible organic materials. Reducing Agents. Finely divided metals. Strong

oxidizers. Water.

Hazardous decomposition

products

Sulfur dioxide. Sulfur trioxide. Carbon monoxide. Sulfuric acid. Hydrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation Exposure to contents of an open or damaged battery: Harmful if inhaled. Causes severe

respiratory tract irritation.

Skin contact Exposure to contents of an open or damaged battery: Causes severe skin burns.

Eye contact Exposure to contents of an open or damaged battery: Causes serious eye damage.

Ingestion Exposure to contents of an open or damaged battery: Harmful if swallowed.

Symptoms related to the

physical, chemical and toxicological characteristics

Exposure to contents of an open or damaged battery: Dust may irritate the eyes and the

respiratory system.

Information on toxicological effects

Acute toxicity Exposure to contents of an open or damaged battery: Harmful if inhaled or swallowed.

Components Species Test Results

Electrolyte (Sulfuric acid) (CAS 7664-93-9)

Acute Oral

LD50 Rat 2140 mg/kg

Skin corrosion/irritation Exposure to contents of an open or damaged battery: Causes severe skin burns.

Serious eye damage/eye Exposure to contents of an open or damaged battery: Causes serious eye damage.

irritation

Respiratory or skin sensitisation Canada - Alberta OELs: Irritant

Antimony (CAS 7440-36-0) Irritant

Respiratory sensitisation No data available.

Skin sensitisation No data available.

Germ cell mutagenicity No data available.

923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 5 / 8

The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid Carcinogenicity

mists containing sulfuric acid" as a known human carcinogen, (IARC category 1). This

classification applies only to mists containing sulfuric acid and not to sulfuric acid or sulfuric acid

solutions.

ACGIH Carcinogens

Electrolyte (Sulfuric acid) (CAS 7664-93-9) A2 Suspected human carcinogen.

Lead and lead compounds (inorganic) (CAS 7439-92-1) A3 Confirmed animal carcinogen with unknown relevance to

Canada - Alberta OELs: Carcinogen category

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Suspected human carcinogen.

Lead and lead compounds (inorganic) (CAS 7439-92-1) Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

Lead and lead compounds (inorganic) (CAS 7439-92-1) Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

Electrolyte (Sulfuric acid) (CAS 7664-93-9) 1 Carcinogenic to humans.

Lead and lead compounds (inorganic) (CAS 7439-92-1) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Known To Be Human Carcinogen.

Lead and lead compounds (inorganic) (CAS 7439-92-1) Reasonably Anticipated to be a Human Carcinogen.

None under normal conditions. Exposure to contents of an open or damaged battery: May damage Reproductive toxicity

fertility or the unborn child.

Specific target organ toxicity -

single exposure

None under normal conditions. Exposure to contents of an open or damaged battery: Causes damage to organs (respiratory system).

Specific target organ toxicity -

repeated exposure

None under normal conditions. Exposure to contents of an open or damaged battery: Causes

damage to organs through prolonged or repeated exposure: Respiratory system.

Due to the physical form of the product it is not an aspiration hazard. Aspiration hazard

Chronic effects Exposure to contents of an open or damaged battery: Heavy lead exposure may result in central

nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic)

tissues. Chronic inhalation of sulfuric acid mist may increase the risk of lung cancer.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment. Exposure to contents of an open or damaged battery: Very toxic to aquatic life with long lasting

effects.

Components Test Results Species

Lead and lead compounds (inorganic) (CAS 7439-92-1)

LC50 Rainbow trout, donaldson trout 1.17 mg/l, 96 Hours

(Oncorhynhus mykiss)

The degradation half-life of the product is not known. Lead and its compounds are highly persistent Persistence and degradability

in water.

Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants, but very little Bioaccumulative potential

bioaccumulation occurs through the food chain.

Mobility in soil If the product enters soil, one or more constituents will or may be mobile and may contaminate

groundwater.

Mobility in general The product is insoluble in water and will spread on the water surface.

None known. Other adverse effects

13. Disposal considerations

Disposal instructions Recycle the batteries, as the primary disposal method. Avoid discharge into water courses or onto

the ground. Dispose of this material and its container to hazardous or special waste collection

point. Neutralize electrolyte/sulfuric acid.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Local disposal regulations

Spent lead-acid batteries are not regulated as hazardous waste when recycled. Hazardous waste code

Depending upon circumstances, the following waste codes may apply:

Spilled electrolyte/Sulfuric acid. D002: Corrosive waste

Lead Acid Battery Wet, Filled With Acid 923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 Waste from residues / unused

products

Avoid discharge into water courses or onto the ground.

Contaminated packaging

Since emptied containers retain product residue, follow label warnings even after container is

emptied.

14. Transport information

TDG

UN number UN2794

UN proper shipping name

BATTERIES, WET, FILLED WITH ACID, electric storage

Transport hazard class(es)

Class 8
Subsidiary risk Packing group III
Environmental hazards No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN2794

UN proper shipping name

Batteries, wet, filled with acid electric storage

Transport hazard class(es)

Class 8
Subsidiary risk Packing group Environmental hazards No
ERG Code 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packing Instruction: 870

IMDG

UN number UN2794

UN proper shipping name

BATTERIES, WET, FILLED WITH ACID electric storage

Transport hazard class(es)

Class 8
Subsidiary risk Packing group Environmental hazards
Marine pollutant No

EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packing Instruction: P801 Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

L 73/78 and

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed. Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Antimony (CAS 7440-36-0)

Electrolyte (Sulfuric acid) (CAS 7664-93-9)

Precursor Control Regulations

Electrolyte (Sulfuric acid) (CAS 7664-93-9) Class B

International regulations

Stockholm Convention

Not applicable.

Lead Acid Battery Wet, Filled With Acid

923330 Version #: 04 Revision date: 19-September-2019 Issue date: September-2017 7 / 8

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

16. Other information

Issue date 19-September-2017 19-September-2019 Revision date

04 Version No.

LD50: Lethal Dose 50%. List of abbreviations

LC50: Lethal Concentration 50%.

IARC Monographs. Overall Evaluation of Carcinogenicity References

Registry of Toxic Effects of Chemical Substances (RTECS)

The information in this SDS was obtained from sources which we believe are reliable, but no Disclaimer

warranty or representation as to its accuracy or completeness is hereby given. Users should consider the information herein only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal, the safety and health of employees and customers

and the protection of the environment.

8/8

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).