



# RUST-OLEUM® OUTDOOR FABRIC PAINT

## DESCRIPTION AND USES

Rust-Oleum® Outdoor Fabric Paint is an easy way to refresh your worn outdoor fabrics with color. It provides broad coverage with excellent adhesion and flexibility. Fabrics stay soft\* to the touch and maintain long-lasting color. Its UV and weather resistant barrier makes it ideal for outdoor fabrics. Great for use on outdoor furniture cushions and pillows, sun umbrellas and more.

## PRODUCTS

SKU	DESCRIPTION (Aerosol)
352115	Dark Red
352116	Navy
352117	Olive Green
352118	Khaki
352121	Medium Gray
352122	Burnt Orange
352124	Turquoise
356101	White

## PRODUCT APPLICATION

### READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist. Works best on weathered outdoor polyester fabrics. For other outdoor fabrics, additional coats may be required.

### SURFACE PREPARATION

Ensure all debris is removed. Clean with soap and water, rinse and let dry.

### PRIMING

Priming is not required, but Rust-Oleum® White Outdoor Fabric Paint can be used as a primer and is recommended on dark fabrics or fabrics with a pattern. Apply 1-2 light coats of primer. Allow to dry. Wait a minimum of 1 hour before painting.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle, **DO NOT STRIKE CAN**. Contact Rust-Oleum. Hold can upright 6-8" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply a light coat. Wait 30 minutes between each additional coat. Too many coats or heavy application could result in a stiffer feeling fabric.

### DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 1 hour and to handle in 2 hours. Fully dry in 24 hours. Machine washable in 3 days.

### CLEAN-UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with soap and water. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse it with warm water and wipe off. Do not insert any object into can valve opening.

\*Softer than regular spray paint.

<small>• TRUSTED QUALITY SINCE 1921 •</small> <b>RUST-OLEUM®</b> <i>Outdoor Fabric</i> <i>Paint</i>	<b>TECHNICAL DATA</b>	<b>SPC-111</b>
<b>RUST-OLEUM®</b> <b>OUTDOOR FABRIC PAINT</b>		

**PHYSICAL PROPERTIES**

		OUTDOOR FABRIC PAINT
<b>Resin Type</b>		Polyurethane
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Water, Ethanol
<b>MIR</b>		0.3-0.5 Max
<b>Fill Weight</b>		12 ounces
<b>Practical Coverage (assumes 15% material loss)</b>		Approximately 10 sq.ft./can
<b>Dry Times at 77°F (25°C) and 50% Relative Humidity</b>	<b>Touch</b>	1 hour
	<b>Handle</b>	2 hours
	<b>Recoat</b>	30 minutes
	<b>Full Cure</b>	24 hours
<b>Shelf Life</b>		24 months
<b>Flash Point</b>		85°F (29°C)
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.