

BEHR MARQUEE™ Interior Semi-Gloss Enamel

- · Stain-Blocking Paint & Primer
- Exclusive MARQUEE™ Interior One-Coat Color Collection
- Superior Stain Resistance
- · Scrubbable, Easy-Clean Finish
- · Antimicrobial-Mildew Resistant Finish
- Lifetime Guarantee*
- Low VOC, 100% Acrylic
- Ideal for Every Room

No. 3450 ULTRA PURE WHITE® No. 3453 Deep Base No. 3454 Medium Base



1 Hr Dry Time 2 Hr Recoat Time



Up to 400 Sq. Ft. Coverage per Gallon



Soap & Water Clean-Up



Protect from Freezing

FOR TINT BASES - DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

BEHR MARQUEE™ Stain-Blocking Paint & Primer is our best interior paint, with exceptional hide and stain resistance plus an Exclusive MARQUEE Interior One-Coat Color Collection.

WHERE TO USE

Ideal for every room and delivers a radiant, sleek finish.

PREPARATION & PRIME

Properly prepare and clean all surfaces. Remove loose paint, wash off dirt and grease with detergent, rinse and allow to dry. Remove mildew stains with a mildew stain remover. Scuff sand glossy surfaces and repair imperfections. Remove all dust with a damp cloth, allow to dry. Allow new stucco, plaster and masonry to cure for 30 days before painting.

Use BEHR MARQUEE paint as a primer for uncoated, porous or repaired interior surfaces, including woods that contain tannins (two primer coats required for redwood and cedar). Lock in stains with BEHR MARQUEE as a spot primer. For heavy stains, test for stain bleed-through by applying BEHR MARQUEE to a small section. If the stain bleeds through, spot prime with another coat to the stained area and test again before topcoating. If bleeding continues, a longer dry time is needed before topcoating.

*LIMITED LIFETIME GUARANTEE Behr Process Corporation guarantees your satisfaction with the performance of this paint when applied to a properly prepared surface and cared for according to the label directions. This guarantee shall be effective for so long as you reside in your home and is made to the original residential consumer paint purchaser. This guarantee is not transferable. If you are not satisfied with this paint's performance, Behr Process Corporation will, at its option and upon proof-of-purchase (the original receipt), either furnish an equivalent amount of paint or refund the purchase price of this paint to you. This guarantee excludes (1) labor and costs of labor for the application or removal of any product and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).



APPLICATION

Apply when air and surface temperatures are between 50-90° F (10-32° C). Stir paint occasionally, Intermix containers of same product to ensure color and sheen uniformity. Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 - .019" spray tip. 60 mesh filter). Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon. Fully saturate roller for best coverage. Untinted ULTRA PURE WHITE and colors outside of the MARQUEE Interior One-Coat Color Collection may require more than one coat to achieve complete hide and a uniform finish. Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time. After 4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant. Do not use on floors.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice and the perfect color coordination with COLORSMART BY BEHR®.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN, PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before vou start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED, CONTAINS: ETHYLENE GLYCOL, MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.