



# CONCRETE PATCHING COMPOUND

PRODUCT NOS. 8650-35

## PRODUCT DESCRIPTION

QUIKRETE® Concrete Patching Compound is a ready to use trowel applied acrylic latex formulation for crack and spall repair for concrete, stucco or masonry walls, sidewalks, patios, driveways, etc.

## PRODUCT USE

QUIKRETE® Concrete Patching Compound repairs and fills spalls (surface imperfections) and cracks up to ¼" (6 mm) deep in concrete, masonry, stucco, sidewalks, patios, and driveways.

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces.
- Weather resistant
- Excellent Adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

**Packaging:** QUIKRETE® Concrete Patching Compound is available in 1 qt. (0.9 L) pails.

**Colors:** QUIKRETE® Concrete Patching Compound is available in concrete gray or white.

**Coverage:** QUIKRETE® Concrete Patching Compound will cover approximately 3.25 sq. ft (0.3 M<sup>2</sup>) at a 1/8" (3 mm) thickness.

## INSTALLATION

### SURFACE PREPARATION

Surface must be clean, dry, and free of grease, dust, or loose particles. Remove all loose stones and chips from damaged area before filling.

### APPLICATION

Apply to cracks or small spalled areas using a margin trowel. For larger areas use a stainless steel pool trowel or plastic trowel. Use heavy trowel pressure to force the product into the surface. For small areas thicker than ¼" (6 mm), apply a 1/8" (3 mm) layer first and allow at least 24 hours before applying a second layer.

## DIVISION 3

Common Work Results  
for Concrete 03 05 00



**Curing:** QUIKRETE® Concrete Patching Compound will form a surface skin in 20 – 40 minutes and will become hard in 4 – 6 hours depending on temperature and humidity. Additional curing will continue for about 3 days, longer under low temperature and high humidity conditions.

**Clean up:** Use soapy water and scrub with a stiff fiber brush before material has dried.

## PRECAUTIONS

Apply only when temperature is between 50°F (10°C) and 90°F (32°C). Do not apply if rain threatens or is predicted within 12 hours. Wait at least 24 hours before painting. Use latex paints only. Protect from freezing. Store between 35°F (2°C) and 100°F (38°C). Keep container tightly sealed when not in use.

## WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies  
One Securities Centre  
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305  
(404) 634-9100 • Fax: (404) 842-1425