



## BEHR PREMIUM® Concrete & Masonry Bonding Primer

No. 880 Clear

- Interior/Exterior
- For Uncoated & Previously Coated Surfaces
- Easy to Apply
- Promotes Topcoat Adhesion
- Reduces Peeling & Hot Tire Pick-Up



Coverage:  
350-500 Sq. Ft.



Dry Time:  
2 Hr. Dry to Touch.  
4 Hr. Ready for Topcoat



Clean-Up:  
Soap & Water



Protect  
from Freezing

PRODUCT DRIES CLEAR - IT WILL LOOK MILKY IN CAN AND AT INITIAL APPLICATION.

**CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

### WHERE TO USE

Uncoated and Previously Coated Interior or Exterior surfaces such as Concrete, Masonry, Stucco, Cinder Block, and any Porous Stone or Brick. Not designed for use on wood, metal, or silicone treated surfaces. **NOTE: SOME SURFACES MAY APPEAR SLIGHTLY DARKER AFTER PRODUCT DRIES.**

### PREPARATION† (Proper Surface Preparation is Required.)

#### For Uncoated Surfaces:

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease.
- New concrete must cure for a minimum of 30 days prior to priming.
- Patch all holes and cracks and allow to dry.
- For touch-ups where surface coatings have failed, completely remove all loose or peeling paint.
- Use a paint stripper to remove any previous coatings or sealers.
- Clean and etch surface using a product such as muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper.
- Wipe your fingers over the clean, dry floor to check for dust or powder. Ensure there is no residue on your fingers that may have been left from the etcher. If residue is found, rinse the surface to remove residue. Allow the surface to dry completely. Sprinkle a few drops of water onto the surface. If water is quickly absorbed and the surface feels like 150 grit sandpaper, the surface is ready. If not, re-etch.

#### For Previously Coated Surfaces:

- For a painted surface in sound condition, use a product to clean and prepare the surface.
- If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface.
- Scuff sand glossy surfaces.
- Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.

### APPLICATION

- **DO NOT THIN.**
- Stir primer thoroughly before and occasionally during application.
- Avoid temperatures lower than 50° F
- Use product when air and surface temperatures are between 50-90° F (10-32° C).
- Apply using a high quality pump sprayer, 1/4" - 3/8" nap roller, nylon/polyester brush or a pad applicator.

### DRY TIME

- Longer dry time required in cooler temperatures and in higher humidity. **Must apply a topcoat after at least 4 hours, but before 30 days.**

### DISPOSAL

- Properly dispose of all soiled rags. To recycle or properly dispose of product in your community, contact your household refuse collection service.

### LIMITED WARRANTY

Visit [behr.com/warranty](http://behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**† WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**⚠ WARNING** Cancer and Reproductive Harm [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**WARNING! CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS: SODIUM LAURETH SILICATE AND SODIUM ORTHOSILICATE.** Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe the dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. Wear eye protection and protect skin with chemical resistant clothing. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

