

D8200-2EQ Series Fiberglass Specialty Extension Ladders



D8200-2EQ The Equalizer® series eliminates uneven ground with the factory installed adjustable EverLevel® leveling system. This system precisely adjusts in 3/8 in increments up to 8 1/4 in, making it easy to use. The dual action feet on the ladder are for use on hard or penetrable surfaces and swivel easily. The TRACTION-TRED® D-rungs are slip resistant. The ladder has a duty rating of 300 lbs making it durable, long lasting and able to meet the demands of the job. The exclusive ALFLO® rung joint means a TWIST-PROOF® performance every time, and the fiberglass rails are non-conductive.

Features

- Alflo rung joint for Twist-Proof performance
- Base section may be used as a single ladder
- Direct rung to rail connections
- Electrically non-conductive side rails
- Guides at top of base section
- Guides on bottom of fly section
- Integrated Leveling
- Interlocking side rails
- Mar-resistant molded end caps
- Rail shield and shoe bracket protects rail
- Rope and pulley system
- Rope clamp ties rope to rung
- Rugged gravity spring locks
- Shoe with slip-resistant pad and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D8220-2EQ	20 ft	19 ft	17 ft	17 ft	10 ft	54
D8224-2EQ	24 ft	23 ft	21 ft	21 ft	12 ft	62
D8228-2EQ	28 ft	27 ft	25 ft	25 ft	14 ft	70