



# MODEL DD70PE

## 70 TRUE PINTS PER DAY™



### WORRY-FREE PUMP FUNCTION

THE PATENTED PUMP FUNCTION ALLOWS THE UNIT TO CONTINUOUSLY DISCHARGE MOISTURE WITHOUT CONSTANTLY EMPTYING A BUCKET. THE UNIT CAN PUMP WATER UPWARD TO DRAIN OUT A BASEMENT WINDOW OR INTO A SINK, UP TO 16' WITH THE PROVIDED HOSE.



### LCD ELECTRONIC CONTROLS

CHOOSE THE IDEAL HUMIDITY LEVEL BY ADJUSTING THE HUMIDISTAT. THE ELECTRONIC CONTROLS ALLOW YOU TO MONITOR RELATIVE HUMIDITY AND TEMPERATURE.



### VISIBLE WATER LEVEL

WITH ITS FRONTALLY LOCATED TANK AND TRANSPARENT WATER LEVEL WINDOW, YOU CAN EASILY SEE HOW MUCH WATER HAS BEEN COLLECTED.



MODEL	DD70PE
SAP CODE	0148870201
UPC	0-44387-00070-3
SCC14	NA
UNIT (LxWxH)	15.3 x 12.4 x 24.3
VOL Unit ft3	2.7
UNIT Weight (Lbs)	37.9
CARTON (LxWxH)	14 x 16.5 x 27.2
VOL Carton ft3	3.6
CARTON Weight	41.9
Pcs per Master	1
MASTER (LxWxH)	
VOL Master ft3	
MASTER Weight	
CONTAINER 20'	270
CONTAINER 40'	549
CONTAINER 40HC'	
CONTAINER 45'	

### EMPTY THE COLLECTED WATER 3 WAYS:

- CONTINUOUSLY THROUGH **PATENTED PUMP SYSTEM**: [16 FT HOSE INCLUDED]
- PASSIVELY THROUGH THE 3' HOSE [INCLUDED]
- DIRECTLY INTO THE TANK [6.0 LITTER CAPACITY]

### ELECTRONIC CLIMATE CONTROL WITH LCD DISPLAY:

- ADJUSTABLE HUMIDISTAT
- ROOM THERMOSTAT
- 24-H TIMER
- ANTI-FROST DEVICE (DOWN TO 41 °F)
- FAN SPEED CONTROL — 2 FAN SPEEDS

### TANK CONTROL SYSTEM WITH ALARM

CAN BE EASILY MOVED BY CASTOR WHEELS & HANDLES

POWER: 1500W



R410A REFRIGERANT GAS

UPDATED 4/05/2013

DISCLAIMER: FEATURES AND COLORS ARE TENTATIVE AND SUBJECT TO CHANGE WITHOUT NOTICE.

# DEHUMIDIFIER