

D5900-2 Series Fiberglass Multi Section Extension Ladders




D5900-2 fiberglass extension ladders feature a rounded rail for improved ergonomics while climbing and carrying. The non-conductive fiberglass rails are interlocking and the exclusive ALFLO® rung joint means TWIST-PROOF® performance every time. The TRACTION-TRED® D rungs are slip resistant. These extension ladders are lightweight for transporting and maneuvering yet still have a duty rating of 225 lbs.

Features

- Alflo rung joint for Twist-Proof performance
- Base section may be used as a single ladder
- Direct rung to rail connections
- Electrically non-conductive side rails
- Guides on bottom of fly section
- Interlocking side rails
- Mar-resistant molded end caps
- Rope and pulley system
- Rope clamp ties rope to rung
- Rugged gravity spring locks
- Shoe with slip-resistant pad and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D5916-2 	16 ft	16 ft	13 ft	13 ft	8 ft	27
D5920-2	20 ft	19 ft	17 ft	17 ft	10 ft	33
D5924-2	24 ft	23 ft	21 ft	21 ft	12 ft	39