

HEAVY DUTY

HIGH PERFORMANCE **LATEX TECHNOLOGY**

A High Strength, Instant Grab, Exterior Grade Adhesive for Heavy Construction & Remodeling Projects.



STRONGER HOLDING POWER

More strength for heavier interior & exterior projects



Reduces nailing, bracing & clamping, ideal for vertical projects



Excellent adhesion on common building materials



HEAVY DUTY

EXTERIOR GRADE PERFORMANCE









LOCTITE® PL

Strength at 120°F (psi)*	530	20	327	460
Extrusion Force at 32°F (lbf)+	47	54	55	90

^{*}Pounds per square inch of force required to break bond of adhesive cured at extreme temperatures

FEATURES









PRODUCT DETAILS

RECOMMENDED USE

Subfloor, deck, structural paneling, drywall & trim molding installation, general construction & repair projects.

NOT RECOMMENDED FOR

Mirror installation, constant water exposure, bonding two non-porous materials, for at/or below grade applications.

ADHERES TO

 Aluminum Brick

Ceramic

- Drywall
- Masonry
- OSB Wood
- Other Common
- **Building Materials**
- Concrete Plywood

TYPICAL PHYSICAL PROPERTIES

Solids: 64% - 68% Shelf Life: 18 months

Skin Time: 15 minutes

Cure Time: 7 days

Coverage: 10 FL. OZ.

1/4" bead yields 32 linear ft. 3/8" bead yields 14 linear ft.

28 FL. OZ.

1/4" bead yields 86 linear ft. 3/8" bead yields 38 linear ft.

APPLICATION TEMPERATURE

40°F - 100°F

SERVICE TEMPERATURE

0°F - 120°F

SPECIFICATIONS

ASTM C557 **Meets or Exceeds**

SKU SPECIFICATIONS

Description	Size	Package Code	GTIN	Case Pack	Case Weight	Case Dims. (LxWxH)	Case Volume (cu. ft.)	Cases Per Pallet
DynaGrip Heavy Duty	5 OZ.	0 70798 27508 9	100 70798 27508 6	12	5.99 lbs.	9.75" x 7.5" x 9.5"	0.40	100
DynaGrip Heavy Duty	10 OZ.	0 70798 27509 6	100 70798 27509 3	12	12.08 lbs.	8" x 6" x 12"	0.33	108
DynaGrip Heavy Duty	28 OZ.	0 70798 27510 2	100 70798 27510 9	12	32.56 lbs.	10.5" x 8" x 17"	0.83	60

⁺Pounds of force required to extrude bead of adhesive from cartridge at freezing temperatures