# SAFETY DATA SHEET



Date of issue/Date of revision 21 May 2019

**Version 7** 

### **Section 1. Identification**

Product name : PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Product code : 00392818

Other means of : Not available.

identification Product type

: Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Consumer applications, Professional applications.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Not applicable.

**Manufacturer** : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272

**Emergency telephone** : (412) 434-4515 (U.S.)

<u>number</u> (514) 645-1320 (Canada)

01-800-00-21-400 or + 52 55 5559 1588 (Mexico)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: CARCINOGENICITY - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 23.1% (Oral), 23.1% (Dermal), 23.1% (Inhalation)

This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many PPG products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).

#### **GHS** label elements

United States Page: 1/12

Date of issue 21 May 2019

Version 7

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

### Section 2. Hazards identification

**Hazard pictograms** 

Signal word : Warning

**Hazard statements** : Suspected of causing cancer.

**Precautionary statements** 

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

**Prevention**: Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Wear protective gloves. Wear eye or face protection.

Wear protective clothing.

**Response** : IF exposed or concerned: Get medical attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Supplemental label

elements

: Contains isothiazolinones. May cause allergic reaction. Sanding and grinding dusts

may be harmful if inhaled. Emits toxic fumes when heated.

**Hazards not otherwise** 

classified

: None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product name : PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Ingredient name	%	CAS number
	≥10 - ≤20	13463-67-7
Diatomaceous earth	≥1.0 - ≤5.0	61790-53-2

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

**Description of necessary first aid measures** 

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

United States Page: 2/12

### Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

### Section 4. First aid measures

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water Skin contact

or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep

person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact No known significant effects or critical hazards. : No known significant effects or critical hazards. Inhalation **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

#### Over-exposure signs/symptoms

**Eve contact** : No specific data. Inhalation No specific data. **Skin contact** : No specific data. : No specific data. Ingestion

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented

from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products Decomposition products may include the following materials:

carbon oxides metal oxide/oxides

> **United States** Page: 3/12

Date of issue 21 May 2019

Version 7

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

# Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special precautions** 

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

United States Page: 4/12

Date of issue 21 May 2019

Version 7

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

### Section 7. Handling and storage

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits
tranium dioxide	OSHA PEL (United States, 5/2018).
	TWA: 15 mg/m³ 8 hours. Form: Total dust
	ACGIH TLV (United States, 3/2018).
	TWA: 10 mg/m <sup>3</sup> 8 hours.
Diatomaceous earth	OSHA PEL Z3 (United States, 6/2016).
	TWA: 20 mppcf 8 hours.
	TWA: 80 mg/m³ / (%SiO2) 8 hours.

#### Key to abbreviations

Α	= Acceptable Maximum Peak	S	=	Potential skin absorption
<b>ACGIH</b>	= American Conference of Governmental Industrial Hygienists.	SR	=	Respiratory sensitization
С	= Ceiling Limit	SS	=	Skin sensitization
F	= Fume	STEL	=	Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	=	Total dust
OSHA	Occupational Safety and Health Administration.	TLV	=	Threshold Limit Value
R	= Respirable	TWA	=	Time Weighted Average
Z	= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances			

#### Consult local authorities for acceptable exposure limits.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

> **United States** Page: 5/12

Date of issue 21 May 2019

Version 7

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

## Section 8. Exposure controls/personal protection

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety glasses with side shields.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Various : Alcohol-like. Odor **Odor threshold** : Not available.

: 9 рH

: Not available. **Melting point** : 100°C (212°F) **Boiling point** 

Closed cup: Not applicable. [Product does not sustain combustion.] Flash point

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

: 0.05 (butyl acetate = 1) **Evaporation rate** 

: 3.3 kPa (25 mm Hg) [room temperature] Vapor pressure

Vapor density : Not available.

**Relative density** : 1.27

> **United States** Page: 6/12

### Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

### Section 9. Physical and chemical properties

Density (lbs / gal) : 10.6

**Solubility** : Soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

**Volatility** : 61% (v/v), 47.724% (w/w)

% Solid. (w/w) : 52.276

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Decomposition products may include the following materials: carbon monoxide, carbon

dioxide, smoke, oxides of nitrogen.

## **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral	Rabbit	>6.82 mg/l >5000 mg/kg >5000 mg/kg	4 hours - -

**Conclusion/Summary**: There are no data available on the mixture itself.

**Irritation/Corrosion** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

United States Page: 7/12

### Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

## **Section 11. Toxicological information**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
Diatomaceous earth	-	3	-

#### **Carcinogen Classification code:**

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA:

Not listed/not regulated: -

#### **Reproductive toxicity**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which may cause damage to the following organs: upper respiratory

tract, eyes.

### **Aspiration hazard**

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

United States Page: 8/12

Date of issue 21 May 2019

Version 7

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

## **Section 11. Toxicological information**

**Conclusion/Summary** 

: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many PPG products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

**Potential immediate** 

effects

Potential delayed effects

Potential delayed effects

Long term exposure

**Potential immediate** 

effects

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity Suspected of causing cancer. Risk of cancer depends on duration and level of

: Explosuren significant effects or critical hazards. Mutagenicity

: No known significant effects or critical hazards. **Teratogenicity Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

## Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

**United States** Page: 9/12

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

# **Section 12. Ecological information**

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### 14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.

### **Additional information**

DOT : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**United States** Page: 10/12

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

## Section 15. Regulatory information

#### **United States**

United States inventory (TSCA 8b): All components are listed or exempted.

United States - TSCA 5(e) - Substances consent order:

partially fluorinated alcohol, reaction products

Listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

partially fluorinated alcohol, reaction products Listed

**SARA 302/304** 

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

**SARA 311/312** 

Classification : CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
tranium dioxide	≥10 - ≤20	CARCINOGENICITY - Category 2

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 1 \* Flammability: 0 Physical hazards: 0

( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)** 

Health: 1 Flammability: 0 Instability: 0

Date of previous issue : 8/15/2018

Organization that prepared : EHS

the MSDS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

United States Page: 11/12

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

### **Section 16. Other information**

as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 12/12