



# SAFETY DATA SHEET

Issue Date 25-Jan-2016

Revision Date 26-Jan-2022

Version 5

## 1. IDENTIFICATION

### Product identifier

**Product Name** WET PATCH ROOF CEMENT

### Other means of identification

**Product Code** HE208  
**UN/ID no** UN1999  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Coatings Sealant  
**Uses advised against** No information available

### Details of the supplier of the safety data sheet

**Supplier Address**  
HENRY COMPANY  
15 Wallsend Dr.  
Scarborough, ON M1E 3X6  
Canada  
Web Site: [www.henry.com](http://www.henry.com)  
[www.ca.henry.com](http://www.ca.henry.com)

**Manufacturer Address**  
HENRY COMPANY  
999 N. Pacific Coast Hwy., Suite 800  
El Segundo, CA 90245-2716  
Web Site: [www.henry.com](http://www.henry.com) [www.ca.henry.com](http://www.ca.henry.com)

### Emergency telephone number

**Company Phone Number** 800-486-1278  
**Emergency Telephone** US and Canada only (toll-free) : 3E Company - 1-866-519-4752 (access code 334832)  
US/Canada, all other countries: 3E Company - +1-760-476-3962 (access code 334832)  
Mexico (additional contact option): 3E Company - +52 55 41696225 (Code 334832)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

and Canadian Workplace Hazardous Material Information System (WHMIS)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

### Label elements

#### **Emergency Overview**

#### **Warning**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



**Appearance** viscous

**Physical state** liquid

**Odor** Solvent

#### Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating / lighting/ mixing / equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

#### Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 If skin irritation occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep cool

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

#### Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Not applicable

#### Mixture

Chemical Name	CAS No	Weight-%
---------------	--------	----------

Asphalt *	8052-42-4	15 - 40
Limestone *	1317-65-3	10 - 30
Solvent naphtha, petroleum, medium aliphatic *	64742-88-7	10 - 30
Fullers earth *	8031-18-3	7 - 13
Cellulose *	9004-34-6	3 - 7

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
<b>Eye contact</b>	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with plenty of water.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
<b>Ingestion</b>	Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Remove all sources of ignition.

##### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.
-----------------	---

##### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO<sub>2</sub>, sand, earth, water spray or regular foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Flammable.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate
-----------------------------	---

ventilation, especially in confined areas. Use personal protective equipment as required.

### Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	-	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup>	-
Cellulose 9004-34-6	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 1 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Solvent
<b>Appearance</b>	viscous	<b>Odor threshold</b>	No information available
<b>Color</b>	black		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	No information available		
<b>Melting point / freezing point</b>	No information available		
<b>Boiling point / boiling range</b>	> 150 °C / 302 °F		
<b>Flash point</b>	42 °C / 108 °F	Pensky-Martens Closed Cup (PMCC)	
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit:</b>	6		
<b>Lower flammability limit:</b>	1		
<b>Vapor pressure</b>	No information available		
<b>Vapor density</b>	3.6		
<b>Relative density</b>	1 - 1.1		
<b>Water solubility</b>	Insoluble in water		
<b>Solubility in other solvents</b>	No information available		
<b>Partition coefficient</b>	No information available		
<b>Autoignition temperature</b>	>250 °C / 482 °F		
<b>Decomposition temperature</b>	No information available		
<b>Kinematic viscosity</b>	> 100 mm <sup>2</sup> /s	@ 40 °C	
<b>Dynamic viscosity</b>	No information available		
<b>Explosive properties</b>	Not an explosive		
<b>Oxidizing properties</b>	Not applicable		
<b>Other Information</b>			
<b>Softening point</b>	No information available		
<b>Molecular weight</b>	No information available		
<b>VOC Content (%)</b>	No information available		
<b>Density</b>	No information available		
<b>Bulk density</b>	No information available		

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Strong bases.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Based on available data, the classification criteria are not met.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt 8052-42-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 94.4 mg/m <sup>3</sup> ( Rat ) 4.5 h
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 25 mL/kg ( Rat )	> 3000 mg/kg ( Rabbit )	> 13 mg/L ( Rat ) 4 h
Cellulose 9004-34-6	> 5 g/kg ( Rat )	> 2 g/kg ( Rabbit ) > 2000 mg/kg ( Rabbit )	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h

### Information on toxicological effects

<b>Symptoms</b>	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Vapors may cause drowsiness and dizziness.
-----------------	---

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Sensitization</b>	Based on available data, the classification criteria are not met.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt 8052-42-4	-	Group 2B	-	X

*IARC (International Agency for Research on Cancer)*

*Group 2B - Possibly Carcinogenic to Humans*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.
<b>STOT - single exposure</b>	Target Organs. Respiratory system. Eyes. Skin. Central nervous system.
<b>STOT - repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Chronic toxicity</b>	May cause adverse effects on the bone marrow and blood-forming system.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	5,252.00 mg/kg
<b>ATEmix (dermal)</b>	2,573.00 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	67.40 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

### Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient
Asphalt 8052-42-4	>6

Other adverse effects

No information available

**13. DISPOSAL CONSIDERATIONS**Waste treatment methods**Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

D001

**14. TRANSPORT INFORMATION**DOT

**UN/ID no** UN1999  
**Proper shipping name** Tars, liquid  
**Hazard Class** 3  
**Packing Group** III  
**Special Provisions** B1, B13, IB3, T1, TP3  
**Description** UN1999, Tars, liquid, 3, III  
**Emergency Response Guide Number** 130

TDG

**UN/ID no** UN1999  
**Proper shipping name** Tars, liquid  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1999, Tars, liquid, 3, III

IATA

**UN/ID no** UN1999  
**Proper shipping name** Tars, liquid  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 3L  
**Special Provisions** A3  
**Description** UN1999, Tars, liquid, 3, III

IMDG

Transport in accordance with 2.3.2.5 of the IMDG Code  
**UN/ID no** UN1999  
**Proper shipping name** Tars, liquid  
**Hazard Class** 3  
**Packing Group** III  
**EmS-No** F-E, S-E  
**Special Provisions** 955  
**Description** UN1999, Tars, liquid, 3, III

## 15. REGULATORY INFORMATION

### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Asphalt - 8052-42-4	0.1

#### **SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

### US State Regulations

#### **California Proposition 65**

This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product

Chemical Name	California Proposition 65
Quartz - 14808-60-7	Carcinogen

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Asphalt 8052-42-4	X	X	X
Limestone 1317-65-3	X	X	X
Cellulose 9004-34-6	X	X	X



Water 7732-18-5	-	-	X
Quartz 14808-60-7	X	X	X
Ethanol, 2-[(2-aminoethyl)amino]- 111-41-1	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<u>NFPA</u>	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

Issue Date 25-Jan-2016

Revision Date 26-Jan-2022

**Revision Note**

No information available

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**