Non-Conductive Fish Rods For Wiring

Extreme Flexibility And Superior Strength

Available in three diameters, all rods feature the same size ferrules so they can be used together in any combination.



1/4" Rod - Long spans where rigidity is needed to cover the distance
- Minimum Bend Radius: 6"
- Tensile/Pull Strength: 750-lbs

3/16" Rod - Preferred for short runs or where space is more limited
- More flexible than 1/4"
- Minimum Bend Radius: 4"
- Tensile/Pull Strength: 500-lbs

5/32" Rod - Security, alarm, home theater, CATV, satellite installation
- The smallest diameter rod in Jameson's line
- Offers extreme flexibility while maintaining high strength
- Minimum Bend Radius: 3.5"
- Tensile/Pull Strength: 300-lbs

Glow Rod

1/4" GLOW ROD KITS

- Most Rigid Glow Rod
- Used For Long Spans
- Minimum Bend Radius: 6"
- Tensile/Pull Strength: 750 lbs

Part Number	Total Rod Length	Package Length	1/4" Glow Rod Kits
7-36-23T	24'	6'	Three 6' X 1/4" Rods, Two 3' X 1/4" Rods One Bullet Nose with Eyelet, One Hook
7-63T	18'	3'	Six 3' X 1/4" Rods One Bullet Nose with Eyelet, One Hook
7-34T	12'	4'	Three 4' X 1/4" Rods One Bullet Nose with Eyelet, One Hook
7-6	6'	*	One 6' X 1/4" Replacement Rod with Male and Female Ferrules
** Single rods are shipped with hanging tag, not in plastic kit tube*			



7-36-23T



7-63T

3/16" GLOW ROD KITS

- More Flexible For Short Runs
- Minimum Bend Radius: 4"
- Tensile/Pull Strength: 500 lbs

Part Number	Total Rod Length	Package Length	3/16" Glow Rod Kits
7S-45T	20'	5'	Four 5' X 3/16" Rods One Bullet Nose with Eyelet, One Hook
7S-718T	10.5'	18"	Seven 18" X 3/16" Rods One Bullet Nose with Eyelet, One Hook
7S-5	5'	*	One 5' X 3/16" Replacement Rod with Male and Female Ferrules
** Single rods shipped with hanging tag, not in plastic kit tube*			



7S-45T



7S-718T

5/32" GLOW ROD KITS

- Smallest Diameter Offers Extreme Flexibility With High Strength
- Ideal For Security and Alarm, Home Theater, CATV, Satellite Installation

Minimum Bend Radius: 3.5"
Tensile/Pull Strength: 300 lbs

Part Number	Total Rod Length	Package Length	5/32" Glow Rod Kits
7SS-36T	18'	6'	Three 6' X 5/32" Rods One Bullet Nose with Eyelet, One Hook
7SS-6	6'	*	One 6' X 5/32" Rod with Permanently Mounted Bullet Nose with Eyelet On Each End of Rod
			** Single rods shipped with hanging tag, not in clear plastic kit tube*



7SS-36T


7SS-6

Permanently mounted bullet nose on each end.

JAMESON
A SPARTACO COMPANY

Glow Rod

INSTALLER'S KIT

Part Number	Total Rod Length	Package Length	Installer's Kit
7-8-IK	35'	6'	Two 1/4" X 5' Rods, Two 1/4" X 2.5' Rods, Four 3/16" X 5' Rods
			Two Bullet Nose with Eyelet, Two Hooks, One Whisk



DELUXE KIT

Part Number	Total Rod Length	Package Length	Deluxe Kit
7S-65K	30'	6'	Six 3/16" X 5' Rods
			One Bullet Nose with Eyelet, One Hook, One Whisk, One Ball Chain Bullet Nose



VERSA KIT

Part Number	Total Rod Length	Package Length	Versa Kit
7-8VK	34'	6'	Two 1/4" X 6' Rods, Two 3/16" X 5' Rods, One 5/32" X 6' Rod
			One 5/32" X 6' Rod - Permanently Mounted Bullet Eye On Each End
			One Hook, One Whisk



ACCESSORIES

To handle any wiring situation





Accessory Kit:
Hook
Magnet
Whisk
Ball Chain
Bullet Nose with Ring
Bullet Nose with Eyelet

Part Number	Glow Rod Accessories
7-00A	Bullet Nose with Eyelet
7-01A	Hook
7-02A	Bullet Nose with Ring
7-03A	Whisk
7-04A	Ball Chain Bullet Nose
7-05A	Magnet
7-06AK	Accessory Kit



Magnet
Retrieve Ball Chain



Bullet Nose with Eyelet
Attach pull line to rod



Hook
Grasp and retrieve



Whisk
Guide rod; avoid obstacles



Bullet Nose with Ring
Pull line or grab with hook

Ball Chain Bullet Nose
Use with Magnet for retrieval