



GREAT STUFF™ WINDOW & DOOR INSULATING FOAM SEALANT WITH QUICK STOP™ STRAW TECHNOLOGY CLOSE THE GAP ON ENERGY LOSS THROUGH WINDOWS & DOORS.



The average U.S. home has a half mile of gaps and cracks¹ where air and moisture can enter. Installing energy-efficient windows and doors can greatly reduce air infiltration, but an area that is often overlooked is around windows and doors and their rough openings.



Close the Gap

Seal out energy loss and improve comfort by sealing the gaps between framework and rough openings with GREAT STUFF™ Window & Door Insulating Foam Sealant with QUICK STOP™ Straw Technology².

Reduces Air Leaks and Energy Costs

GREAT STUFF™ Window & Door Insulating Foam Sealant is a minimal-expanding polyurethane foam with low pressure build that forms a durable, airtight and water-resistant seal between a window or door frame and its rough opening. This specially formulated sealant:

- is minimal expanding and proven not to bow window or door frames when properly installed
- when cured remains soft and flexible. Cured foam can be stuffed back into the gap without trimming
- expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal



Now with NEW
**QUICK STOP™
Straw
Technology**

- Easy, stop-start product usage
- Less mess, less clean-up (saves time)
- Less wasted foam (increases efficiency)

Features and benefits at a glance

- Fills, seals and insulates around windows and doors and their rough openings
- Ready-to-use (straw applicator)
- Forms a long-lasting weathertight seal to minimize drafts
- Repels/deflects water
- Enhances energy efficiency of the window or door and improves comfort by reducing drafts
- Once cured, remains soft and flexible, allowing natural expansion and contraction between the frame and rough opening
- Tack free in 5-15 minutes³; Trims in one hour
- Paintable, stainable and sandable
- Yellow colored foam
- All-direction dispensing
- UL Classified
- Conforms to ASTM & AAMA standards
- CCMC #13074-L

¹ www.energystar.gov

² Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

³ 70 ± 5 °F and 50 ± 5 % RH, 1 inch bead diameter, 6 inch length. Cure rate is dependent on temperature, humidity and size of foam bead.

Where to Use GREAT STUFF™ Window & Door Insulating Foam Sealant

Use GREAT STUFF™ Window & Door Insulating Foam Sealant to seal around windows and doors and their rough openings.



Doors and their rough openings



Windows and their rough openings



When cured, remains soft and flexible. Cured foam can be stuffed back into the gap without trimming.

GREAT STUFF™ Window & Door Insulating Foam Sealant is Cost Effective

- One 16 oz. can foams 6-8 average sized residential windows (36" x 60", 3/8" wide gap, and 1" deep)

Greatness comes in many forms

Did you know that the average U.S. home has a 1/2 mile of gaps and cracks?*** Seal them with GREAT STUFF™

Each GREAT STUFF™ Insulating Foam Sealant* is specially formulated to seal gaps and cracks to block air, moisture and even pests. Our comprehensive line of ready-to-use sealants is a simple, inexpensive money-saving solution for any do-it-yourself homeowner.

- **GREAT STUFF™ Gaps & Cracks*** — Foam sealant that expands to seal and insulate gaps up to one inch.
- **GREAT STUFF™ Window & Door*** — Minimally expanding foam that seals between a window or door and its rough opening.
- **GREAT STUFF™ Fireblock*** — Impedes spread of fire and smoke through service penetrations.***
- **GREAT STUFF™ Big Gap Filler*** — Foam sealant that expands to seal and insulate gaps up to three inches.
- **GREAT STUFF™ Pestblock*** — Blocks pests out of the home by eliminating points of entry.



In the United States

The Dow Chemical Company
Dow Building Solutions
 1501 Larkin Center Drive
 Midland, MI 48674

In Canada

Dow Chemical Canada ULC
Dow Building Solutions
 2400, 215 – 2 Street S.W.,
 Calgary, Alberta T2P 1M4

For Technical Information:

1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

dowgreatstuff.com

dowgreatstuff.ca

dowbuildingsolutions.com

For Sales Information:

1-800-232-2436 (English)
1-800-565-1255 (French)

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release The Dow Chemical Company of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call Dow at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood-burning stoves, gas stoves and gas dryers, are properly vented to the outside. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

GREAT STUFF™ Insulating Foam sealant and adhesive products contain isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death. Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

*Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

**www.energystar.gov

***Intended for use in residential application to maintain the continuity of an approved fire block material.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

Printed in the U.S.A.

Form No. 179-15219-0315 CDP
 Form No. 178-15116-0315 CDP