



BEHR PREMIUM™ AEROSOL

PRODUCT INFORMATION

BEHR PREMIUM™ Aerosol features an enhanced formulation that combines paint and primer† in a single can, delivering a premium, durable finish. Designed for both indoor and outdoor use, BEHR PREMIUM™ Aerosol can be used on wood, metal, cast stone and wicker. Weather and corrosion resistant, it delivers a reliable, long-lasting finish. The unique, ergonomic shape of the BEHR PREMIUM™ Aerosol can and its comfort tip deliver a superior spray experience that fights fatigue so you can create a smooth finish every time.

†A primer coat may be needed on some surfaces.

RECOMMENDED USES:

Ideal for use on properly prepared surfaces such as:

- Wood
- Metal
- Plastic
- Cast Stone
- Wicker

CONTAINER CAP PROVIDES CLOSE APPROXIMATION OF COLOR AND SHEEN OF THE PRODUCT.

PRODUCT SPECIFICATIONS:

Colors:

- B000144 Black Gloss
- B000244 Orion Gray Gloss
- B000344 Lunar Surface Gloss
- B000444 Hidden Sea Glass Gloss
- B000544 Inked Gloss
- B000644 Blazing Bonfire Gloss
- B000744 Baronial Brown Gloss
- B000844 No More Drama Gloss
- B000944 Flirt Alert Gloss
- B001044 Unmellow Yellow Gloss
- B001144 Luck of the Irish Gloss
- B001244 Congo Gloss
- B001344 Venom Gloss
- B001444 Tropics Gloss
- B001544 Mayan Treasure Gloss
- B001644 Sugar Beet Gloss
- B001744 Outdoor Café
- B001844 Khaki Shade Gloss
- B001944 White Gloss
- B002044 White Matte
- B002144 Black Matte
- B002244 Lunar Surface Flat
- B002344 Clear Flat
- B002444 Resort Sunrise Gloss
- B004744 White Primer
- B004944 Gray Primer
- B005044 Off White 73
- B005744 Roasted Corn Gloss
- B006144 Beyond Navy Flat
- B006244 Adored Blue Gloss
- B006844 Black Satin
- B006944 White Satin
- B007044 Breezeway Satin
- B007144 Toasty Gray Gloss
- B007244 Deep Espresso Satin

Finish:

- Flat: < 5 @ 60
- Gloss: > 80 @ 60
- Sheen level depends on porosity of surface and various surface irregularities.

Resin Type: Modified Alkyd

Net Weight: 12 oz / 340 g

*% Solids by Volume: 17% ± 3%

*% Solids by Weight: 28% ± 3%

Max Product-Weighted MIR:

- Flat: 0.80
- Non-Flat: 0.95
- Primer: 0.70

Coverage: Up to 15 sq ft per can, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

SURFACE PREPARATION:

- The surface must be clean, free of dust, grease, wax, peeling paint, mold and mildew. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.
- Scrape off loose paint and sand to a smooth surface.
- For maximum adhesion, sand glossy surfaces thoroughly before coating.

Stain-Blocking:

- If stain-blocking performance is required, apply a coat of primer such as KILZ® ORIGINAL Interior/Exterior Oil-Based Aerosol Primer No. 1008.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION:

- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use.
- Test your spray application technique on a scrap surface or inconspicuous area before starting the project.
- Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted. Always start and finish spraying off the object. Each spray pass should overlap the previous pass by half.
- Apply multiple thin coats to prevent dripping and sagging. Allow to dry between each coat.

Dry Time: @ 77°F & 50% RH:

To Touch: 15 minutes

Re-coat: Before 1 hour or after 24 hours

Dry times are temperature, humidity, and film thickness dependent

CLEAN-UP/DISPOSAL:

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean with paint thinner or mineral spirits where allowed.
- Do not stick pins or wire into spray nozzle opening.
- Clean fresh overspray with VOC-compliant paint thinner or mineral spirits. Otherwise use acetone. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.
- Wipe off tip before storing.
- Do not burn or place in home trash compactor.
- For recycling or disposal information, contact your household refuse collection service.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 Ext. 2 (U.S.A. only). ©2021 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

*Values given here are from BEHR PREMIUM™ Aerosol Gloss White.





BEHR PREMIUM™ AEROSOL

CAUTIONS/LIMITATIONS:

- Temperature and humidity extremes can affect dry time and final appearance.
- Apply if surface, air and product temperatures are between 50° – 90°F.
- Avoid painting in direct sunlight.
- Avoid spraying in very windy and dusty conditions.
- Ensure adequate ventilation when spraying indoors.
- Cover adjacent areas to avoid overspray.
- Do not apply directly to galvanized steel without first applying a metal primer.
- Not for touch-up on surfaces previously painted with non-aerosol BEHR paint.

GENERAL INFORMATION:

DANGER. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN AND RESPIRATORY TRACT. VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. **MAY CONTAIN ACETONE, BUTYL ACETATE, PROPANE, ISOBUTANE, METHOXYISOPROPYL ACETATE, C8-9 ALKANE/CYCLOALKANE, LIMESTONE, CALCIUM CARBONATE, METHYL ETHYL KETONE, 2-BUTANONE, 3-ETHOXYPROPIONIC ACID ETHYL ESTER, DISTALLATES (PETROLEUM), C9-12 LIGHT ALKANES, ALIPHATIC PETROLEUM DISTILLATES, NAPHTHA (PETROLEUM), LIGHT AROM. SOLVENT NAPHTHA (PETROLEUM), CARBON BLACK, COBALT 2-ETHYLHEXANOATE, ZIRCONIUM CARBOXYLATE, CRYSTALLINE SILICA and TITANIUM DIOXIDE. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting.

FIRST AID: If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.

