






KNOCKOUTS							
SYMBOL	A	B	C	D	E	F	G
IN	.50	.75	1.00	1.25	1.50	2.00	2.50
MM	13	19	25	32	38	51	64



DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	MAXIMUM SYSTEM VOLTAGE	MAINS AMPERE RATING	SPACES	MAXIMUM CIRCUITS	MAIN WIRE SIZE AWG AL	MAIN WIRE SIZE AWG CU
HOM816L125PC	120/240VAC 1PH 3W	125	8	16	#6-2/0	#6-1
HOM816L125PGC		125	8	16	#6-2/0	#6-1
HOM1224L125PC		125	12	24	#6-2/0	#6-1
HOM1224L125PGC		125	12	24	#6-2/0	#6-1
HOM1224M100PC		100	12	24	#6-2/0	#6-1

NOTES:  
FINISH - GRAY BAKED ENAMEL ELECTRODEPOSITED OVER CLEANED PHOSPATIZED STEEL.  
UL LISTED - FILE E-6294  
NEUTRALS - INSULATED GROUNDABLE.  
LOAD CENTERS WITH A SUFFIX "G" INCLUDE A FACTORY-INCLUDED EQUIPMENT GROUNDING BAR.

HOMELINE LOAD CENTERS  
GENERAL PURPOSE NEMA TYPE 1 ENCLOSURE  
INDOOR



by Schneider Electric

DWG# PWFDS-SYRS-0070  
NO.