

DESCRIPTION

Perfect-90°, a paper laminated composite tape from Strait-Flex, is twice as fast and twice as strong as conventional paper or mesh tapes. Perfect-90° is designed as only way to finish inside 90° corners in one coat, cutting the finish time in half. The pre-finished laminated center section of Perfect-90° ensures a clean, sharp corner without the risk of damage from a taping knife, will not shrink, and will not fuzz up during sanding. The tape's outer edge features a diamond punch pattern for a superior bond, faster drying, with no rippling or blistering. Perfect-90° comes in 50', and 100' rolls.

ADVANTAGES

- Inside 90° corners and flat butt joints.
- Twice as fast and twice as strong as conventional paper or mesh tapes.
- Spans common gaps in drywall.
- No delayed shrinkage.
- No compound required over pre-finished surface. Finishes inside 90° corners in one coat, cutting the finish time in half.
- PUR-laminated center ensures perfect corners without paper fuzz-up.
- .025" thickness

WARRANTY

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

DIRECTIONS

- Fold PERFECT-90° in half at center crease with print size facing each other. For intersecting corners, cut ends at 45° angles. For inside corners, fold less than desired angle with print side facing out.
- With a 5" or 6" taping knife, apply a smooth, liberal coat of compound to corner.
- Press PERFECT-90° into the wet compound. Adjust if necessary to create a straight line.
- Wipe down tight with taping knife using a little additional pressure on the outer edges of PERFECT-90°. Let dry completely several hours or overnight.
- Apply final coat to perforated edge only. No compound is needed over finished area of tape. It's ready to paint. Let dry completely over several hours or overnight.
- Sand lightly with 120 grit sandpaper. PERFECT-90° will not fuzz-up like paper or mesh tapes.

STORAGE

Store in dry place protected from moisture.

SUBMITTAL APPROVALS

JOB NAME

CONTRACTOR

DATE

