

• **FOR YOUR SAFETY:** Registering your product will allow us to contact you in the unlikely event a safety notification is required under the Federal Consumer Safety Act.

Register online at www.dewalt.com/account-login.

Three-Year Limited Warranty

For warranty terms, go to






www.dewalt.com/support/warranty.





To request a written copy of the warranty terms, contact: Customer Service at DeWALT Industrial Tool Co., 701 East Joppa Road, Towson, MD 21286 or call **1-800-4-DEWALT (1-800-433-9258)**.



LATIN AMERICA: This warranty does not apply to products sold in Latin America. For products sold in Latin America, see country-specific warranty information contained in the packaging, call the local company or see website for warranty information.





FREE WARNING LABEL REPLACEMENT: If your warning labels become illegible or are missing, call **1-800-4-DEWALT (1-800-433-9258)** for a free replacement.



ACCESSORIES CHART





Approved wheels for use with DCG410	
Type 1 / T1 / 41 / T41	
Type 27 / T27	
Type 28 / T28	
Type 29 / T29	
Non-approved wheels for DCG410	
Type 11 / T11	 Do Not Use





5" (125 mm) Grinding Wheels	
Type 27 guard	
Backing flange	
Type 27 Depressed center wheel	
Locking flange	





5" (125 mm) Grinding Wheels	
Type 27 guard	
Type 27 hubbed wheel	


5" (125 mm) Sanding Flap Discs	
Type 27 guard	
Backing flange	
Non-hubbed sanding flap disc	
Locking flange	

5" (125 mm) Sanding Flap Discs	
Type 27 guard	
Hubbed sanding flap disc	

5" (125 mm) Cutting Wheels	
Type 1/41 guard**	
Backing flange	
Type 27/42 depressed center wheel, cutting only	
Locking flange	

5" (125 mm) Cutting Wheels	
Type 1/41 guard**	
Backing flange	
Type 1/41 abrasive cutting wheel	
Locking flange	

5" (125 mm) Cutting Wheels	
Type 1/41 guard**	
Backing flange	
Diamond cutting wheel	
Locking flange	

Wire Wheels	
Type 27 guard	
3-4" (76.2-100 mm) wire cup brush	