



7565 Drive-Seal™ 8 Blacktop Driveway Filler-Sealer



- Restores blacktop surfaces
- Heavy duty sand mix, added traction
- Advanced gel, faster & E-Z to apply
- Latex enhanced, durable long life

GARDNER® DRIVE-SEAL™ 8 delivers dependable lasting protection and a renewed finish for asphalt and blacktop pavements. DRIVE-SEAL™ 8 is formulated as a heavy duty resurfacer for worn driveways. The higher sand concentration fills small cracks for an even finish and provides a durable non-skid texture. Our trademark Gel formula speeds application, making your project faster and easier.

PREPARING THE SURFACE: New asphalt must cure at least six months and/or one full summer season before applying sealcoat. Clean driveway first to ensure adhesion. Scrub oil spots with degreaser and a brush. Repair cracks and fill holes with appropriate Gardner Blacktop repair products. Repairs must cure according to label instructions before sealing.

APPLICATION: Do not apply products if heavy dew, rain or colder temperatures are expected within 24 hours. Do not use on surfaces with greater than 20° slope. Surface and air must be at least 60°F and rising, but below 90°F. Completely mix to ensure no separation inside the pail. After preparing the surface and rinsing thoroughly, apply sealer to the damp pavement. Pour out 1/4 of the container across blacktop and spread product with brush or squeegee. Complete coat in one continuous wet application to prevent uneven color or sheen. Do not allow to puddle. Touch up areas as needed.

HOW MUCH TO APPLY: For driveways in average condition, apply 350 sq. ft. per pail. Coverage varies based the surface condition and texture.

DRY TIME: (based on 75°F, clear sunny skies, and humidity < 35%): For foot traffic, allow 3 - 4 hours after application. For vehicle traffic, allow 24 - 48 hours. Temperature, wind, sunlight, applied thickness and humidity affect dry time.

CLEAN-UP: Until dried, clean tools with warm water and soap. Clean up dried product with a citrus-based cleaner.

PRECAUTIONS: Do not thin, mix or blend this product with any other product. Use protective clothing and eyewear when using these products to avoid skin irritation. When transporting this product, ensure the lid is completely sealed and the pail upright and secure, allowing pail to tumble may cause it to leak. Do not transport inside the passenger compartment of any vehicle. Transport in the cargo area of vehicle and secure over protective cloths to prevent damage due to accidental spills. CLOSE CONTAINER WHEN NOT IN USE. Do not reuse empty containers. Use caution not to track onto linoleum floors, which are subject to household traffic stains, including asphalt driveway sealers. Consult the linoleum manufacturer for suggestions. Do not use in drinking water or food systems. KEEP FROM FREEZING.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 8 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7565-GA	5 gal.	12" x 12" x 14.75"	4.75 gal / 18 L	50 lbs.	1 ea.	025056756503

www.gardner-gibson.com
 Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
 Phone: (813) 248-2101