

Product data sheet

Characteristics

QO120CAFIC

Mini circuit breaker, QO, 20A, 1 pole,
120/240VAC, 10kA, combo arc fault, pigtail,
plug in mount, clam pack



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Combination ARC-fault
Ratings	Not rated
Electrical Connection	Pressure plate
Connections Terminals	Pigtail neutral
Type of Packing	Clam packaging

Complementary

Interrupt Rating	10 KA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Height	4.76 in (121 mm)
Width	0.75 in (19 mm)
Depth	2.91 in (74 mm)
Net Weight	0.60 lb(US) (0.272 kg)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	01318-QO 1 POLE BULK BRKRS.
Discount Schedule	CPQ
GTIN	785901698180
Nbr. of units in pkg.	1
Package weight(Lbs)	9.60 oz (272.155 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.20 in (3.048 cm)
Package 1 width	4.50 in (11.43 cm)
Package 1 Length	7.90 in (20.066 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	3

Package 2 Weight	30.40 oz (861.825 g)
Package 2 Height	3.90 in (9.906 cm)
Package 2 width	4.90 in (12.446 cm)
Package 2 Length	8.40 in (21.336 cm)
Unit Type of Package 3	PAL
Number of Units in Package 3	960
Package 3 Weight	608.00 lb(US) (275.784 kg)
Package 3 Height	40.00 in (101.6 cm)
Package 3 width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information