INSTRUCTION SHEET AFDWF5

## Braided PVC Dishwasher Connector with Elbow 3/8 in. Comp. x 3/8 in. MIP x 5 ft.

CAUTION: DO NOT INSTALL THIS PRODUCT UNTIL YOU READ AND UNDERSTAND ALL INSTRUCTIONS. FAILURE TO FOLLOW THESE INSTRUCTIONS MAY RESULT IN PERSONAL INJURY, PROPERTY DAMAGE OR PRODUCT FAILURE.

The 3/8 in. Compression x 3/8 in. MIP Elbow x 5 ft. Braided PVC Dishwasher Connector with Elbow by Apollo is a highly flexible water connector. Designed for longer life under harsh conditions, Apollo appliance connectors are corrosion resistant, highly flexible, extremely reliable water connectors.

## **FEATURES:**

- Corrosion resistant
- Bends freely without kinking or crimping
- Quick & easy installation

## INSTALLATION INSTRUCTIONS:

- 1. Turn off water supply.
- 2. Apply thread sealant to male iron pipe threads of 90° elbow and thread into dishwasher inlet. Hand tighten, then wrench tighten 1/4 turn more. DO NOT OVERTIGHTEN.
- 3. Thread one end of connector onto compression threads of 90° elbow.\* Hand tighten, then wrench tighten 1/4 turn more.
- 4. Thread other end of connector onto the water supply stop outlet.\* Hand tighten, then wrench tighten 1/4 turn more.
- 5. Turn on water supply and check for leaks. If any appear, carefully tighten nuts further.

Tools Needed for Installation: Wrench

- \*NOTE: Connector includes washers, DO NOT USE THREAD SEALANT. To prevent premature wear and connector damage:
- Keep connector away from moving parts.
- Do not allow connector to be pinched or trapped.
- Protect connector from rough or sharp edges (such as hole in side of cabinet) that could wear away hose surface over time which may lead to water damage.



