

# MODEL SERIES WFHD1300

## Universal Heavy Duty Whole House Filtration System

### Replacement Cartridges: **WFHDC300, WFHDC800 Series**



Tested and Certified by Water Quality Association (WQA) against NSF/ANSI Standard 42 for materials safety and structural integrity requirements only.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after this filter system. Maximum operating temperature 38° C/100° F. Operating pressure 30-100 psi/207-690 kPa.

## CAUTION

### READ BEFORE INSTALLING!

A pressure regulator **must be installed** before the filter, if water pressure will at any time exceed the

**MAXIMUM RATING OF  
100 PSI (690 kPa).**

It is recommended that the pressure regulator be set at 75 psi (517 kPa) or less. This will guard against the pressure exceeding the maximum rating at any time.

Protect against freezing. Failure to do so may result in cracking and leakage.

Do not install filter in applications where failure or leakage would cause damage.

NOTICE: We strongly recommend that the entire filter system be replaced every 5 years to guard against leaks caused by wear and tear.

828-449-1040 Service Requests/Product Information  
800-441-7515 Safety/Health Questions  
Protect Plus, LLC Hickory, NC 28601 USA  
[www.waterfiltration.DuPont.com](http://www.waterfiltration.DuPont.com)

**P**