

Approximate Weight: 0.6 - 7.0 g

Page 1 of 5 Coin/Button Lithium Manganese Dioxide Batteries March 2015

PRODUCT SAFETY DATA SHEET

PRODUCT NAME: Energizer Battery

Type No.:

Designed for Recharge: No

Volts: 3.0

TRADE NAMES: Coin/Button Lithium Manganese Dioxide Batteries

CHEMICAL SYSTEM: Lithium Manganese Dioxide

Energizer has prepared copyrighted Product Safety Datasheets to provide information on the different Eveready/Energizer battery systems. Batteries are articles as defined under the GHS and exempt from GHS classification criteria (Section 1.3.2.1.1 of the GHS). The information and recommendations set forth herein are made in good faith, for information only, and are believed to be accurate as of the date of preparation. However, ENERGIZER BATTERY MANUFACTURING, INC. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM REFERENCE ON IT.

SECTION 1- MANUFACTURER INFORMATION

Manufactured for Energizer Battery Manufacturing, Inc. 25225 Detroit Rd. Westlake, OH 44145

Telephone Number for Information: 800-383-7323 (USA / CANADA)

Date Prepared: March 2015

SECTION 2 – HAZARDS IDENTIFICATION

GHS classification: N/A

Signal Word: N/A

Hazard Classification: N/A

Under normal conditions of use, the battery is hermetically sealed.

Ingestion: Swallowing may lead to serious injury or death in as little as 2 hours due to chemical burns and potential perforation of the esophagus. Immediately see doctor; have doctor phone (202) 625-3333. Do not induce vomiting or give food or drink.
 Inhalation: Contents of an open battery can cause respiratory irritation.
 Skin Contact: Contents of an open battery can cause skin irritation.
 Eye Contact: Contents of an open battery can cause severe irritation.

SECTION 3 - INGREDIENTS

IMPORTANT NOTE: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.	
Carbon Black (CAS# 1333-86-4)	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA	0-1	
1,2-Dimethoxyethane (CAS# 110-71-4)	None established	None established	0-6	
1,3-Dioxolane (CAS# 646-06-0)	None established	None established	0-8	
Graphite (CAS# 7782-42-5)	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	2 mg/m ³ TWA (respirable fraction)	0-3	
Lithium or Lithium Alloy (CAS# 7439-93-2)	None established	None established	1-6	



Page 2 of 5 Coin/Button Lithium Manganese Dioxide Batteries March 2015

Lithium Perchlorate (CAS# 7791-03-9)	None established	None established	0-3
Lithium Trifluoromethanesulfonate (CAS# 33454-82-9)	None established	None established	0-3
Lithium Trifluoromethanesulfonimide (CAS# 90076-65-6)	None established	None established	0-3
Manganese Dioxide (CAS# 1313-13-9)	5 mg/m ³ Ceiling (as Mn)	0.2 mg/m ³ TWA (as Mn)	12-42
Propylene Carbonate (CAS# 108-32-7)	None established	None established	0-8
Non-Hazardous Components:			
Steel (iron CAS# 65997-19-5)	None established	None established	20
Plastic and Other	None established	None established	Balance

SECTION 4 – FIRST AID MEASURES

Ingestion: Swallowing may lead to serious injury or death in as little as 2 hours due to chemical burns and potential perforation of the esophagus. **Immediately see doctor; have doctor phone (202) 625-3333.** Do not induce vomiting or give food or drink.

Inhalation: Provide fresh air and seek medical attention.

Skin Contact: Remove contaminated clothing and wash skin with soap and water.

Eye Contact: Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

Note: Carbon black is listed as a possible carcinogen by International Agency for Research on Cancer (IARC).

SECTION 5- FIRE FIGHTING MEASURES

In case of fire where lithium batteries are present, flood area with water or smother with a Class D fire extinguishant appropriate for lithium metal, such as Lith-X. Water may not extinguish burning batteries but will cool the adjacent batteries and control the spread of fire. Burning batteries will burn themselves out. Virtually all fires involving lithium batteries can be controlled by flooding with water. However, the contents of the battery will react with water and form hydrogen gas. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended. A smothering agent will extinguish burning lithium batteries.

Emergency Responders should wear self-contained breathing apparatus. Burning lithium manganese dioxide batteries produce toxic and corrosive lithium hydroxide fumes.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

To cleanup leaking batteries:

Ventilation Requirements: Room ventilation may be required in areas where there are open or leaking batteries.
 Respiratory Protection: Avoid exposure to electrolyte fumes from open or leaking batteries.
 Eye Protection: Wear safety glasses with side shields if handling an open or leaking battery.
 Gloves: Use neoprene or natural rubber gloves if handling an open or leaking battery.
 Battery materials should be collected in a leak-proof container.

SECTION 7 - HANDLING AND STORAGE

Storage: Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life. In locations that handle large quantities of lithium batteries, such as warehouses, lithium batteries should be isolated from unnecessary combustibles.

Mechanical Containment: If potting or sealing the battery in an airtight or watertight container is required, consult your Energizer Battery Manufacturing, Inc. representative for precautionary suggestions. Do not obstruct safety release vents on batteries. Encapsulation of batteries will not allow cell venting and can cause high pressure rupture.



Page 3 of 5 Coin/Button Lithium Manganese Dioxide Batteries March 2015

Handling: Accidental short circuit for a few seconds will not seriously affect the battery. Prolonged short circuit will cause the battery to lose energy, generate significant heat and can cause the safety release vent to open. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries into devices. Damaging a lithium battery may result in an internal short circuit.

The contents of an open battery, including a vented battery, when exposed to water, may result in a fire and/or explosion. Crushed or damaged batteries may result in a fire.

If soldering or welding to the battery is required, consult your Energizer representative for proper precautions to prevent seal damage or short circuit.

Charging: This battery is manufactured in a charged state. It is not designed for recharging. Recharging can cause battery leakage or, in some cases, high pressure rupture. Inadvertent charging can occur if a battery is installed backwards.

Labeling: If the Energizer label or package warnings are not visible, it is important to provide a package and/or device label stating:

WARNING: Battery can explode or leak and cause burns if installed backwards, disassembled, charged, or exposed to water, fire or high temperature.

Where accidental ingestion of small batteries is possible, the label should include:

WARNING

(1) KEEP OUT OF REACH OF CHILDREN. Swallowing may lead to serious injury or death in as little as 2 hours due to chemical burns and potential perforation of the esophagus. **Immediately see doctor; have doctor phone (202) 625-3333.** Keep in original package until ready to use. Dispose of used batteries immediately.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: Not necessary under normal conditions. Respiratory Protection: Not necessary under normal conditions. Eye Protection: Not necessary under normal conditions. Gloves: Not necessary under normal conditions.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid object
Upper Explosive Limits:	Not applicable for an Article
Lower Explosive Limits	Not applicable for an Article
Odor	No odor
Vapor Pressure (mm Hg @ 25°C)	Not applicable for an Article
Odor Threshold	No odor
Vapor Density (Air = 1)	Not applicable for an Article
pH	Not applicable for an Article



Page 4 of 5 Coin/Button Lithium Manganese Dioxide Batteries March 2015

Density (g/cm ³)	2.0-3.0
Melting point/Freezing Point	Not applicable for an Article
Solubility in Water (% by weight)	Not applicable for an Article
Boiling Point @ 760 mm Hg (°C)	Not applicable for an Article
Flash Point	Not applicable for an Article
Evaporation Rate (Butyl Acetate = 1)	Not applicable for an Article
Flammability	Not applicable for an Article
Partition Coefficient	Not applicable for an Article
Auto-ignition Temperature	Not applicable for an Article
Decomposition Temperature	Not applicable for an Article
Viscosity	Not applicable for an Article

SECTION 10 - STABILITY AND REACTIVITY

Lithium manganese dioxide batteries contain no sulfides or cyanides and they do not meet any other reactivity criteria including "reacts violently with water" and therefore do not meet any of the criteria established in 40 CFR 261.2 for reactivity.

SECTION 11 – TOXICOLOGICAL INFORMATION

Under normal conditions of use, lithium manganese dioxide batteries are non-toxic.

SECTION 12 – ECOLOGICAL INFORMATION

Issues such as ecotoxicity, persistence and bioaccumulation are not applicable for articles.

SECTION 13 – DISPOSAL CONSIDERATIONS

Lithium iron disulfide batteries are not hazardous waste per the United States Resource Conservation and Recovery Act (RCRA) - 40 CFR Part 261 Subpart C. Dispose of in accordance with all applicable federal, state and local regulations.

SECTION 14 – TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Energizer lithium batteries are compliant with these regulatory concerns.

Energizer lithium coin batteries are exempt from the classification as dangerous goods as they meet the requirements of the special provisions listed below. (Essentially, they are properly packaged and labeled, contain less than 1 gram of lithium and pass the tests defined in UN model regulation section 38.3).

Regulatory Body	Special Provisions	
ADR	188, 230, 310, 636, 656	
IMDG	188, 230, 310, 957	
UN	UN 3090, UN 3091	
US DOT	29, A54, A100, A101	
IATA, ICAO	Packaging Instructions 968 - 970	



Page 5 of 5 Coin/Button Lithium Manganese Dioxide Batteries March 2015

Energizer is registered with CHEMTREC. In the event of an incident during transport call 1-800-424-9300 (North America) or 1-703-527-3887 (International).

A global lithium label chart is provided below to summarize the current global labeling requirements.

Shipping Mode	Li content	Net quantity wt. of batteries per package	Battery Type	₩,		CARGO AIRCRAFT ONLY TREBECK IN ARGENCIAL COMPANY
	0.3g to <u><</u> 1g/cell 0.3g to <u><</u> 2g/ battery	<u><</u> 2.5 kg	L91, L92, L522	YES	YES	YES
AIR	<0.3g/cell	<u><</u> 2.5kg	All Li Coin and 2L76	NO	YES	YES
	<0.3g/cell	>2.5kg	All Li Coin and 2L76	YES	YES	YES
Land/ Sea only	All	All	All	NO	YES	YES

Label Summary Chart

SECTION 15 - REGULATORY INFORMATION

Outside of the transportation requirements noted in Section 14, lithium manganese dioxide batteries marketed by Energizer Battery Manufacturing, Inc. are not regulated.

SARA/TITLE III - As an article, this battery and its contents are not subject to the requirements of the Emergency Planning and Community Right-To-Know Act.

SECTION 16 - OTHER INFORMATION

None.



No.: CANEC1216097701 Date: 30 Nov 2012

Page 1 of 1

GUANG ZHOU NPP POWER CO., LTD.

NO.3 LONGHUI INDUSTRIAL ROAD, HUASHAN TOWN, HUADU DISTRICT, GUANGZHOU, CHINA

SGS Job No. Sample Name End Uses Composition/Ingredient of sampl (as per client submission) Job Receiving Date SDS Preparation Period	e	CP12-056341-GZ Valve Regulated Lead Acid Battery Telecom system, UPS, Solar system, Standby power, etc See Section 3 Composition/information on ingredients on the SDS report 26 Nov 2012 26 Nov 2012 - 30 Nov 2012
Service Requested	:	Safety Data Sheet (SDS) for the sample with submitted composition.
Summary	:	As per request, the contents and formats of the SDS are prepared in accordance with European Commission Directives 67/548/EEC, 1999/45/EC, Regulation (EC) No 1907/2006, Regulation (EC) No 1272/2008 and Regulation (EU) No 453/2010, and is provided per attached.

Signed for and on behalf of SGS-CSTC Ltd.

Allen Xie

Approved Signatory

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. htm and, for electronic format documents.subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemolection is used to the first of the company's findings at the time of its intervence rom and conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of from explained the intervence rom and conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of from explained at the units of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from explained at the units of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from explained at the units of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from explained at the units of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from explained at the units of Client's instructions of the company. Any upschoor and atteration, or gery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise states the even is shown in this test report refer only to the sample(s) tested .



198 Kezhu Road, Scientech Park Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075113 www.cn.sgs.com 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075113 e sgs.china@sgs.com

Member of the SGS Group (SGS SA)

Printing date 30.11.2012

Revision: 30.11.2012

	of the substance/mixture and of the company/undertaking
· Product identifier	
Trade name: Valv	e Regulated Lead Acid Battery
Manufacturer/Sup Name: JULIE CA Full address:	NDUSTRIAL ROAD, HUASHAN TOWN, HUADU DISTRICT, GUANGZHOU, CHINA 86-20-87561800
• Emergency teleph • Email: sales@npp	ion obtainable from: GUANG ZHOU NPP POWER CO., LTD. one number: +86-13450463300 power.com.cn r: CP12-056341-GZ; CANEC1216097701
2 Hazards identij	fication
	he substance or mixture
· Classification acc	ording to Regulation (EC) No 1272/2008
GHS08	health hazard
Repr. IA	H360Df May damage the unborn child. Suspected of damaging fertility.
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.
GHS05	corrosion
Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
\mathbf{A}	
GHS09	environment
V	
A arratio A arrea I	
Aquatic Acute 1 Aquatic Chronic 1	H400 Very toxic to aquatic life.H410 Very toxic to aquatic life with long lasting effects.
Aquatic Acute 1 Aquatic Chronic 1 GHS07	
Aquatic Chronic 1	
Aquatic Chronic 1	H410 Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 1 Aquatic Chronic 1 GHS07 Acute Tox. 4 Acute Tox. 4 Classification acce	H410 Very toxic to aquatic life with long lasting effects.H302 Harmful if swallowed.
Aquatic Chronic 1 Aquatic Chronic 1 GHS07 Acute Tox. 4 Acute Tox. 4 Classification acco T; Toxic	 H410 Very toxic to aquatic life with long lasting effects. H302 Harmful if swallowed. H332 Harmful if inhaled. bording to Directive 67/548/EEC or Directive 1999/45/EC
Aquatic Chronic 1 Aquatic Chronic 1 GHS07 Acute Tox. 4 Acute Tox. 4 Classification acco T; Toxic R61:	 H410 Very toxic to aquatic life with long lasting effects. H302 Harmful if swallowed. H332 Harmful if inhaled. bording to Directive 67/548/EEC or Directive 1999/45/EC May cause harm to the unborn child.
Aquatic Chronic 1 Aquatic Chronic 1 GHS07 Acute Tox. 4 Acute Tox. 4 Classification acco T; Toxic	 H410 Very toxic to aquatic life with long lasting effects. H302 Harmful if swallowed. H332 Harmful if inhaled. bording to Directive 67/548/EEC or Directive 1999/45/EC May cause harm to the unborn child.

- EU

Safety Data Sheet 1907/2006/EC, 1272/2008/EC

1907/2006/EC, 1272/2008/EC Printing date 30.11.2012 Revision: 30.11.2012 Trade name: Valve Regulated Lead Acid Battery (Contd. of page 1) Xn; Harmful R62-20/22-40-48/20/22: Possible risk of impaired fertility. Harmful by inhalation and if swallowed. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. N; Dangerous for the environment R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Danger of cumulative effects. R33: Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of Directive 67/548/EEC, 1999/45/EC and Regulation (EC) No. 1272/2008. Classification system: The classification is according to the latest edition of the Directive 67/548/EEC, 1999/45/EC and Regulation (EC) No. 1272/2008, and extended by company and literature data. · Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS05 GHS07 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: lead dioxide sulphuric acid lead poly (acrylonitrile-co-butadiene-co-styrene) Hazard statements H302 Harmful if swallowed. H332 Harmful if inhaled. H314 Causes severe skin burns and eye damage. H360Df May damage the unborn child. Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects. H410 Contains lead. Should not be used on surfaces liable to be chewed or sucked by children. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. (Contd. on page 3)

Printing date 30.11.2012

Revision: 30.11.2012

Trade name: Valve Regulated Lead Acid Battery

· vPvB: Not applicable.

(Contd. of page 2)

	m: Mixtures listed below with nonhazardous additions. risk phrases refer to section 16.	
Dangerous components:		
CAS: 1309-60-0 EINECS: 215-174-5 EU number: 082-001-00-	lead dioxide Image: Trepr. Cat. 1, 3 R61; Xn R62-20/22; N R50/53 6 R33 Image: Repr. 1A, H360Df; STOT RE 2, H373; Image: Repr. 1A, H360Df;	31,29
CAS: 7439-92-1 EINECS: 231-100-4	lead T R61; Xn R62-40-48/20/22; R N R50/53 R33 Repr. 1A, H360Df; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H332	30,0
CAS: 7664-93-9 EINECS: 231-639-5 EU number: 016-020-00-	sulphuric acid C R35 Skin Corr. 1A, H314	24,6
CAS: 9003-56-9	poly (acrylonitrile-co-butadiene-co-styrene) Xn R22; Xi R36/37/38 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10.24
CAS: 7440-50-8 EINECS: 231-159-6	copper R53 � Aquatic Chronic 1, H410	0,29
Non-dangerous compone	ents:	
AGM clapbo	pard	2,6
Expoxide-re	sin glue	0,6
Red & black	marking glue	0,4
25038-36-2 Poly(ethylene-co-propylene-co-5-methylene-2-norbornene)		0,11

Classification of AGM clapboard, Expoxide-resin glue, Red & black marking glue is not covered by company database and is declared by client as nonhazardous.

4 First aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:
- Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· Information for doctor

• Most important symptoms and effects, both acute and delayed: No further relevant information available.

(Contd. on page 4)

Printing date 30.11.2012

Revision: 30.11.2012

(Contd. of page 3)

Trade name: Valve Regulated Lead Acid Battery

• Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2 powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.*
- · Environmental precautions:
- Do not allow product to reach sewage system or any water sourse.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- \cdot Methods and material for containment and cleaning up:
- Use neutralizing agent. Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- · Reference to other sections:
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

Handling

- Precautions for safe handling:
- Thorough dedusting.
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- · Information about fire and explosion protection: Keep respiratory protective device available.
- · Storage:
- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1309-60-0 lead dioxide

PEL (USA) 0,05 mg/m³

as Pb; See 29 CFR 1910,1025

(Contd. on page 5)

Printing date 30.11.2012

-

Revision: 30.11.2012

Trade name: Valve Regulated Lead Acid Battery

DEL (TICA)	(Contd. of page
REL (USA)	0,05* mg/m ³ as Pb; *8-hr TWA, Blood Pb<0,06mg/100g whole blood
TLV (USA)	0,05 mg/m ³ as Pb; BEI
MAK (Germany)	
7439-92-1 lead	
PEL (USA)	0,05* mg/m ³
	*see 29 CFR 1910,1025
REL (USA)	$0,05 mg/m^3$
	excluding lead arsenate; See Pocket Guide App. C
TLV (USA)	$0.05* mg/m^3$
MARIC	*and inorganic compounds, as Pb; BEI
MAK (Germany)	
7664-93-9 sulphi	
IOELV (EU)	0,05 mg/m ³
PEL (USA)	1 mg/m ³
REL (USA)	1 mg/m ³
TLV (USA)	0,2* mg/m ³
ACHIV(Carrows)	*as thoracic fraction
AGW (Germany)	1(I); DFG, EU, Y
9003-56-9 poly (d	acrylonitrile-co-butadiene-co-styrene)
TLV (USA)	10* mg/m ³
	*nuisance particulates(total)
7440-50-8 copper	
PEL (USA)	1*0,1** mg/m ³
	as Cu *dusts and mists **fume
REL (USA)	1*0,1**mg/m ³
TT SZ (TTCA)	as Cu *dusts and mists **fume
TLV (USA)	1*0,2**mg/m ³ *dusts and mists; **fume; as Cu
MAK (Germany)	
DNELs: Not avai	
PNECs: Not avai	
	nation: The lists valid during the making were used as basis.
Exposure control	
	position shown in Section 3, the following measures are suggested for occupational safe
measure	
Personal protecti	
	e and hygienic measures: Toodstuffs, beverages and feed.
	we all soiled and contaminated clothing
	re breaks and at the end of work.
	lothing separately.
Avoid contact with	h the eyes and skin.
Respiratory prote	
In case of brief ex	posure or low pollution use respiratory filter device. In case of intensive or longer exposur I respiratory protective device.

Printing date 30.11.2012

Revision: 30.11.2012

(Contd. of page 5)

EU

Trade name: Valve Regulated Lead Acid Battery

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and General information	cnemicai properiies
Appearance	
Form:	Cuboid battery
Colour:	Black
Odour:	Odourless
Odour threshold:	Not available
pH-value:	Not available
Change in condition	
Melting point/Melting range:	Not available
Boiling point/Boiling range:	110 °C
Freezing point:	Not available
Flash point:	259 °C
Flammability (solid, gaseous):	Not available
Auto-Ignition temperature:	580 °C
Decomposition temperature:	Not available
Self-igniting:	Product is not selfigniting.
Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
Explosion limits	
Lower:	Not available
Upper:	Not available
Oxidizing properties:	Not available
Vapour pressure:	Not available
Density:	Not available

Printing date 30.11.2012

Revision: 30.11.2012

Trade name: Valve Regulated Lead Acid Battery

		(Contd. of page 6
Relative density:	Not available	
Vapour density:	Not available	
Evaporation rate:	Not available	
Solubility in / Miscibility with	2	
water:	Not available	
Partition coefficient (n-octan	ol/water): Not available.	
Viscosity		
Dynamic:	Not available.	
Kinematic:	Not available	
Other information:	Melting point / range: Lead 327.4 °C	
	Solubility in water: 100% (Electrolyte)	

10 Stability and reactivity

· Reactivity: Data not avaiable

- · Chemical stability: Data not avaiable
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification: Not applicable
- · Primary irritant effect
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- Toxicokinetics, metabolism and distribution: No further relevant information available
- Acute effects (acute toxicity, irritation and corrosivity): No further relevant information available
- · Repeated dose toxicity: No further relevant information available.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): No further relevant information available.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behaviour in environmental systems: No further relevant information available
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- · Remark: Very toxic for fish

(Contd. on page 8)

Printing date 30.11.2012

Revision: 30.11.2012

Trade name: Valve Regulated Lead Acid Battery

(Contd. of page 7)

- \cdot Additional ecological information
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Must not reach sewage water or drainage ditch undiluted or unneutralized. Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Very toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
 Other adverse effects: No further relevant information available.
- 13 Disposal considerations
 - · Waste treatment methods
 - · Recommendation:
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - · Uncleaned packaging
 - · Recommendation: Disposal must be made according to official regulations.

· UN-Number	
ADR, IMDG, IATA	UN2800
· UN proper shipping name	
ADR	2800 BATTERIES, WET, NON-SPILLABLE ENVIRONMENTALLY HAZARDOUS
·IMDG	BATTERIES, WET, NON-SPILLABLE, MARINE POLLUTANT
·IATA	BATTERIES, WET, NON-SPILLABLE
· Transport hazard class(es)	
Class	8 Corrosive substances.
Label	8 Corrosive substances. 8
Label Packing group	8 Not applicable
Label Packing group ADR, IMDG, IATA	8 Not applicable Product contains environmentally hazardous substances: lea
Label Packing group ADR, IMDG, IATA Environmental hazards	8 Not applicable Product contains environmentally hazardous substances: lea dioxide, lead
Label Packing group ADR, IMDG, IATA Environmental hazards Marine pollutant:	8 Not applicable Product contains environmentally hazardous substances: lea dioxide, lead Yes
Label Packing group ADR, IMDG, IATA Environmental hazards Marine pollutant: Special precautions for user:	8 Not applicable Product contains environmentally hazardous substances: lea dioxide, lead Yes Warning: Corrosive substances.

Printing date 30.11.2012

Revision: 30.11.2012

(Contd. of page 8)

2

2

4

EU-

Trade name: Valve Regulated Lead Acid Battery

· UN "Model Regulation":

UN2800, BATTERIES, WET, NON-SPILLABLE, ENVIRONMENTALLY HAZARDOUS, 8

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· MAK(German Maximum Workplace Concentration)

1309-60-0 lead dioxide

7439-92-1 lead

7664-93-9 sulphuric acid

· National regulations

• Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

• Other regulations, limitations and prohibitive regulations

- SVHC Candidate List of REACH Regulation Annex XIV Authorisation (18/6/2012) None of the igredients is listed
- · REACH Regulation Annex XVII Restriction (19/9/2012) None of the igredients is listed
- REACH Regulation Annex XIV Authorisation List (14/2/2012) None of the igredients is listed
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H360Df May damage the unborn child. Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R20/22 Harmful by inhalation and if swallowed.
- R22 Harmful if swallowed.
- R33 Danger of cumulative effects.
- R35 Causes severe burns.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R40 Limited evidence of a carcinogenic effect.
- R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R53 May cause long-term adverse effects in the aquatic environment.
- *R61 May cause harm to the unborn child.*
- *R62 Possible risk of impaired fertility.*

DISCLAIMER OF LIABILITY

The information in this MSDS/SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal (Contd. on page 10)

Printing date 30.11.2012

Revision: 30.11.2012

Trade name: Valve Regulated Lead Acid Battery

(Contd. of page 9)

of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may not be applicable.
Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
- 赤杨梅梅格洛安特尔希格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格格
End of document

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 25-Jan-2017

Revision Number 1

Canada / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier		
Product Name	Sealed Valve Regulated Lead Acid Battery	
Other means of identification		
Product Code(s)	1362552	
Recommended use of the chemical	and restrictions on use	
Recommended Use	Lead Acid (Non-Spillable) Battery	
Restrictions on use	No information available	
Details of the supplier of the safety data sheet		
Initial supplier identifier	Ghost Controls LLC.	
Address	1572 Capital Circle NW Tallahassee Florida 32303 United States	
Telephone	Phone:8506010922 Fax:8506010922	
E-mail	info@ghostcontrols.com	
Emergency telephone number		
Company Emergency Phone Number	8506010922	

2. HAZARDS IDENTIFICATION

Classification

This is a battery. In case of rupture:.

Acute toxicity - Oral

Category 4



Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 2
Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1A
Effects on or via lactation	Yes
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Danger

Hazard statements

This is a battery. In case of rupture:.

Harmful if swallowed Fatal if inhaled Causes severe skin burns and eye damage May cause cancer May damage fertility or the unborn child May cause harm to breast-fed children Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapors/spray Avoid contact during pregnancy and while nursing Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Wear respiratory protection

Precautionary Statements - Response

Specific treatment is urgent (see supplemental first aid instructions on this label) Immediately call a POISON CENTER or doctor

Eyes

Immediately call a POISON CENTER or doctor IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower] Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing



Immediately call a POISON CENTER or doctor

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell Rinse mouth IF SWALLOWED: Rinse mouth. DO NOT induce vomiting Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life Very toxic to aquatic life with long lasting effects

Unknown acute toxicity

111.49 % of the mixture consists of ingredient(s) of unknown toxicity 25.6 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

111.49 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

50.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

50.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

25.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lead peroxide	1309-60-0	31.29	-	-
Lead	7439-92-1	30	-	-
Sulfuric acid	7664-93-9	24.6	-	-
Copper	7440-50-8	0.2	-	-

4. FIRST AID MEASURES

First aid measures

Show this safety data sheet to the doctor in attendance. Immediate medical attention is General advice required. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of sealed battery. Inhalation If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.



Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.
Most important symptoms and effe	cts, both acute and delayed
Symptoms	Coughing and/ or wheezing. Difficulty in breathing. Burning sensation.
Indication of any immediate medica	I attention and special treatment needed
Note to physicians	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES		
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.	
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.	
Specific hazards arising from the chemical	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.	
Hazardous Combustion Products	Carbon oxides.	
Explosion Data Sensitivity to Mechanical Impac Sensitivity to Static Discharge	t None. None.	
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautionsAttention! Corrosive material. Ensure adequate ventilation. Avoid contact with skin, eyes or
clothing. Avoid generation of dust. Do not breathe dust. Use personal protective equipment
as required. Evacuate personnel to safe areas. Keep people away from and upwind of

	spill/leak.	
Other Information	Refer to protective measures listed in Sections 7 and 8.	
Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Pick up and transfer to properly labeled containers.	

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not breathe dust. Avoid generation of dust. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Lead peroxide 1309-60-0	TWA: 0.05 mg/m ³			
Lead 7439-92-1	TWA: 0.05 mg/m ³			
Sulfuric acid 7664-93-9	TWA: 1 mg/m ³ STEL: 3 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³	TWA: 1 mg/m ³ STEL: 3 mg/m ³
Copper 7440-50-8	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³

Other Exposure Guidelines

Engineering controls

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Face protection shield.



Hand protection	Wear suitable gloves. Impervious gloves.	
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.	
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.	
General hygiene considerations	Avoid contact with skin, eyes or clothing. Do not breathe dust. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties		
Physical state	Solid	
Appearance	Solid	
Odor	Neutral	
Color	No information available	
Odor Threshold	Not applicable	
Property	Values	Remarks Method
pH	2	Kemarka Method
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
	No data available	
Vapor density		None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	NI
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/wate		
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Other Information		
Explosive properties	No information available.	
Oxidizing properties	No information available.	
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Excessive heat. Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.
Hazardous Decomposition Products Carbon oxides.	

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information In case of rupture:		
Inhalation	Specific test data for the substance or mixture is not available. Fatal if inhaled. (based on components). Corrosive by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.		
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.		
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.		
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.		
Information on toxicological effects	<u>5</u>		
Symptoms	Coughing and/ or wheezing. Difficulty in breathing. Redness. Burning. May cause blindness.		
Numerical measures of toxicity			
Acute Toxicity			
The following values are calculated based on chapter 3.1 of the GHS document .			

The following values are calculated based on chapter 3.1 of the GHS document			
ATEmix (oral)	554.90 mg/kg		
ATEmix (inhalation-gas)	3,656.40 ppm		
ATEmix (inhalation-dust/mist)	0.06 mg/L		
ATEmix (inhalation-vapor)	8.94 mg/L		
Unknown acute toxicity	111.49 % of the mixture consists of ingredient(s) of unknown toxicity		
· · · · · ·	5		



- 25.6 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 111.49 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 50.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 50.2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

25.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Sulfuric acid	= 2140 mg/kg (Rat)	-	85 - 103 mg/m³ (Rat)1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes burns.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lead peroxide 1309-60-0	A3	Group 2A	Reasonably Anticipated	Х
Lead 7439-92-1	A3	Group 2A	Reasonably Anticipated	Х
Sulfuric acid 7664-93-9	A2	Group 1	Known	Х

Legend

ACGIH (American Conferer A2 - Suspected Human Carc A3 - Animal Carcinogen IARC (International Agency Group 1 - Carcinogenic to Hu Group 2A - Probably Carcino NTP (National Toxicology F Known - Known Carcinogen	r for Research on Cancer) Imans genic to Humans
Reasonably Anticipated - Reasonably	asonably Anticipated to be a Human Carcinogen y and Health Administration of the US Department of Labor)
Reproductive toxicity	Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. May damage fertility or the unborn child. May cause harm to breastfed babies.
STOT - single exposure	No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects. .

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)	
Lead	-	96h LC50: = 1.17 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.44 mg/L (Cyprinus carpio) 96h LC50: = 1.32 mg/L (Oncorhynchus mykiss)	-	48h EC50: = 600 μg/L	
Sulfuric acid	-	96h LC50: > 500 mg/L (Brachydanio rerio)	-	24h EC50: = 29 mg/L	
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: < 0.3 mg/L (Pimephales promelas)	-	48h EC50: = 0.03 mg/L	
Persistence and Degrada	Persistence and Degradability No information available.				
Bioaccumulation There is no data for this product.					
Mobility	lobility No information available.				
Other adverse effects	Idverse effects No information available.				
13. DISPOSAL CONSIDERATIONS					
Waste treatment methods					
Waste from residues/un products	Ste from residues/unused Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.			e in accordance with	
Contaminated packaging	aminated packaging Do not reuse empty containers.				

14. TRANSPORT INFORMATION

TDG	
UN-No.	UN2800
Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE
Hazard Class	8
Description	UN2800, BATTERIES, WET, NON-SPILLABLE, 8



DOT	
UN-No.	UN2800
Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE
Hazard Class	8 UN2800, BATTERIES, WET, NON-SPILLABLE, 8
Description Emergency Response Guide	154
Number	
MEX UN-No.	UN2800
Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE
Hazard Class	8
Description	UN2800, BATTERIES, WET, NON-SPILLABLE, 8
ICAO	
UN-No.	UN2800
Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE
Hazard Class	
Description	UN2800, BATTERIES, WET, NON-SPILLABLE, 8
IATA	
UN-No.	
Proper Shipping Name Hazard Class	BATTERIES, WET, NON-SPILLABLE 8
ERG Code	8L
Description	UN2800, BATTERIES, WET, NON-SPILLABLE, 8
IMDG/IMO	
UN-No.	UN2800
Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE
Hazard Class	8
EmS-No.	F-A, S-B
Description	UN2800, BATTERIES, WET, NON-SPILLABLE (LEAD PEROXIDE, LEAD), 8, MARINE POLLUTANT
<u>RID</u> UN-No.	
Proper Shipping Name	UN2800 BATTERIES, WET, NON-SPILLABLE
Hazard Class	8
Classification code	C11
Description	UN2800, BATTERIES, WET, NON-SPILLABLE, 8, ENVIRONMENTALLY HAZARDOUS
ADR/RID-Labels	8
ADR	
UN-No.	UN2800
Proper Shipping Name Hazard Class	BATTERIES, WET, NON-SPILLABLE
Classification code	8 C11
Tunnel restriction code	(E)
Description	ÚŃ2800, BATTERIES, WET, NON-SPILLABLE, 8, (E), ENVIRONMENTALLY
	HAZARDOUS
ADN	
UN-No.	UN2800
Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE
Hazard Class Classification code	8 C11
Special Provisions	238, 295, 598
Description	UN2800, BATTERIES, WET, NON-SPILLABLE, 8, ENVIRONMENTALLY HAZARDOUS
Hazard Labels	8



1 L

Limited Quantity

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

16. OTHER INFORMATION

<u>NFPA</u>	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 0	Flammability 0	Physical hazards 0	Personal Protection X
Prepared By	23 British Latham,	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501		
Revision Date	25-Jan-2	017		
Revision Note	No inforn	nation available		

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

