

S-761 Seam Adhesive for Sheet Flooring "Product Information"

Caution/Warning

Caution / Warning



Caution Eye and Skin Irritant

MSDS

MSDS

[S-761 Seam Adhesive MSDS](#)

Product Attributes

Product Attributes

Description	
Type	Water-based/resin
Color	White
Taggants	Yes – Saturn Yellow
Coverage	1/8" bead, approximately 144 lin. ft./bottle (43 lin. m.)
Units	8 oz (236 mL) bottle; 12/ctn
Open Time	None recommended
Working Time	15 minutes
Dry Time	User can walk on seam after 2 hours; 4-6 hours is full dry time
Shelf Life	1 year, unopened
Freeze/Thaw Stable	No, keep from freezing
VOC Content	136 g/L; calculated and reported, SCAQMD 1168
Clean Up	Wet– clean, white cloth with neutral detergent and water Dry– clean, white cloth and mineral spirits
Advantages	Nonflammable, ammonia-free and low odor Contains low or no organic solvents

MANUFACTURING LOCATIONS: Bourbonnais, IL

Order & Warehouse Information

Order & Warehouse
Information

Order and Warehouse Information	
Language	English / Spanish
Size	8 ounces
Carton Item No.	00761123

Item/Carton UPC	042369319720 / 042369219723
Carton Dimensions	15" x 15" x 18"
Carton Weight	8.27 lbs
Items per Carton	12
Cartons per Pallet	145

Substrates

Substrates For seaming of vinyl sheet and linoleum sheet.

Installation Procedures

Installation Procedures For use with the following Installation Systems:

Highly Recommended:

- [Residential Linoleum](#)

Optional:

- [Commercial Linoleum](#)
- [Commercial Vinyl-Backed](#)
- [Commercial Heterogeneous and Inlaid](#)
- [Full-Spread Light Commercial Glass Back](#)
- [Fiberglass-Reinforced Sheet Flooring](#)
- [ToughGuard II](#)

[S-761 Seam Adhesive Procedure for Fiberglass Reinforced and Toughguard II - Residential](#)

[S-761 Seam Adhesive Procedure - Commercial](#)

[S-761 Seam Adhesive Video - Commercial](#)

[S-761 Video](#)

LEED / Environmental

LEED / Environmental **LEED Credits:** EQ 4.1
[Sustainable Design Information Sheet](#)
[LEED Credit Information - Installation Products](#)

Warranty

Warranty When Armstrong S-761 Seam Adhesive is used with a recommended Armstrong floor application, the Armstrong Guaranteed Installation System warranty applies.

Product Image

Product Image

