



SAFETY DATA SHEET

1. Identification

Product identifier BEHR DYNASTY® Exterior Flat Paint – Deep Base

Other means of identification

Product code 4653

Recommended use Architectural Coating

Recommended restrictions Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process LLC
1801 E. St. Andrew Place
Santa Ana, CA 92705

Telephone 714-545-7101

Emergency telephone +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Not classified.

Hazards for the product as sold

Health hazards Sensitization, skin Category 1A
Carcinogenicity Category 1B

Hazards for the product as sold

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Diuron	330-54-1	0.1 - 1



Chemical name	CAS number	%
Hindered amine light stabilizer	41556-26-7	0.1 - 1
Hindered amine light stabilizer	82919-37-7	0.1 - 1
2-Methyl-2H-isothiazol-3-one	2682-20-4	0 - 0.1
5-Chloro-2-methyl-2H-isothiazol-3-one	26172-55-4	0 - 0.1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Absorb spillage with suitable absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
Diuron (CAS 330-54-1)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Diuron (CAS 330-54-1)	TWA	10 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Opaque.
Odor	Slight.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	Property has not been measured.
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Property has not been measured.
Explosive limit - upper (%)	Property has not been measured.
Flash point	Property has not been measured.
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Property has not been measured.
pH	7 - 10

pH concentration	Property has not been measured.
Kinematic viscosity	Property has not been measured.
Solubility	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Property has not been measured.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Density and/or relative density	
Density	10.47 lb/gal
Relative density	Property has not been measured.
Relative density temperature	Property has not been measured.
Vapor density	Property has not been measured.
Vapor density temp.	Property has not been measured.
Particle characteristics	Not applicable, material is a liquid.
Other information	
Dynamic viscosity	Property has not been measured.
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Viscosity	50 - 150 ku
VOC	36 g/l (excluding water) (Coating) 15 g/l (including water) (Material)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	May cause an allergic skin reaction. Dermatitis. Rash.
---	--

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.
-----------------------	-----------------------------------

Product	Species	Test Results
BEHR DYNASTY® Exterior Flat Paint – Deep Base (CAS Mixture)		
<u>Acute</u>		
Dermal		
ATEmix		429600 mg/kg bw
Oral		
ATEmix		123400 mg/kg bw

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	May cause cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Not listed.	
NTP Report on Carcinogens	
Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	
Partition coefficient n-octanol / water (log Kow)	
Diuron (CAS 330-54-1)	2.68
Mobility in soil	No data available.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Diuron)
Transport hazard class(es)	
Class	9
Subsidiary hazard	-
Packing group	III
Environmental hazards	Yes
ERG Code	9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3082
UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diuron)
Transport hazard class(es)
Class 9
Subsidiary hazard -
Packing group III
Environmental hazards
Marine pollutant Yes
EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to IMO instruments Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % Subject to One-Time Reporting Requirements (Per Country)
5-Chloro-2-methyl-2H-isothiazol-3-one 1.0 % One-Time Export Notification only.
(CAS 26172-55-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

Diuron (CAS 330-54-1) Listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Respiratory or skin sensitization
Carcinogenicity

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Diuron (CAS 330-54-1)
Hindered amine light stabilizer (CAS 41556-26-7)

US. Massachusetts RTK - Substance List

Diuron (CAS 330-54-1)

US. New Jersey Worker and Community Right-to-Know Act

Diuron (CAS 330-54-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Diuron (CAS 330-54-1)

16. Other information, including date of preparation or last revision

Issue date	10-August-2022
Revision date	15-August-2025
Version #	03
HMIS® ratings	Health: 2* Flammability: 0 Physical hazard: 0
List of abbreviations	DOT: Department of Transportation. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. LD50: Lethal Dose, 50%. LOEC: Lowest observable effect concentration. MARPOL: International Convention for the Prevention of Pollution from Ships. PEL: Permissible Exposure Limit.
References	IARC Monographs. Overall Evaluation of Carcinogenicity
Disclaimer	Behr Process LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.