

*Glidden Premium Interior Paint + Primer Semi-Gloss***GENERAL DESCRIPTION**

Glidden Premium Interior Paint + Primer zero-VOC* formula provides a mildew resistant, scrubbable, and washable coating that is ideal for use on properly prepared or previously painted interior walls, ceilings and trim.

*Colorants added to this base paint may increase VOC level significantly depending on color choices.

RECOMMENDED SUBSTRATES

Concrete/Masonry Block
Gypsum Wallboard-Drywall
Plaster
Wood

FEATURES / BENEFITS

Scrubbable and washable
Thick, easy to apply formula
Good hide and coverage
Provides mildew resistant coating
Zero VOC*, low odor

*Colorants added to this base paint may increase VOC level significantly depending on color choices.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Apply when air, product, and surface temperatures are between 50°F (10°C) and 90°F (32°C).

Not recommended for use on floors. When *Glidden Premium* paint is applied to an uncoated substrate, two coats are required, with the first coat acting as the primer. For stains, water marks, and challenging conditions use an appropriate high-quality primer.

PROTECT FROM FREEZING.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae.

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)
5-Gallon (18.9L)

TINTING AND BASE INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

GLN6411N Pure White Base 1
GLN6412N Base 2**
GLN6413N Base 3**

**Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

PRODUCT DATA

PRODUCT TYPE: Latex
GLOSS: Semi-Gloss: 30 to 45 @ 60°
VOLUME SOLIDS*: 34% +/- 2%
WEIGHT SOLIDS*: 48 +/- 2%
VOC*: 0 g/L (0 lbs./gal.)

WEIGHT/GALLON*: 10.5 lbs. (4.7 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on GLN6411N.

COVERAGE: One gallon (3.78 Liters) covers approximately 400 sq. ft. (37.2 sq. meters) on primed, smooth non-porous surfaces.

Wet Film Thickness: 4.0 mils

Wet Microns: 102

Dry Film Thickness: 1.3 mils

Dry Microns: 33

Coverage does not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @77°F (25°C); 50% relative humidity.

To Touch 30-60 minutes

To Recoat: 2-4 hours

To Full Cure: 30 days

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

WASHING INSTRUCTIONS: Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

CLEANUP: Clean tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

Glidden Premium Interior Paint + Primer Semi-Gloss

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry. Remove all loose and peeling paint, dirt, grease and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Masonry and plaster surfaces must be allowed to cure for 30 days prior to painting. Uncoated substrates, repaired surfaces or lightly stained areas may require additional coats. For severe stains, water marks, and other challenging conditions, use a premium problem solving primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

CONCRETE/MASONRY BLOCK: Mortar should cure for at least 30 days and preferably 90 days prior to painting. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust prior to painting the substrate.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to painting.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface before painting.

APPLICATION INFORMATION

Stir thoroughly before and occasionally during use. When using more than one can of the same color, intermix to ensure color uniformity.

Application Method: Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat. Allow each coat to dry before applying the next coat.

Application Equipment: For smooth surfaces, use a polyester nylon brush or 3/16" - 3/8" nap roller cover. For textured surfaces, use a nylon brush or roller designed for this purpose. If applied by spray, back-brushing or back-rolling is recommended. For airless spray application, use tip size 0.015" - 0.021" and pressure range of 1500 - 2000 psi.

Thinning: DO NOT THIN.

Permissible temperatures during application:

Material: 50 to 90°F 10 to 32°C Ambient: 50 to 90°F 10 to 32°C Substrate: 50 to 90°F 10 to 32°C

PRECAUTIONS

WARNING! HARMFUL IF SWALLOWED. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *Glidden* and *The Glidden Logo* are registered trademarks of the PPG Group of Companies.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.glidden.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
2505, rue de la Metropole
Longueuil (Quebec) Canada J4G 1E5

T.D. GLN6411N 3-2016