



## BEHR PREMIUM® WOOD STAIN & FINISH STRIPPER

### NO. 64-N

BEHR PREMIUM® Wood Stain & Finish Stripper is designed to remove oil, latex-based, and 100% acrylic finishes such as semi-transparent stains, solid color stains and clear sealers. It also removes loose wood fibers to help ensure a sound surface prior to staining or painting. Created especially for use on wood deck and siding surfaces.

Intended for use on exterior latex and oil-based coatings over wood.

#### PRODUCT SPECIFICATIONS:

**Active Type:** Benzyl Alcohol

**Weight per Gallon:** 8.5 lb

**% Solids by Weight:** 13%

**VOC:** VOC: < 50 wt%

**Flash Point:** 240°F

**Coverage:** 60-75 sq ft/gal. Depending on the condition and porosity of the wood.

#### APPLICATION:

- Use product when air and surface temperatures are between 40-90 F (5-32 C).
- Wear protective clothing, goggles, and acid resistant rubber gloves and boots. Use a NIOSH approved air purifying respirator with an organic vapor cartridge.
- Completely wet the entire wood surface then apply a thick layer of stripper onto the surface. using a paint brush or a stiff bristle broom to spread evenly.
- Completely cover original coated surface.
- Allow product to stand for a minimum of 1 hour. More opaque / thicker coatings may require more time.
- Penetration varies according to coating type, thickness, and temperature. Check periodically to ensure that the coating has softened and is completely covered with the stripper.
- If the coated surface becomes dry, re-apply a light coating to dry areas. The stripper should remain wet and active until the coating softens.
- Use a stiff brush to scrub and remove all coating and residue. Some areas may require an additional application.
- Rinse thoroughly with water to remove all chemical residues before recoating. Allow surface to dry completely before recoating.
- Follow up with a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner to remove stains and rejuvenate natural wood color.
- In case of contact with painted or finished surfaces, rinse immediately with fresh water. Product will damage automotive finishes.

#### COMPLIANCE & CERTIFICATIONS

Complies with the below as of 4/1/2025

|               |     |       |     |
|---------------|-----|-------|-----|
| SCAQMD        | YES | OTC   | YES |
| CARB SCM 2007 | YES | LADCO | YES |
| CARB          | YES | AIM   | YES |
| OTC Phase II  | YES |       |     |

#### SURFACE PREPARATION:

- Be sure to have a source for water, hose with nozzle and stiff bristle broom or brush and a product such as BEHR Premium No. 63 All-In-One Wood Cleaner to open up the pores of the wood.
- DO NOT THIN PRODUCT.
- Do not apply in direct sunlight or on hot surfaces.
- Dampen nearby foliage with water and cover with plastic drop cloths.
- Conduct a small test patch in an inconspicuous area to ensure product performance.
- Prevent all rinse solution from entering storm drains.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

#### CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

#### CAUTIONS/LIMITATIONS:

- Wearing the proper Personal Protective Equipment (PPE) is essential when using this product. Use chemical-resistant gloves, goggles or a face shield, protective clothing, and any additional protection as needed.
- Protect from freezing.
- Use as is. Do not mix with other products.
- For best results, apply when air, material and surface temperatures are between 40°F and 90°F. Avoid applying in direct sunlight or to hot surfaces.
- Surfaces must be thoroughly dry before applying any type of new finish, except those finishes that can be applied to damp wood.
- Allow the wood to dry for a minimum of 24 hours in warm, dry weather.
- Prevent all rinse solution from entering storm drains.
- Shelf life under normal conditions is two years unopened.

#### GENERAL INFORMATION:

**DANGER. CAUSES SEVERE EYE DAMAGE. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC REACTION UPON SKIN CONTACT. CONTAINS: BENZYL ALCOHOL, GLYCOLIC ACID, DISTILLATES (PETROLEUM), AND POTASSIUM PYROPHOSPHATE.**

**USE ONLY WITH ADEQUATE VENTILATION. NOTICE:** Do not mix BEHR PREMIUM NO.64 Wood Stain & Finish Stripper with chlorine bleach or with any other household or industrial cleaning product or detergent. Mix only in plastic containers. Use in areas with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing mist and vapors. Wear protective clothing and eye protection. Wash contaminated clothing before reuse. Close container after each use.

**FIRST AID:** If on skin, remove contaminated clothing and rinse skin with water. Seek medical attention. If in eyes, rinse continuously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If swallowed, do not induce vomiting. Get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

