

## D1700-2EQ Series Aluminum Specialty Extension Ladders




D1700-2EQ The Equalizer® series eliminates uneven ground with the factory installed adjustable EverLevel® leveling system. This system precisely adjusts in 3/8 in increments up to 8 1/4 in, making it easy to use. The dual action feet on the ladder are for use on hard or penetrable surfaces and swivel easily. The TRACTION-TRED® D-rungs are slip resistant. The ladder has a duty rating of 225 lbs making it durable, long lasting and able to meet the demands of the job. The exclusive ALFLO® rung joint means a TWIST-PROOF® performance every time, and the lightweight aluminum makes it easy to transport.

### Features

- Alflo rung joint for Twist-Proof performance
- Integrated Leveling
- Interlocking side rails
- Mar-resistant molded end caps
- Modified I-beam rails
- Rope and pulley system
- Rope clamp ties rope to rung
- Slip-resistant shoe with Shu-lok feature and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

### Specifications

Model No.		Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D1716-2EQ		16 ft	15 ft	13 ft	13 ft	8 ft	27.5
D1720-2EQ		20 ft	19 ft	17 ft	17 ft	10 ft	32.5
D1724-2EQ		24 ft	23 ft	21 ft	21 ft	12 ft	39
D1728-2EQ		28 ft	27 ft	25 ft	25 ft	14 ft	48.5