

WHITE



WHITE



WHITE



WHITE

CAUTION! Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Do not ingest. Use gloves and safety glasses.

For emergencies, call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

¡PRECAUCIÓN! Contiene etilenglicol. Úsela sólo con la ventilación adecuada. Evite el contacto con los ojos y la piel. No lo ingiere. Utilice guantes y gafas de seguridad. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Refiérase a la Hoja de datos de seguridad (SDS) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo
www.P65warnings.ca.gov

LIFETIME GUARANTEE: DAP warrants this product for sealant purposes during the lifetime of your home, when used as directed, within one year of purchase. Call **888-DAP-TIPS**, with your sales receipt and product container available for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

QUESTIONS? ¿PREGUNTAS? Call/Llame al **888-DAP-TIPS** or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com.

DAP Products Inc.,
Baltimore, MD 21224
Made in the USA with
U.S. and globally
sourced materials.
dap.com

ALEX[®] ULTRA

ADVANCED ANTI-SHRINK SEALANT

- Lifetime Guarantee
- 15 Minute Paint Ready

**15 MINUTE
PAINT READY**



EASY WATER CLEAN UP & LOW ODOR

Paint Projects

Read back panel for cautions!
¡Lea las precauciones en el
panel posterior!

10.1 FL OZ (300 mL)

DAP[®] ALEX[®] ULTRA Advanced Anti-Shrink Sealant is a high performing acrylic latex sealant designed for the professional painting contractor. It provides anti-shrink technology, designed to reduce shrinking, creating a more durable, long-lasting seal that won't crack after painted. It applies easily, tools smoothly & adheres to a wide variety of surfaces. It's paintable in just 15 minutes & won't shine through or discolor paint. Provides a durable, waterproof & airtight seal that is mold & mildew resistant once cured. Interior/exterior use.

ADHERES TO:

Wood, Drywall, Plaster, Brick, Masonry, Glass, Most
Plastics & Metals

SPECIFICATIONS

ASTM C834

PHYSICAL PROPERTIES

App. Temp Range:	40°F to 100°F
Ideal Bead Size:	3/16" (recommended)
Coverage:	3/16" bead 55 linear ft
Skin Time:	5 minutes
Tack Free Time:	15 minutes
Full Cure Time:	24 hours
Paint Ready Time:	15 minutes
Water Ready Time:	24 hours
Odor:	Very mild
Clean-Up:	Water
VOC Content:	NCCS Calif. ARB VOC <1.5% wt/wt% (VOC 13 g/L)
Shelf Life:	12 months (unopened/ cool & dry conditions)

FOR BEST RESULTS: Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temps. & higher humidity will slow down dry time. Not for continuous underwater use, filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer rod material. Store away from extreme heat or cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at 45° angle to desired bead size. 3. Load cartridge into caulk gun. 4. Fill gap with sealant. 5. Smooth/tool bead no smaller than 1/8". 6. Clean excess wet sealant with damp sponge before it skins over. Excess dried sealant must be cut or scraped away. 7. Paintable after 15 minutes (longer in cool/humid conditions) with latex or oil-based paints or spray paint immediately. 8. Reseal cartridge for storage & reuse.