MOEN®

Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2'' IPS connections for flexible hoses only; not for use with rigid or semi-rigid supply risers(3/8'' Copper or Pex) with coupling nuts
- Installation through 3 holes, 1''min.diameter, and 4'' on center
- Includes non-metal push-down waste assembly

OPERATION

- Lever handles
- Maximum handle rotation angle is 90° to full on
- Hot side counterclockwise to open (clockwise to close)
- Cold side clockwise to open (counter-clockwise to close)

FLOW

- Water usage is limited to the maximum flow rates as indicated by corresponding product markings
  - 1.2 gpm max (4.5 L/min) at 60 psi

CARTRIDGE

- 1224 cartridge
- Nonmetallic and stainless steel material

STANDARDS

- Third party certified at WaterSense®, ASME A112.18.1/CSA B125.1, and all applicable requirements referenced therein including NSF 61/9 & 372
- Products marked with 1.2 gpm are compliant with California water efficiency regulations
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- **ADA** for lever handles


WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 years limited warranty when used in a multifamily installation
- 5 years limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations

OPTIONS (See Illustrated Parts page)

- Thin and thick deck mounting hardware kits available




Banbury®

Two-Handle 4'' Centerset Lavatory Faucet

MODELS: 84942 series

WaterSense Meets EPA Criteria
Certified by IAPMO R&T



CRITICAL DIMENSIONS DO NOT SCALE