

# Safety Data Sheets (SDSs)

Client	Sunwoda Electronic Co., Ltd.
	Floor 1,A,B,D District of Floor 2 and Floor 3 to 9 of Comprehensive
	Building, No.2 Yihe Road, Shilong Community, Shiyan Street, Bao'an
Add. of Client	District, Shenzhen City, Guangdong Province, P. R. China
Description	Rechargeable Li-ion battery pack
Model /Type	BRR-2P4S-5200S
Manufacturer	Sunwoda Electronic Co., Ltd.
	Floor 1,A,B,D District of Floor 2 and Floor 3 to 9 of Comprehensive
Add. of	Building, No.2 Yihe Road, Shilong Community, Shiyan Street, Bao'an
Manufacturer	District, Shenzhen City, Guangdong Province, P. R. China
Nominal Voltage	14.4V, 5200mAh, 74.88Wh
Date of Receipt	2020-02-25

Laboratory	Dongguan ZRLK Tes	ting Technology Co., Ltd.		
	Building D, No.2, Jin	yuyuan Mansion, No.18, Industrial West Road,		
Address	Songshan Lake High-	tech Industrial Development Zone, Dongguan,		
	Guangdong, China	Guangdong, China		
Approved Signatory	Maggie.Gao	Maggie Gao		
Inspected by	Ailis.Ma	Ailis Ma		
Censored by	Lahm Peng	Lahn Peng		



# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### **Product Identifier**

Product name: Rechargeable Li-ion battery pack Model: BRR-2P4S-5200S

#### **Other means of identification**

Synonyms:none

#### Recommended use of the chemical and restrictions on use

Recommended Use:Used in portabl electronic equipments;

Uses advidsed against:

a) Do not dismantle, open or shred secondary cells or batteries.

b) Keep batteries out of the reach of children

Battery usage by children should be supervised. Especially keep small batteries out of reach of small children.

c) Seek medical advice immediately if a cell or a battery has been swallowed.

d) Do not expose cells or batteries to heat or fire. Avoid storage in direct sunlight.

e) Do not short-circuit a cell or a battery. Do not store cells or batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

f) Do not remove a cell or battery from its original packaging until required for use.

g) Do not subject cells or batteries to mechanical shock.

h) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has

been made, wash the affected area with copious amounts of water and seek medical advice.

i) Do not use any charger other than that specifically provided for use with the equipment.

j) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.

k) Do not use any cell or battery which is not designed for use with the equipment.

1) Do not mix cells of different manufacture, capacity, size or type within a device.

m) Always purchase the battery recommended by the device manufacturer for the equipment.

n) Keep cells and batteries clean and dry.

o) Wipe the cell or battery terminals with a clean dry cloth if they become dirty.

p) Secondary cells and batteries need to be charged before use. Always use the correct charger and refer to the manufacturer's instructions or equipment manual for proper charging instructions.

q) Do not leave a battery on prolonged charge when not in use.

r) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.

s) Retain the original product literature for future reference.

t) Use the cell or battery only in the application for which it was intended.

u) When possible, remove the battery from the equipment when not in use.

v) Dispose of properly.

#### Details of the supplier of the safety data sheet:

Supplier Name: Sunwoda Electronic Co., Ltd.



Address: Floor 1,A,B,D District of Floor 2 and Floor 3 to 9 of Comprehensive Building, No.2 Yihe Road, Shilong Community, Shiyan Street, Bao'an District, Shenzhen City, Guangdong Province, P. R. China Telephone number of the supplier: 0086-13480986964 Fax: / Postcode: 518000

E-mail address: lilichong@sunwoda.com

Emergency telephone number

Company Emergency Phone Number: 0086-13480986964

# 2. HAZARDS IDENTIFICATION

#### **Classification**

Acute toxicity - Dermal	Category 3
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

#### **GHS Label elements, including precautionary statements**

#### Danger

#### Hazard statements

Toxic in contact with skin

Causes serious eye irritation

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



#### **Precautionary statements-Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

Report No.:ZKS200200286 TRF No. SDS-1A



If exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Skin

IF ON SKIN: Wash with plenty of water and soap Call a POISON CENTER or doctor if you feel unwell Take off immediately all contaminated clothing and wash it before reuse

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other information

harmful if swallowed. Very toxic to aquatic life with long lasting effects.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Chemical characterixation: Mixtures

#### **Description:**

Product: Consisting of the following components.

Common Chemical Name	Concentration (%)	CAS Number
Lithium Cobalt Oxide (LiCoO <sub>2</sub> )	10	12190-79-3
Aluminum Foil	10	7429-90-5
Lithium nickel oxide (LiNiO <sub>2</sub> )	15	12031-65-1
Graphite	18	7782-42-5
Copper	10	7440-50-8
Iron	10	7439-89-6
Phosphate(1-),hexafluoro-,lithium	2.8	21324-40-3
Ethylene carbonate	5	96-49-1
Dimelene carbonate	5	616-38-6
Lithium manganese oxide (LiMn <sub>2</sub> O <sub>4</sub> )	5	12057-17-9
Nickel	1	7440-02-0



### Safety Data Sheets (SDSs)

Polyethylene	5	9002-88-4
Ethyl acetate	0.8	141-78-6
Carbon black	0.8	1333-86-4
Lithium carbonate	0.8	554-13-2
1-Methyl-2-pyrrolidone	0.8	872-50-4

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

# 4. FIRST-AID MEASURES

### <u>First aid measures</u>

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

# 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical powder, water spray. Unsuitable Extinguishing Media:No information available. Specific Hazards Arising from the Chemical Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released: Carbon monoxide(CO) Carbon dioxide Other irritating and toxic gases. Hazardous Combustion Products Carbon oxides. Explosion Data Sensitivity to Mechanical Impact No Sensitivity to Static Discharge No Protective Equipment and Precautions for Firefighters



As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

#### Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

#### **Environmental precautions**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

#### Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Wash thoroughly after handling. Use this material with adequate ventilation. The product is not explosive.

#### Conditions for safe storage, including any incompatibilities

If the Lithium-ion Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Li-ion Polymer Battery periodically.

3 months:  $-10^{\circ}C \rightarrow 40^{\circ}C$ , 45 to 85%RH

And recommended at 0°C~+35°C for long period storage.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

The voltage for a long time storage shall be 3.7V~4.2V range.

Do not storage Lithium-ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.



Do not expose Li-ion Polymer Battery to heat or fire. Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials. Keep ignition sources away- Do not smoke. Store in cool, dry and well-ventilated place.

**Incompatible Products** None known.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **Control parameters**

Ingredients with limit values that require monitoring at the workplace:

TLV (USA)	0.02mg/m <sup>3</sup>
MAK (Germany)	0.1mg/m <sup>3</sup>

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection:** 



Tightly sealed goggles

**Body protection:** 

Protective work clothing.

Skin protection:



Protective gloves

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

	Form: Prismatic				
Physical	Color: Orange				
State	Odour: Odourless				
	Odor Threshold: No information av	vailable			
Change in co	ondition:	Not determined.			
pH, with ind	ication of the concentration	Not determined.			
Melting poir	nt/freezing point	Not determined.			
Initial boilin	g point and Boiling range:	Not determined.			
Flash Point		Not determined.			
Evaporation	rate	Not determined.			
Flammability (solid, gas)		Not determined.			
Upper/lower flammability or explosive limits		Not determined.			
Vapor Pressure:		Not determined.			
Vapor Density:		Not determined.			
relative density:		Not determined.			
Solubility in	Water:	Not determined.			
Solubility in	other solvents	Not determined.			
n-octanol/wa	ater partition coefficient	Not determined.			
Auto-ignition temperature		Product is not self-igniting.			
Decomposition temperature		Not determined.			
Odout threshold		Not determined.			
Evaporation	rate	Not determined.			
Viscosity		Not determined.			
Other Information		No further relevant information available.			

# 10. STABILITY AND REACTIVITY



<u>Reactivity:</u> Stable under recommended storage and handling conditions (see section 7, Handling and storage).
<u>Chemical stability:</u> Stable under normal conditions of use, storage and transport.
<u>Thermal decomposition/conditions to be avoided:</u> No decomposition if used according to specifications.
<u>Possibility of Hazardous Reactions:</u> None under normal processing.
<u>Hazardous Polymerization:</u> Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

**Incompatible materials:** Strong oxidizing agents. Strong acids.Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

# **11. TOXICOLOGICAL INFORMATION**

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

# **12. Ecological Information**

#### **Toxicity:**

Acquatic toxicity:

No further relevant information available.

**<u>Persistence and degradability:</u>** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No information available.

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

#### **Uncleaned packaging:**

Recommendation: Disposal must be made according to official regulations.



# **14. TRANSPORT INFORMATION**

This report applies to by sea, by air and by land;

The Rechargeable Li-ion battery pack must be of a design type proved to meet the testing requirements of the Manual of test and criteria, Part III, subsection 38.3;

The Polymer Li-ion Battery according to Section II of PACKING INSTRUCTION 965-967 of the 2018 IATA Dangerous Goods regulations 59<sup>th</sup> Edition may be transported. and applicable U.S. DOT regulations for the safe transport of Lithium-ion Battery.

Polymer Li-ion Battery was protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to short circuit;

Cell and batteries offered for transport must be packed in inner packaging's that completely enclose the cell or battery; to provide protection from damage or compression to the batteries, the inner packaging's must be placed in a strong rigid outer packaging;

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

The package must be handled with care and that a flammability hazard exists if the package is damaged; With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions.

- The International Air transport Association (IATA) Dangerous Goods Regulations.

UN number of lithium battery: UN3480;

UN Proper shipping name/Description (technical name): Lithium ion batteries; Marina nallytant(V/N); N

Marine pollutant(Y/N): N;

- The International Maritime Dangerous Goods Code 2016 Edition (Amdt.38-16)

For lithium-ion batteries by sea, provided that packaging is strong and prevent the products from short-circuit. UN number of lithium battery: UN3481;

UN Proper shipping name/Description (technical name): Lithium ion batteries Marine pollutant(Y/N): Y;

Special Provision: International maritime dangerous goods code (IMDG) 188, 230, 310, 348, 957;

- The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA

- The Office of Hazardous Materials Safety within the US Department of Transportations' (DOT) Research and Special Programs Administration (RSPA)

# **15. REGULATORY INFORMATION**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available.

Restrictions on use: No information available.

#### **Regulatory information**



Safety Data Sheets (SDSs)

CAS No.	EU	US	Japan	Canada	Austrlia	Korea	China
	(EINECS	(TSCA)	(ENCS)	(DSL/	(AICS)	(ECL)	(IECSC)
	)			NDSL)			
12190-79-3	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
7429-90-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
12031-65-1	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7440-50-8	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7439-89-6	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
21324-40-3	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
96-49-1	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
616-38-6	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
12057-17-9	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
7440-02-0	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
9002-88-4	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
141-78-6	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
1333-86-4	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
554-13-2	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
872-50-4	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed

<u>Chemical safety assessment</u> A Chemical Safety Assessment has not been carried out.

# **16. OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# <u>SECTION 1: Identification of the substance/mixture and of the</u> <u>company/undertaking</u>

# **1.1Product Identifier**

Name of Product: Rechargeable Li-ion Battery Pack

# 1.2 Other means of identification

Product Models: BRR-2P4S-5200D Nominal Voltage: 14.4V Nominal capacity: 5200mAh Nominal Power: 74.88Wh Weight: 432g

# **1.3 Recommended use of the chemical and restriction on use** Recommended Use: Rechargeable Li-ionBattery

Restriction on Use: No information available

# **1.4 Information Of Supplier:**

Company Name: Huizhou Desay Battery Co.,LTD

Address: No.15 Zone, Zhong Kai Hi\_Tech Development Zone, Huizhou, Guangdong, China Zip code: 516006 Contact person: Li Henyun Tel: 86-752-2629634

E-mail: lihy\_pow@desay.com

# <u>1.5 Emergency Telephone</u> 86-0752-2629750

# 2. Hazard(s) Identification

# 2.1 Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

# 2.2 Label elements

### 2.2.1 Signal WordDanger

### 2.2.2 Hazard Statements

Causes skin irritation Causes serious eye damage Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure

# 2.2.3 Symbol



Page1 of 12

This product is an article which contains a chemical substance. Safety information is given for exposure to the article as solid. Intended use of the product should not result in exposure to the chemical substance, this is a battery. In case of rupture: the above hazards exist.

# 2.3 Precautionary Statements

### **2.3.1 Precautionary Statements – Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Wash face, hands and any exposed skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Keep away from flames and hot surface -no smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

#### 2.3.2Precautionary Statements – Response

If exposed or connected: Get medical advice/attention. Specific treatment (see supplemental first aid/instruction on this label).

### Skin

If ON SKIN: wash with plenty of soap and water. Take off contaminated clothing and water before reuse. If skin irritation or rash occurs: get medical advice/attention if feel unwell.

#### Eye

If IN EYES: Rinse cautiously with water for several minutes, remove contact lenses, if present and easy to do, Continue rinsing. Call a POISON CENTER or doctor/physician.

### Inhalation

If inhalation: if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

#### Ingestion

If swallowed: rinse mouth, do not induce vomiting, Call a poison center or doctor/physician if feel unwell.

#### 2.3.3 Precautionary Statements – Storage

Store locked up

### 2.3.4 Precautionary Statements – Disposal

Dispose of contents/container to an approved waste disposal plant.

### 2.4 Hazards not otherwise classified (HNOC)

Not applicable

#### 2.5 Unknown Toxicity

39% of the mixture consists of ingredient(s) of unknown toxicity.

#### 2.6 Other information

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# 2.7 Interactions with other chemicals

Use of alcoholic beverages may enhance toxic effect.

Chemical Name	CAS No.	Weigh%
Graphite	7440-44-0	19
Lithium Cobalt Oxide	12190-79-3	35
Lithium Hexafluorophosphate(1-)	21324-40-3	4
Diethyl Carbonate	105-58-8	10
Propylene Carbonate	108-32-7	5
Ethylene Carbonate	96-49-1	5
Copper	7440-50-8	11
Aluminum	7429-90-5	4
Nickel	7440-02-0	7

# 3. Composition/ Information on Ingredients

# 4. First Aid Measures

### 4.1 General Advice

First aid isupon rupture of sealed battery.

### 4.1.1 Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical attention/advice.

### 4.1.2 Skin Contact

Wash off immediately with plenty of water and soap for at least 15 minutes. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists.

#### 4.1.3 Inhalation of Vented Gas

Remove to fresh air. Get medical attention immediately if symptoms occur. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

#### 4.1.4 Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

### 4.1.5 Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved. Take precaution to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personnel protective equipment as required. Wear personnel protective clothing (see section8).

# 4.2 Most important symptoms and effects, both acute and delayed

Burning sensation, Itching. Rashes. Hives, Coughing.

# 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to physician

Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization of susceptible persons. Treat symptomatically.

# **<u>5. Fire – Fighting Measures</u>**

# 5.1 Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.Dry chemical, CO<sub>2</sub>,water spray or regular foam. Move containers from fire area if you can do it without risk.

### 5.2 Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

### 5.3 Specific Hazards Arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Product is or contains a sensitizer.

# **Hazardous Combustion products**

Carbon oxides

### 5.4 Explosion Data

Sensitivity to Mechanical Impact:None. Sensitivity to Static Discharge: None.

### 5.5 Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/IOSH (approved or equivalent) and full protective gear. Move containers from fire area if you can do it without risk.

# 6. Accidental Release Measures

# 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

# 6.2 Environmental Precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillageif safe to do so. Should not be released into the environment. Do not allow to enter intosoil/subsoil. Prevent product from entering drains.

#### 6.3 Methods for containment

Prevent further leakage or spillage if safe to do so.Absorb with earth, sand or othernon-combustible material and transfer to containers for later disposal.

#### 6.4 Methods for cleaning up

Pick up and transfer to properly labeled containers.

# 7. Handling and Storage

#### 7.1 Precaution for safe handling

In case of rupture, use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

#### Incompatible products

Strong acids.Strong oxidizing agent. Strong bases.

# 8. Exposure Controls/Personal Protection

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	TWA:2mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Lithium Cobalt Oxide 12190-79-3	TWA:0.02mg/m <sup>3</sup>	-	-

### 8.1 Exposure Guidelines

ACGIH TLV: American Conference of Governmental Industrial Hygienists-Threshold Limit Value OSHA PEL : Occupational Safety and Health Administration-Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health.

# **Other Exposure Guidelines:**

Vacated limits revoked by the court of Appeals decision in AFL-CLO v. OSHA, 965F, 2d 962(11th Cir., 1992) See section 15 for national exposure control parameters.

### 8.2 Appropriate engineering controls

#### **Engineering Measures:**

Showers、 Eyewash stations、 Ventilation systems

#### 8.3 Individual protection measures, such as personal protective equipment

**Respiratory protection :**No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Eye /face protection:** if splashes are likely to occur: Wear safety glasses with side shields(or goggles). None required for consumer use.

**Skin protection:** Wear protective gloves and protective clothing. Long sleeved clothing. Imperious gloves.

**Hygiene Measure:** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. No information available.

# 9. Physical and Chemical Properties

Physical State: Solid Color: Black Odor: Odorless Odor Threshold: No information available pH: No data available Melting/freezing point: No data available Boiling point/boiling range: No data available Flash Point: No data available Evaporation Rate: No data available Flammability(Solid, gas): No data available Flammability Limit in Air: No data available Upper flammability limit: No data available Lower flammability limit: No data available Vapor pressure: No data available

Vapor density: No data available

Specific Gravity: No data available

**Solubility:** Insoluble in water

Partition coefficient: n-octanol/water: No data available

Autoignition temperature: No data available

**Decomposition temperature:** No data available

Kinematic viscosity: No data available

Dynamic viscosity: No data available

# **10. Stability and Reactivity**

Reactivity:

No data available

**Chemical stability:** 

Stable under recommended storage conditions.

Possibility of Hazardous Reactions:

None under normal processing.

Hazardous Polymerization:

Hazardous polymerization does not occur.

Conditions to avoid:

Do not subject battery to mechanical shock. Keep away from open flames, high temperature.

Incompatible materials:

Strong acids, Strong oxidizing agents. Strong bases.

Hazardous decomposition products:

Carbon oxides

# **<u>11. Toxicological Information</u>**

### **11.1 Information on likely routes of exposure**

### **Product information:**

Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:

### Inhalation:

Specific test data for the substance or mixture is not available. Corrosive by inhalation(base on components). Inhalation of corrosion fumes/gases may cause coughing, choking, headache, dizziness and weakness for several hour. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure and increased heart rate. Inhaled

corrosion substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

### Eye Contact:

Specific test data for the substance or mixture is not available. Cause burns. (based on components). Corrosion to the eyes and may cause severe damage including blindness. Cause serious eye damage. May cause irreversible damage to eyes.

### Skin Contact:

Specific test data for the substance or mixture is not available.Corrosion (based on components). Cause burns. Toxic in contact with skin.May be absorbed through the skin in harmful amounts.

#### Ingestion:

Specific test data for the substance or mixture is not available. Cause burns. (based on components). Ingestion cause burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

#### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000mg/kg ( Rat )	-	-
Propylene Carbonate 108-32-7	=29000mg/kg (Rat)	>20mL/kg(rabbit)	-

### **11.2 Information on toxicological effects**

#### Symptoms:

Erythema (skin redness).May cause redness and tearing of eyes.Itching.Rashes.Hives. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/or wheezing.

# **11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization:** May cause sensitization of susceptible person, May cause sensitization by skin contact. May cause sensitization by inhalation.

Mutagenic Effects: No information available.

**Carcinogenicity:** the table below whether each agency has listed any ingredient as a carcinogen.

Chemical Name ACGIH IARC NTP OSHA
-----------------------------------

Lithium Cobalt			
Oxide12190-79-3	A3	Group 2B	Х

**ACGIH** (American Conference of Governmental Industrial Hygienists)

A3- Animal Carcinogen

**IARC** (International Agency for research on Cancer)

Group 2B- Possibly Carcinogenic to humans

**NTP** (National Toxicology Program)Reasonably Anticipated- reasonably anticipated to be a human Carcinogenic.

**OSHA**(Occupational safety and Health Administration of the US Department of Labor) X-Present

**Reproductive Toxicity:** No information available.

- **STOT- single exposure:** No information available.
- STOT- repeated exposure: Cause damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE)
- **Chronic Toxicity:** Prolonged exposure may cause chronic effects. Repeated contact may cause allergic reactions in very susceptible persons. Contain a known or suspected carcinogen. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.
- **Target Organ Effects:** Respiratory system. Eyes.Skin. Gastrointestinal tract(GI). Blood. Central Nervous System(CNS). Kidney.Liver.Lungs.Nasal cavities.

Aspiration Hazard: No information available.

**F** = = 4 = + 2<sup>1</sup> = 14 = 2

### **11.4 Numerical measures of toxicity product information**

The following values are calculated based on chapter 3.1 of the GHS document. ATE mix(oral):6513mg/kg ATE mix(dermal): 5141mg/kg (ATE)

# **<u>12. Ecological Information</u>**

Ecotoxic	ity :	1	1	,
Chemical name	Toxicity to Aglae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propylene Carbonate 108-32-7	72h EC50: >500mg/L (Desmodesmussubspicatus)	96h LC50: >1000mg/L (Cyprinuscarpio) 96h LC50: =5300mg/L (Leuciscusidus)	17h EC50: >1000mg/L	24h EC50: >5600mg/L

Persistence and Degradability:No information available

Bioaccumulation:No information available

**Other adverse effects:** No information available

# **<u>13. Disposal Considerations</u>**

# **13.1Waste treatment methods**

# **Disposal methods:**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements. Should not be released into the environment.

# **Contaminated Packaging:**

Dispose of in accordance with federal, state and local regulations.

### California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide 12190-79-3	Тохіс

# **<u>14. Transportation Information</u>**

The transportation of primary lithium cells and batteries is regulated by the International Civil

Aviation Organization, International Air Transport Association, International Maritime

Dangerous Goods Code and the US Department of Transportation. The batteries must

meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous

Goods Regulations. 2. Meet the requirements for the US Department of Transportation

listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard

passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard

Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment",or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods"when shipped in accordance with "PI965-967 section II of IATA-DGR" or "special provision188 of IMO-IMDG Code"

#### **DOT:** NOT REGULATED

Proper Shipping Name: NON REGULATED

### Emergency Response Guide Number: 147

Hazard Class: N/A

TDG: Not regulated

MEX: Not regulated

**ICAO:** Not regulated

**IATA:** Not regulated

### Proper Shipping Name: Not regulated

Hazard Class: Not regulated

**IMDG/IMO:** Not regulated

#### Proper Shipping Name: NON REGULATED

Hazard Class: N/A

Ems No.: F-A,S-1

**RID:** Not regulated

ADR: Not regulated

**AND:** Not regulated

# **<u>15. Regulatory information</u>**

# 15.1International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA – United State Toxic Substance Control Act Section 8(b) Inventory

DSL/NDSL – Canadian Domestic Substance List/Non-Domestic Substance List

### **15.2 US Federal Regulations**

**SARA 313**: Section 313 of Title III of the superfund Amendments and Reauthorization Act of 1986(SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

	Chemical Name	CAS No.	Weight (%)	SARA313-Threshold values(%)
L	ithium Cobalt Oxide	12190-79-3	15-40	0.1

### 15.3SARA 311/312Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	l No
Reactive Hazard	No

15.4CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

# 15.5CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# **15.6 US State Regulations**

### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Nickel 7440-02-0	Cancer

### **U.S State Right-to-Know Regulations**

Chemical Name	NewJersey	Massachusetts	Pennsylvania	RhodeIsland	IIIinois
Graphite 7782-42-5	×	×	×		
Lithium Cobalt Oxide 12190-79-3	×	×	×	×	×
Diethyl Carbonate 105-58-8	×	×	×	×	×

# **15.7 International Regulations**

#### Mexico

National occupational exposure limits

Chemical Name	Carcinogen Status	Exposure Limits
Graphite		Mexico: TWA= 2 mg/m <sup>3</sup>

### Canada

WHMIS Hazard Class Non-controlled

# **16. Other Information**

#### **Disclaimer:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used material used in combination with any other materials or in any process, unless specified in the test.

Prepared By: Guangzhou MCM Certification and Testing Co., Ltd.

Issuing Date: Feb. 06, 2020

Revision Date: Feb. 06, 2020

--- End of SDS ---