

LTG4715

Gas Double Oven Slide-in

ProBake Convection®

EasyClean®

Glass Touch (SmoothTouch™)

WideView™ Window

Slide-in Design

Large Capacity (6.9 cu ft.)

SmartDiagnosis™

wi-fi Connectivity



CAPACITY	
Total Oven Capacity (cu.ft.)	6.9
Upper Oven Capacity (cu. ft.)	2.6
Lower Oven Capacity (cu. ft.)	4.3
COOKTOP	
Burner/BTU - Left Rear	9100 / 9100
Burner/BTU - Right Rear	5000 / 5000
Burner/BTU - Left Front	12000 / 10000
Burner/BTU - Right Front	18500 / 12500 (UltraHeat™)
Center (Warming Zone) (BTU)	10000 / 10000 (Oval)
Burner Simmer / BTU - Left Rear	1100
Burner Simmer / BTU - Right Rear	650
Burner Simmer / BTU - Left Front	1200
Burner Simmer / BTU - Right Front	1330
Center (Warming Zone)	2300
Cooktop Finish	Stainless Steel
UPPER OVEN FEATURES	
Broil Element (BTU/h)	14,500 / 12,500 (LNG/LPG)
Bake Element (BTU/h)	14,500 / 12,500 (LNG/LPG)
Oven Cooking	Conventional
Oven Cooking Modes	Bake, Broil, Delay Bake, Delay Clean, Pizza
Oven Control Features	Glass Touch (SmoothTouch™) and Control Knob
EasyClean®	Yes
Self Clean	Yes
GoCook Smart Oven Light	Yes (1 Light)
No. of Rack Positions	2
Door Lock	Yes
Automatic Safety Shut-Down	After 12 hours
LOWER OVEN FEATURES	
Convection Burner (BTU/h)	14,000 / 12,000 (LNG/LPG)
Convection Conversion	Yes
Convection System/Mode/Cooking System	ProBake Convection®
Oven Cooking Modes	Bake, Convection Bake, Convection Roast, Favorites, Delay Bake, Delay Clean, Proof, Warm
Oven Control Features	Glass Touch (SmoothTouch™)
EasyClean®	Yes
Self Clean	Yes
GoCook Smart Oven Light	Yes (1 Light)
No. of Rack Positions	4
Door Lock	Yes
Automatic Safety Shut-Down	After 12 hours
CONTROL	
Cooktop Control Type	Front Tilt-Control Knobs
Oven Control Type	Glass Touch (SmoothTouch™) and Control Knob
Display	VFD
Language	English

Clock	12 hr or 24 hr (option)
Temperature Unit of Measure	Fahrenheit / Celsius
Cooking Complete Reminder Volume	Beeper
APPEARANCE	
All Available Colors	Matte Black Stainless Steel, Black Stainless Steel, Stainless Steel
Handle/Knobs	Matte Black Stainless Steel, Black Stainless Steel, Stainless Steel
Knobs	Aluminum
Oven Door Feature	WideView™ Window
PrintProof™ Finish	Yes (only LTG4715BM & LTG4715BD)
SMARTTHING®	
SmartDiagnosis™	Yes
wi-fi Connectivity	Yes
DIMENSIONS/CLEARANCES/WEIGHT	
Shipping Weight (lbs)	280
Product Weight (lbs)	225
Cabinet Width (in)	30"
Overall Depth (in) - including handle	28 15/16"
Overall Height (in) - including backguard	37 7/8"
Overall Width (in)	29 7/8"
Oven Interior Dimensions (Upper) (in) (W x H x D)	24 13/16" x 9 1/4" x 20"
Oven Interior Dimensions (Lower) (in) (W x H x D)	24 13/16" x 14 1/4" x 20"
Height to Cooking Surface (in)	36"
Carton Dimensions (in) (W x H x D)	31 31/32" x 51" x 30 17/32"
POWER/RATINGS	
Amp at 120V	8.3A
kW at 120V	996W
Requirements	120 VAC
ACCESSORIES	
Griddle Plate	Yes
Gliding Rack	1
Standard Rack	2
Work Grate	Yes
Meat Probe	Yes
Spray Bottle	Yes
Scouring Pad	Yes
WARRANTY	
Parts & Labor	1 Year
UPC CODES	
LTG4715BM (Matte Black Stainless Steel)	048231340205
LTG4715BD (Black Stainless Steel)	048231340199
LTG4715ST (Stainless Steel)	048231340182